

Douglas County Surveyor's Record of
Government Corners Renewed

T. 22 S. T. S. R. 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

B.A. Shaner
For: U.S.
B.L.M.
M 42 - 68

Section Corner R S 1 | S 6 R
5W S 12 | S 7 4W 133

Found - 1959 Co. Surv. Brass Cap mkd., as above, See Ren. #57.
18" Chinquapin BT. scribes visible bears S.30°E. 14.8 ft.
24" Cedar BT., scribes visible bears N.16°E. 46.8 ft.
12" D.Fir BT., bears N.62°W. 13.0 ft. (Rec. N.64°W.)
40" Orig. D.Fir BT Windfall, shows rotted face, bears S.18°E. 44.9 ft.
Orig. 30" Doug.Fir BT., stump hole only, bears N.70°E. 33.7 ft.
I scribed an 18" Hemlock "T22S R5W S12 BT", bears S.26°W. 112.6 ft.
Found - 4"x4" Post scribed S1, S6, S7, S12 laying by Brass Cap.

8/30/72

1/4 Corner to Sec. 36, T21-5W. & Sec. 1, T22-5W. 134

Found - 1" Iron Pipe set in ground & a partially rotted 4"x4" Post Mkd:
"1/4 S" with scribing visible laying beside the iron pipe.
Set Brass Cap Mkd: T21S, T22S, R5W, W.M. 1/4 S S36, S1 1972
Found - Orig. Doug. Fir BT, now 56", bears N.8°E. 68.4 ft.
(Record N.10°E. 66.0 ft.)
62" Orig. Doug. Fir BT., scribes visible, bears S.52°E. 115.0 ft.
(Record 112.0 ft.)
20" Doug. Fir BT. bears S.24°W. 80.5 ft. (Rec. 79.6') Ren. #14, T21-5.

8/30/72

1/4 Corner Sections 11 and 12. 135

Found - Original 40" D. Fir, face vis. Bears N.41°W., 132.0 ft.
Set - Brass cap mkd. T22S, R5W, WM S11, S12 1/2 S 1972.
New BT's - 8" D. Fir, Bears N.19°E., 12.9 ft. Scribed 1/2 S S12 BT.
10" Madrone, bears N.77°W., 20.5 ft. scribed 1/2 S S11 BT.
Note - North-south fence line runs 1 ft. east of the brass cap. East-west fence line, now partially destroyed, approx. 30 ft. north of the corner. This corner is the same as recorded by McGillicuddy in his 1952 survey as per both BT's and fence lines.

1/4 Corner Sections 11 and 2. 136

Found - 5" x 5" post scribed 1/2 S on west face.
Mound of stone approx. 1 ft. SE of the post. I found no markings on the stones nor any original BT's. Same as described by McGillicuddy.
Set - Brass cap mkd. T22S, R5W, WM 1/2 S S2, S11 1972.
New BT's - 15" D. Fir, bears N.56°E., 15.5 ft. Scribed 1/4 S S2 BT.
48" D. Fir, bears S.67 1/2°W., 8.3 ft. scribed 1/4 S S11 BT.

1/4 Corner Sections 10 and 11. 137

Found - 1" I. Pipe and a 4" x 4" post Ren. No. 85
40" Orig. D. fir, face vis. bears N.55 1/2°E., 20.7 ft. (Record N.50°E., 22.4 ft.)
36" Orig. D. fir, face vis. bears S.64 1/2°W., 20.3 ft. (Record S.65°W., 21.1 ft.)
Set - Brass cap mkd. T22S, R5W, WM S10, S11 1/2 S 1972. Placed iron pipe beside brass cap.

Section Corner Secs. 10, 11, 15, 14 138

Found - 1 1/2" iron pipe 16" above ground and a 3" x 3" post scribe vis. Ren. No. 40
36" D. Fir, partly open no scribe vis. bears N.10°W., 2.5 ft. 84
30" D. Fir, scribing vis. bears N.25°E., 26.0 ft. (record 25.0 ft.)
28" D. Fir, face vis. bears S.29°W., 42.8 ft. (record S.26°W. 41.9 ft.)
36" D. Fir stump, partially uprooted, face vis. bears S.23 1/2°E., 50.7 ft. (record S.31°E., 47.5 ft.)
Set - Brass cap mkd. T22S, R5W, WM S10, S11, S15, S14 1972. Placed iron pipe beside brass cap.

RE-RENEWED, SEE CORNER NO. 133

Bruce A. Shaner
For U.S. Bureau of Land Management
M 49 - 12
September 18, 1972

Jan 1973

FND. OK 2-91
M111-54