

Douglas County Surveyor's Record of  
Government Corners Renewed

22 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

139

1/4 Corner Sections 15 and 14  
Found - 3/4" Iron pipe 16" above ground. Ren. No. 39  
40" orig. D. Fir, stump, face and scribing vis. Bears N.15°W.,  
33.0 ft.  
RE-RENEWED, SEE CORNER NO. # 207  
32" D. Fir, face vis. bears N.86°E., 47.8 ft.  
22" D. Fir, face vis. Bears S.86 1/2°E., 45.1 ft.  
Set - Brass cap mkd. T22S, R5W, WM S15, S14 1/2 S 1972.  
F.D. 1/80  
D. PERKINS  
M105-54

Bruce A. Shaner  
For U.S. Bureau of  
Land Mgt.  
M 49 - 12  
Sept. 18, 1972

140

Center 1/4 Section 11  
Set - Brass cap mkd. T22S R5W, WM C 1/4 S11 1972  
BT's - 8" D. Fir, scribed "C 1/4 S11 BT", bears N.56°W., 41.7 ft.  
14" Madrone, scribed "C 1/4 S11 BT", bears N.75°E., 58.9 ft.

1/4 Corner Sections 3 and 10.  
No evidence found of original corner.  
Set Corner by single proportionate measurements.  
Set - 1" Iron pipe with brass cap stamped "T22S, R5W, 1/4 S3, S10, RLS 934, 1973"  
New BT's - 26" Madrone, bears S1°W., 13.2 ft. scribed 1/4 S10 on BT.  
16" Madrone, bears N.33°W., 24.6 ft. scribed 1/4 S3 BT.  
RE-RENEWED, SEE CORNER NO. # 192

Victor Melind for  
Floyd & Lena Rust  
M 48 - 78  
June 1973

142

E. 1/16 Corner between Sections 3 and 10.  
Set - 2" x 30" Iron pipe.  
BT - D. Fir, 9", bears N.19°E., 16.0 ft.

143

1/4 Corner for Sections 27 and 34.  
Set - Brass cap mkd. T22S R5W 1/4 S27 S34 P.E. 2128  
BT's - 18" Oak, bears N.43°E., 23.5 ft. scribed 1/4 S27 B.T.  
9" Oak, bears S.20°E., 18.8 ft. scribed 1/4 S34 B.T.

W. S. Barnes  
for Rex Applegate  
M 53 - 75  
July 1974

144

Section Corner for Secs. 17, 16, 20 and 21.  
Found - 3/4" Bolt. Ren. #29  
Orig. Oak BT, S.15°W., 46 lks. was here 15 or 20 yrs. ago.  
No trace of trees shown on Ren. #29 was ever found by me.  
Area has been cleared & burned. Only the bolt remains.  
New BT - 40" Inc. Cedar, bears N.71°W., 16.8 ft.  
Set - 5/8" Rebar on line.

WILFORD N. HAINES  
for: Field & Stream Real Est. Inc.  
Aug. 6, 1975  
M 57 - 66

145

1/4 Corner for Secs. 16 and 21.  
Set - 5/8" Rbar on line.  
Found - 1" I.P. in mound of stone. (no record)  
20" Bl. Oak, N.15°W., 59 lks., now dead, 40.0 ft. to center  
of tree.  
2 oaks that look like BT's probably marked at least 20 years ago:  
10" W. Oak, N. 3 1/2°E., 18.6 ft.  
14" B. Oak, S.80°W., 45.5 ft.

146

1/4 Corner for Sections 13 and 24.  
Found - 6" Cedar, now 44". (see M105-27 FOR FOLDER)  
Set - 5/8" Steel rod, S.45°W., 35 lks. from bearing tree.

WILFORD N. HAINES  
for: Jim Whipple  
August 15, 1975  
M 57 - 71

147

Witness corner for 1/4 Corner, Secs. 24 and Sec. 19-T22-4  
1/4 not found. Falls on steep bank. Did not set.  
Set - 5/8" steel rod, 59.5 ft. south.  
Scribed - 22" Fir, N.57 3/4°W., 6.9 ft.

8/15/75

148

#148 NOT USED