

**Douglas County Surveyor's Record of  
Government Corners Renewed**

22 T. S. 5 R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

L.E. Monrean  
J H C  
C.S. 57/39  
11/13/75

S.W. Cor. D.L.C. 43 FD. OK. PEE. PEEL  
2/16/88 M 105-69 REN# 120 149  
 Found: 10" x 12" x 18" stone set below surface, plow share in buried mound  
 of stone with fence post along side. Original bearing tree not found.  
 Set: - Brass cap at S.W. cor. DLC#43 stamped T 22 S R 5 W  
 "COUNTY SURVEYOR'S OFFICE  
 1975 S.W. Cor  
D.L.C. 43  
 Cap is approx 1 ft. above ground, in mound of stone approx 1 ft. high and 3 ft.  
 dia. at base. Cap is approx 4 ft east of fence running N31°E, in open field.  
 BT's- 30" Dia. Fir tree bears N 55 1/2°E., 544.9 ft., scribed "SW Cor DLC 43CSBT"  
11/13/75

Clell Goodwin  
Gary Langlitz  
Vic Cangie  
Lenora Ladig  
CS 57/39  
12/15/75

Sec. corner to S 32 And S 33 only REN# 108 150  
 Found- A 1" X 30" I.P. with brass cap properly stamped (1965 County Surveyors)  
 projecting out of ground 8".  
 From which, an orig. 12" now 42" grand fir opened to reveal orig. scribe marks  
 and rescribed bears N. 23°E., 7.9 ft. The stump hole from Roger's 8" fir  
 scribed in 1965 bears N. 29°W., 45.5 ft. ( This tree is now blown down)  
 There is no sign of the original dogwood Bt.  
 New BT: The most southerly of four trunks of a maple with a common base, an  
 8" trunk scribed "CC T 22 S R5W S32 CS BT" in a double blaze bears  
 N. 64°W., 36.9 ft. # 204  
 The easiest route to this corner is through the property of Mr. Mays on  
 Hayhurst Rd. and then N.W. up the creek bed. Corner lies about 300' from the  
 Rd. and 40' south of the creek. Compass Declination 20° East 12/15/75

Interior angle corner DLC 38 FD. OK. PEE. PEEL  
2-8/16/88 M 105-69 REN# 119 151  
 Found- 5/8" x 36" I. Rod firmly set in a small mound of stones, from which  
 bearing trees marked by Haines in 1967 bear as follows:  
 An 8" now 9" W. Oak fork of a 3-forked clump bears N 39°E., 121.7 ft. (rec. N 39°  
 E., 120.7) alive and well-healed. (note: our distance taken to center of  
 clump) N 31°E  
 A 10" now 21" maple bears in 79°E., 91.0 ft. alive with scribe marks visible  
 on partially healed blaze.  
 We also find the remains of an oak at the proper position for the orig. SE  
 bearing tree.  
 Set- A 1" x 30" iron pipe, set 27" in the ground and surrounded by stones, with  
 brass cap attached marked T 22 S R 5 W  
 DOUGLAS CO. SURVEYOR INT. COR. <  
 1975 DLC 38  
 Note: this corner is located in an open field at the base of a hill approx.  
 one half mile east of the Mt Baldy sawmill, north of Yoncalla. 12/15/75

L.E. Monrean  
P.L. Earle  
12/30/75  
C.S. 57/39

1/4 corner to Sec. 32 & 33 REN# 5 152  
 Found- A 5/8" dia, Iron rod ( not of record) (SEE H. EN. 3)  
 From which: An 8" dia. d. fir bears N59°E., 12.9 ft. Tree is blazed and  
 scribed "1/4 S33 BT". (Not of Record)  
 A 25" dia. D. Fir bears N60 1/2°W, 27.6 ft. Tree has good blaze, I open and  
 find scribing "1/4 S32 BT" (Not of record) (SEE HAINES FB #110)  
 NOTE: no original or record evidence found. The unrecorded evidence  
 found appears to be approximately 8 years old. 12/30/75

L.E. Monrean  
J. H. Cook  
Surveyors Office  
Feb. 1976  
C.S. 59/8

Section Corner for Secs. 4 and 5 only, T23-5 153  
 Found - 1959 County Brass cap, out of ground, on edge of road stamped  
 "County Surveyors Office, T22S R5W S5 S4 T23S 1959. Ren. #129  
 Orig. 18" now 38" Fir stump bears S. 58°E., 33.0 ft. scribed "R5W  
 T23S 4"  
 12" now 16" Red Fir, bears S. 45°E., 68.4 ft. (Rec. 89.4 ft.) Tree  
 has good blaze, tagged  
 8" now 11" Red Fir, bears S. 16 1/2°W., 14.0 ft. (Rec. S. 19°W.) Tree  
 has good blaze. Tagged.  
 Re-Set - Brass cap at section corner, cap stamped as noted. Corner lies  
 on edge of road. Set fence post and sign beside monument.  
 Compass Mag. Dec. 20°E. 2/18/76