

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 22 T. S. R 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
T. Plouff
Feb. 9, 1982
C.S. 61/30

170

Section corner for Sec. 24 and 25; and Secs. 19 & 30 of T.22-4
Found - 1959 County Surveyors brass cap, properly mkd. set firmly in ground protruding 4" out of ground. Ren. #58
Stone set by Theil with "+" on top, mentioned in Ren. #58 just east of brass cap. Stone protrudes 4" out of ground. Orig. 10" now rotted 28" fir stump previously opened bears N.52°W., 21.8 ft. Scribing no longer visible.
6" now 13" fir bears S.32°E., 26.1 ft. (Rec. S.30°E.) with well healed double blaze. Ren. #58
7" now 13" fir bears S.4 1/2°W., 41.0 ft. (Rec. S.6 1/2°W.) with well healed double blaze. Ren. #78
All other bearing trees have been destroyed by recent logging.
Note: Due to wire fence & 2 steel fence posts being within approx. 2 ft. of brass cap, all of my compass bearings were taken on lines projected back approx. 10 ft. from brass cap.
New BT - 15" fir scribed "T22S R4W S30 CS BT" in double blaze bears S.63°E., 54.6 ft.
Sketch in C.S. file.

2/9/82

Eugene A. Bloom
RLS: 492
For: Robert Lee &
Nora May Allen
January, 1986
M 100 - 25

171

1/4 Section Corner to Sec. 31 (T22-5) and Sec. 36 (T22-6)
SET - A 5/8" by 30" Iron rod, with plastic cap mkd. "AA Surveying Incorporated".
BT's - A 10" C. Fir, bears S.66°W., 33.1 ft. dist., scribed "1/4 S36 BT"
A 21" W. Fir BT., bears S.15°E., 35.2 ft. dist., scribed "1/4 S31 BT"
NOTE - Corner lies 6.7 ft. south of fence.

172

North 1/4 Corner for Section 1 only of T.23-5
Found - A 2 3/8" dia. County brass cap on a 1 1/4" O.D. I.P. is firmly set and protrudes 12" from the ground. Ren. #130
Ren. No. 2 (of T.23-5) describes an iron bar 3/8" x 1 1/2" x 48" as the corner monument. An iron bar measuring 1/2" x 1 5/8" firmly set and protruding 11" above ground bears S.05 3/4°E., 1.8 ft. from the brass cap monument.
(Both objects above are set in a north-south fenceline.)
Orig. BT, a 28" Y. Oak, now a 39" DBH black Oak previously opened now rotted, no clear evidence of blaze or scribing bears S.37 1/2°W., 36.3 ft. (Rec. S.36°W., 36.3 ft.)
(Other Orig. BT removed by logging cat work)
A Black oak, 10" dia. now a 12" DBH W. Oak bears S.35°W., 6.9 ft. (Rec. B. Oak, S.39°W., 6.9 ft.) Tree has a fully healed double blaze. Ren. No. 2 of T.23-5
(Other BT per Ren. No. 2 (T.23-5) not found due to logging cat work.)
A 6" R. fir, now a 12" dia. 1 foot tall fir stump with partial lower blaze remaining, no scribing found, bears S.15°W., 14.4 ft. (as per record, Ren. No. 59 of T.23-5)
A 5" R. fir now a 25" dia. fir stump 6" tall with partial lower blaze remaining, no scribing visible, bears S.60°E., 36.7 ft. (as per record, Ren. No. 59, T.23-5)
No new monument set. Brass cap monument agrees best with remaining original evidence.
New BTs - An 8" DBH D. fir scribed 1/4 S1 CS BT on a double blaze bears S.83 3/4°E., 57.6 ft. distant.
A 7" DBH D. fir scribed 1/4 S1 CS BT on a double blaze bears S.12°W., 40.6 ft. distant.
Corner is located in a north-south fenceline on a north-west slope approx. 75ft. east of a cat road.

173

South 1/4 Corner for Section 36 only.
Found - 1960 Doug.Co. brass cap/I.P. bent and leaning 0.8ft. northwest of plumb position, protrudes 7" above ground. Ren. No. 67
Orig. BT, 24" now 40" B.Oak shows a single well healed face bears N.60°W., 4.0 ft. (Rec. N.60°W., 2.6 ft. to face.)
17" now 22" D. fir with a fully healed double blaze bears N.10°E., 17.5 ft. Ren. No. 67
13" now 21" D. fir with a fully healed double blaze bears N.31°W., 26.1 ft. (Rec. N.33°W., 26.1 ft. is to center of trunk at level distance.) Ren. No. 67.

*F10.01c 10/92
K.HOFFINE M 116-2*

Douglas County Surveyors Office
Deputies - Randall Smith - Stephen Flause
February 24, 1986
C.S. 62/31