

Douglas County Surveyor's Record of  
Government Corners Renewed

T 22

T. S.

R 5

R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORG. 21881

187

1/4 Corner for Sections 9 and 10

Found - A firmly set 1/2" iron rod with eye on top protrudes 6" above ground, eye bolt leans 6" west of plumb. (Source unknown).

*FND. OK  
2-91 M 111-54*

6" now 30" dia. rotting D. fir snag with a previously opened blaze, scribing visible "1/4 S" bears N.56°W., 16.5 ft. (agrees with record.) Original BT.

5" now 9" dia. madrone partially rotted blaze opened and scribing "S10" found., bears S.49°E., 9.2 ft. (Rec. S.49°E., 10.0 ft. dist. is a slope measurement) Per Ren. #117

Set - A brass cap iron pipe monument was not set. Corner lies in a steep rocky area with shallow soil.

New BTs- 6" dia. maple double blazed and scribed "1/4 S9 CS BT" bears S.6°W., 67.6 ft.

5" dia. madrone bark scribed "1/4 S10 CS BT" bears N.6°E., 22.2 ft.

Corner lies on steep westerly slope.

(Bearings and distances of found BTs taken to plumb position of eye bolt.)

11/3/88

Douglas County  
Surveyors Office  
Randall Smith  
Steven Flaue  
Nov. 3, 1988  
C.S. 62/59

David H. Wellman  
For: Weyerhaeuser Co.  
October 28, 1988  
M 107 - 26  
C.S. 63/85

1/4 Corner for Section 3; and Section 34 of T.21-5

Found - 72" rotted fir stump with axe marks, N.8°E., 72 lks. (1855 BT)

Set - 1" x 36" iron pipe with yellow plastic cap inscribed 'Weyer Co'.

New BTs - 14" fir, N.38°W., 28.9 ft. to 'W' nail and tag scribed '1/4 S34BT'.

15" fir, S.2°W., 42.8 ft. to 'W' nail and tag scribed '1/4 S3BT'.

14" fir, S.70°W., 60.8 ft. to 'W' nail and tag scribed '1/4 S3BT'.

*FND. OK BY BAKER 9-93 M 118-10*

10/28/88

188

Section Corner for Secs. 2, 3, 10 and 11

Found - 1958 County brass cap 2 3/8" dia. on a 1 3/8" dia. galv. I.P.

Ren. No. 41

60" cedar stump with fragmentary scribing bears N.78°E., 17.2 ft. to face. Orig. BT.

40" fir stump no scribing visible bears S.8°W., 68.0 ft. Orig.

20" now 26" fir stump 4 1/2 ft. high with well healed double blaze bears N.34°E., 39.5 ft. Ren. No. 41

16" now 28" fir with well healed double blaze bears N.13°W., 21.2 ft. Ren. No. 41

18" now 24" fir with healed blaze bears S.3°W., (Rec. S.8°W) 53.4 ft. Ren. No. 41

18" now 30" fir stump 1 1/2 ft. high bears S.65 1/4°E., (Rec. S.60 1/2°E) 120.8 ft. Ren. No. 41.

*FND. OK 2/91  
M 111-54  
FND. OK 9-93 BY BAKER  
M 118-10*

New BT - 9" D. fir double blazed and scribed "S11 CS BT" bears S.53 1/2°E., 61.5 ft.

Fences running north and west intersect at corner. Clear cut to east.

11/20/90

Douglas County  
Surveyors Office  
Larry Monrean  
S. J. Flaue  
Nov. 20, 1990  
C.S. 64/11

Section Corner for Sections 5 and 6 only of T.23-5

CORNER REPORT ONLY

Found - Corner is a 1982 BLM alum. cap in good condition.

18" D. fir bears S.7 1/2°E., 44.2 ft. BT tag. BLM

16" D. fir bears S.11°W., 33.7 ft. BT tag. BLM

20" D. fir bears South 17.3 ft. BT tag. NO record.

Metal fence post 1.5 ft. west. NO record

Haines T-Iron 1.8 ft. west.

Ren. No. 127

Painted faces and wrote Bt on tree trunks of BTs with flourescent orange paint. Corner lies on steep west slope approx. 100 ft. east of creek flowing north.

5/90

190

Ken Hoffine  
For: Lone Rock  
Timber Co  
May, 1990  
C.S. 63/127

*FND. OK 10/92  
HOFFINE, M 116-2*

Ken Hoffine, LS 2291  
For: Lone Rock  
Timber Co.  
Aug. 1990  
C.S. 63/127

1/4 Corner for Sections 35 and 36

Found - Corner is a 1962 County brass cap 0.5 ft. above ground in good condition. Ren. No. 74

9" D. fir bears N.88°E., 24.0 ft. well healed face and BT tag.

16" D. fir bears S.18°W., 8.4 ft. well healed face and BT tag.

New BT - Put Lone Rock Timber location tag on 6" round treated fence corner bearing S.49°E., 1.7 ft.

Painted faces and wrote BT on tree trunks of BTs with flourescent orange paint. New fence corner bears S.49°E., 1.7 ft. Fence runs east and south from corner. Corner lies on small flat bench on east slope approx. 200 ft. west of south flowing creek.

8/90

191