

Douglas County Surveyor's Record of
Government Corners Renewed

T. S. 6 R. W. W. M.

✓ COR. OF 1, 6, 31, 36 ON TP. LINE ON N.E. COR. TP. 22 - 6
Renew from old B.T.s
Set in a 1 1/2" x 30" C.I.P. from which
A 12" Fir bears S. 15° W. 2.10 chs. dist.
A 24" W. Oak bears S. 13° W. 2.10 chs. dist.
A 20" W. Oak, bears S. 7 1/2° E. 1.45 chs. dist.

RE-RENEWED, SEE CORNER NO. 59

1

✓ N.E. COR. OF D.L.C. NO. 44., 30L. EMBLEY CL.
Renew from old B.T.s
Set in or buried a 8" x 10" x 14" sandstone, from which
A 24" Oak, bears N. 10° W. 7.25 chs. dist.
A 12" Oak, bears N. 12° W. 7.61 chs. dist.
A 8" Apple, bears S. 61° W. 3.26 chs. dist.

2

✓ N.W. COR. OF CL. 44
Renew from old B.T.s
Set in a 1" x 30" Iron pipe, from which
A 18" Fir, bears S. 46° E., 0.395 chs. dist.
A 36" Fir, bears N. 59 1/2° E., 0.470 chs. dist.
A 24" Oak, bears S. 79° W., 0.54 chs. dist.

3

✓ EXTERIOR "L" COR. OF CL. 44
Renew from old B.T.s
Set in a 3" x 20" Steel Wagon skein, from which
A 60" Fir, bears N. 25° W., 0.35 chs. dist.
A 10" Fir, bears S. 39° E., 0.615 chs. dist.
A 12" Fir, bears N. 58° E., 0.48 chs. dist.

4

✓ INTERIOR "L" COR. CL. 44
Renew from old B.T.s and set in a 8" x 12" x 12" sand stone,
from which
A 24" Oak, bears N. 15° W., 1.68 chs. dist.
A 20" Oak, bears N. 50° W., 1.71 chs. dist.

5

✓ COR. OF SECS. 7, 8, 17, 18
Renew from old B.T.s. Set in a 1/2" x 1 1/2" x 36" Iron Bar & a
2" x 12" x 30" Fir stake, from which
A 20" Maple, bears S. 77° E., 92 lks. dist.
A 60" Fir, bears S. 32 1/2° W., 57 lks. dist.

RE-RENEWED, SEE CORNER NO. 70

6

✓ S.E. COR. OF JOB. DAISLEY D.L.C. NO. 37
Renew from old B.T.s. Set in a 3/8" x 1 1/2" x 40" Iron Bar
with looped end, from which
A 40" Fir, bears N. 13° W., 30 lks. dist.
A 40" Fir, bears N. 30° E., 35 lks. dist.

7

✓ COR. BETWEEN SEC. 8-9
Renew from old B.T.s. Set a 3/4" round iron bar 18" long,
from which
A 24" White Fir, bears N. 100° E. 16.2 feet dist.
A 18" White Fir, bears N. 100° E. 19 feet dist.

RE-RENEWED, SEE CORNER NO. 72

8

✓ SEC. COR. BETWEEN SEC. 14 - 15
Replaced from original Hemlock B.T. now 40" bearing copper
scribemarks and stool of Dogwood in position of old dogwood B.T.
Original field notes called for 24" Hemlock N. 30° E. 29 lks. &
5" Dogwood N. 80° W. 22 lks. Actually found that these trees
were N. 30° W. and S. 76° E. distances checked O.K.

Set 6" x 6" x 2 1/2" sandstone 12" in ground chisled X-1/2 for
corner with 4" x 30" Yew wood post alongside scribed 1/2.
3.14 15 - C.S.
A 30" Fir, bears S. 69° 35' E., 44 lks. dist scribed
3.14 C.S., B.T.
A 16" Fir, bears S. 15' E. 35 lks. dist. scribed
3.14, C.S., B.T.

RE-RENEWED, SEE CORNER NO. 66

9

June 26, 1924
H. I. Epstein
C. S.
M. C. Powker
Phillip Snell
Don Blackford
Ben P. Irvine
Jan 16, 1928
W. S. Clear
Geo. Montgomery
Witness c.s. 22/25

F. C. Frear, Dep. Co. Sur.
J. W. Harness
Earl Prier
F. C. Frear D.C.S.
Robert Lancaster
E. Snell, Witness
Feb. 7-9, 1919
Wit. c.s. No. 3, p. 44555

Witnesses
Dec. 1917
c.s. 1/4, 16, 13, 19, 23, 5 m-6