

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 6 R. W. W. M.

ROSE-CHAPMAN CO., EUGENE, ORE. 97008

SEC. COR. 10-11-14-15

O.B.T.s as called for in original field notes, both down. I with scribe marks well preserved and the other so badly charred that no scribe marks remained but position checked. Set 2" x 36" iron pipe for corner "B" in ground. A 3" W. Oak, bears S. 11° E. 280 lks. on slope of 21° 41' scribed T. 22S. R. 6W., S. 15., C.S. P.T. 10
A 24" W. Oak, bears S. 65° W., 143 lks. on slope of 19° 10' scribed T. 22S., R. 6W. S. 15., C.S., B.T.
A 30" W. Oak, bears S. 21° W., 202 lks. on slope of 18° 30' scribed T. 22S. R. 6W., S. 15., C.S., B.T.

N.W. COR. OF DONATION LAND CLAIM #41 (HENRY CHRISTIAN)

Replaced from original B.T.s as called for in original notes. Both trees gone but scribe marks B.T. visible on stump. Set a cam shaft with gear attached driven flush with the ground for corner. 11
An 8" W. Oak, S. 49° E. 461 lks. scribed Cl. 41., C.S. P.T.
An 20" W. Oak, S. 82° E. 450 lks., scribed Cl. 41., C.S., B.T.

S.W. COR. OF CHAS. F. PUTMAN, D.L.C. 39

Set 1 1/2" x 30" iron pipe driven flush with ground from original B.T.s., Remarkd original B.T.s. 12
36" Fir, S. 5° E., 30 lks. dist.
40" Fir., S. 5° W., 30 lks. dist.

SEC. COR. 15, 16, 21, 22

Crowned out old B.T. 40" Fir, S. 45° E. 11 lks. dist. Scribe marks plain. The burned out stump of an old Maple bears N. 85° W. 41 lks. This may be remains of an old B.T. as the original field notes call for a maple N. 85° W. 51 lks. Set 8" x 6" x 20" sandstone for corner chisled X and having 3 notches on each face. 92
An 8" Fir, bears N. 30° W. 49 lks. dist. scribed T. 22S. R. 6W. S. 15., C.S. P.T. 13
An 14" Fir, bears S. 25° E. 52 lks. dist. scribed T. 22T. R. 6W. S. 15., C.S. P.T.
An 15" Fir, bears S. 15° E. 47 lks. dist. scribed T. 22S. R. 6W., S. 22, C.S. P.T.
An 16" Fir, bears S. 38° W. 48 lks. dist. scribed T. 22T. R. 6W. S. 21, C.S. P.T.

S.W. COR. CL. 41, HENRY CHRISTIAN 92

Position computed by proportional distance between N.W. cor. Cl. 41 & S.E. corners of D.L.C. 39. Set sandstone 6" x 10" x 18" set 10" in ground chisled X on top. 14
18" Fir, bears S. 59° 37' E. 169.2 lks. dist. scribed Cl. 41. C.S. B.T.
30" W. Fir, bears N. 44° 50' E. 305.5 lks. dist. scribed Cl. 41., C.S. B.T.

S.E. COR. CL. 39

Position determined by intersection of E. & S. lines of the claim. Set boulder 7" x 10" x 10" flush with the ground. 15
A 20" fir, S. 19° E. 89.8 lks. dist. scribed Cl. 39. C.S. B.T.
A 20" Fir, N. 19° W. 68.9 lks. dist. scribed Cl. 39, C.S., B.T.

Ben B. Irvine Deputy
Dec. 1927 & Jan 1928
W. S. Greer
Geo. Montgomery
Witnesses

Vol 3, Page 284
C.S. File 22/25

Vol 3, Page 284

C.S. File 22/25

Ben B. Irvine Deputy County Surveyor
Jan. 1928
W. S. Greer
Geo. Montgomery
Witnesses

RE-RENEWED, SEE CORNER NO. 92

RE-RENEWED, SEE CORNER NO. 92

RE-RENEWED, SEE CORNER NO. 92

NOT RENEWED
B.M.
BRASS
CAP