

Douglas County Surveyor's Record of
Government Corners Renewed

22

T. S.

6

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Center $\frac{1}{4}$ corner to sec. 30.

37

Set angle iron with brass cap at intersection of centerlines inscribed, survey point - Wilford N. Haines 239.

Scribed two trees:

8 inch Fir, N. 83°W., 23.3 feet.

12 inch Fir, N. 84°00'E., 21.3 feet.

Wilford N. Haines
1955. C. S. File No. 42-13.

Northwest corner of section 11. (2, 3, 10 and 11).

38

Found no trace of iron pipe for corner. Found Ash tree that looked like BT.

Set 36 inch angle iron with brass cap inscribed - Survey point - Wilford N. Haines No. 239, N. 23°W., 99 lks. from the ash tree.

Nailed a brass survey point on 16 inch Ash which bears S. 05°08'E., 26.8 feet.

Wilford N. Haines
1955. C. S. File No. 42/75.

$\frac{1}{4}$ corner to Section 6, T22S, R6W., and Section 1, T22S, R7W.

39

Found: Original Fir, S. 88°W., 22 lks.

Cedar Stump, N. 84°E., 21 lks.

Set an angle iron with brass cap inscribed - survey point - Wilford N. Haines # 239.

Scribed two trees:

20 inch D. Fir, N. 59°30'W., 73.2 feet.

18 inch W. Fir, S. 47°E., 165.0 feet.

FD OK
M121-27
By Les Robert
12/94

FD OK PER DONALD BRANCH
8/86 - M-102-29

40

Section corner to secs. 6 & 7, T22S, R6W., and secs. 1 & 12, T22S, R7W.

Corner located by proportional measurement.

Set an angle iron with brass cap at corner point inscribed - survey point - Wilford N. Haines # 239.

From which:

12 inch Fir, N. 22°30'W., 21.5 feet.

24 inch Fir, S. 07°E., 70.8 feet.

24 inch Fir, S. 22°30'E., 73.8 feet.

6 inch Fir, N. 57°E., 45.9 feet.

RE-RENEWED, SEE CORNER NO. # 130

FD OK 8/86 DONALD BRANCH
M 102-29

41

$\frac{1}{4}$ corner to sec. 7, T22S, R6W., and sec. 12, T22S, R7W.

Corner location determined by proportional measurement.

Set an angle iron with brass cap for corner, inscribed - survey point - Wilford N. Haines # 239.

From which, scribed:

12 inch Fir, N. 72°W., 58.8 feet.

16 inch W. Fir, N. 45°E., 42.6 feet.

RE-RENEWED, SEE CORNER NO. # 149

42

Section corner to secs. 7 & 18, T22S, R6W., and secs. 12 & 13, T22S, R7W.

Location of corner determined by proportional measurement.

Set an angle iron with brass cap inscribed - survey point - Wilford N. Haines, No. 239.

From which, scribed:

26 inch Fir, S. 05°E., 45.5 feet.

26 inch Fir, S. 45°E., 51.5 feet.

16 inch Fir, N. 13°W., 47.3 feet.

10 inch Fir, N. 35°E., 57.7 feet.

RE-RENEWED, SEE CORNER NO. # 148
INFORMATION NOT CORRECT FOR THIS COR. M.E.G.

- SEE C.S. 59/8 -
REN #42 DOESN'T MATCH
CONDITION ACTUALLY AT COR.

VISITED 4/14/76 (G. LANGE) NET VERIFIED AS SR10

43

$\frac{1}{4}$ corner to section 18, T22S, R6W., and section 13, T22S, R7W.

Found original Fir bearing tree. Maple is dead and down.

Set an angle iron with brass cap inscribed - survey point - Wilford N. Haines # 239.

FD OK BY Ken Hoggan
3/94 M 119-23 # 185