

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

Wilford N. Haines
For Harold Woolley
December, 1957
Filed Jan. 21, 1958
Map File M 8 - 30

S. W. Corner of D. L. C. No. 42.
Found: Oak B.T. (Snag) to South for S.W. Corner.
D. L. C. #42 Corner bears S.84°37'E., 1199.54 ft. from
S.W. Corner Section 35, T21S, R6W.
Scribed: 12" W. Oak, S.87°15'W., 23.2 ft.
22" W. Oak, N.89°30'E., 40.5 ft.
Set 1"x1"x36" Iron **L** Rod with Brass Cap.

44
Duplicate of
REN. #67

S. E. Corner of D. L. C. No. 42.
Found: Oak B.T. (Snag) to N. W. for S.E. Corner D.L.C. #42.
Corner bears S.88°21'E., 3803.31 ft. from S.W. Corner
Section 35, T21S, R6W.
Scribed: 12" Fir, N.17°E., 57.0 ft.
Set 1"x1"x36" Iron **L** Rod with Brass Cap.

45
Duplicate
of REN. #68

Wilford N. Haines
For Don Levenhagen
Jan. 21, 1958
Map File M 7 - 65

$\frac{1}{4}$ Section Corner to Sections 13 & 24.
Found Iron Pipe & 2 B. T.'s. ~~REN. #20~~
Set 1"x1"x36" Iron Pipe with Brass Cap beside Pipe.

$\frac{1}{4}$ Section Corner to Section 12 & 13.
Found Post & 2 B. T.'s. ~~REN. #18~~
Set 1"x1"x36" Iron with Brass Cap by Post.

46
RE-RENEWED, SEE CORNER NO. #134
47
RE-RENEWED, SEE CORNER NO. #126

Wilford N. Haines
For E. G. Whipple Mill, Drain
Filed Jan. 15, 1959
Map File M 13 - 66

West $\frac{1}{4}$ Section Corner to Section 32.
Set Lot Marker 1"x 1"x 36" T irons with caps inscribed -
survey point, Wilford N. Haines #239,
from old BT's.
Scribed 10" Fir N.32°W. 13.51+ ft.

48
Fd 5/90
CS. 63/104

North $\frac{1}{4}$ Section Corner to Section 32.
Set Lot Marker from old BT's.
1"x 1"x 36" T irons with caps inscribed, survey point,
Wilford N. Haines #239.

49

East $\frac{1}{4}$ Section Corner to Section 32.
Found Old BT's. - Set Lot Marker, same as above.

50

(SEE P. B. H-108 FOR BT's)

$\frac{1}{4}$ Section Corner to Sections 22 & 23.
Found - 10" Fir S.75°W. 17 lks., (now about 18")
Set Lot Marker, 1"x 1"x 36" T Irons with Brass Cap inscribed,
survey point - Haines #239.
Scribed New BT's:
10" Fir S.40°W. 13.0 ft.
36" Fir S.52°E. 9.6 ft.

51
RE-RENEWED, SEE CORNER NO. #127

Wilford N. Haines
For
Filed March 24, 1959
Surveyed 12/58
Map File M 14 - 23

Center $\frac{1}{4}$ Corner of Section 23
Set Lot Marker, 1"x 1"x 36" T. Iron with Brass Cap inscribed,
survey point - Haines #239.
Scribed: 15" Fir N.78°E. 5.0 ft.
14" Fir S.53°W. 20.5 ft.

52

$\frac{1}{4}$ Section Corner to Sections 23 & 24.
Found - Iron Pipe & scribed Stake. Old BT's. have been knocked
down by logging operation.
Set Lot Marker, 1"x 1"x 36" T Iron with Brass Cap inscribed,
survey point - Haines #239.
Scribed: 15" Fir S.44°W. 96.4 ft.
12" Fir N.19°E. 21.7 ft.

53