

Douglas County Surveyor's Record of
Government Corners Renewed

22

T. S.

6

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

54

1/4 Section Corner to Sections 23 & 26.
Found - Stub of 30" Fir B.T. N.75°W. 66 lks.
Madrone N.55°W. 80.2 ft. scribed 1/4 S C.S., must have
been scribed by Britt, 1887.
Set Lot Marker, 1" x 1"x 36" T Iron with Brass Cap inscribed,
survey point - Wilford N. Haines #239.
Scribed: 12" Fir S.39°W. 24.4 ft.-B.T. on Madron

*Fd. 8/90
M110-47*

Wilford N. Haines
For
Filed March 24, '59
Surveyed 12/58
Map File M 14 - 23

55

1/4 Section Corner to Sections 25 & 36.
Found - 1/2" Galv. Iron Pipe at Corner.
Black Oak, now 48", N.89°E. 330.7 ft., This tree has
been opened previously & scribe marks "1/4 S" are
plainly visible. A ring count shows that scribing
was done 90 to 100 yrs. ago. Tree nearly dead.
No trace of SE B.T. found.
Blaze & scribe following new BT's:
26" Black Oak S.19°E. 223.3 ft. Mkd. "1/4 S36 CS BT."
15" Black Oak N.83°E. 218.8 ft. Mkd. "1/4 S25 CS BT."

RE-OPENED TREE CORNER NO. #192

56

Section Corner to Sections 25, 26, 35, & 36.
Found - Three Original BT's., All check bearings & distances.
Orig. SW B.T., now 40" Rotted Stump, shows good scribing
on old face "35 22".
Orig. NW B.T., now Short Stub, shows good scribing "BT".
Orig. NE B.T. shows good scribing on small section of
Stub.
No trace of Original SE B.T. found.
Set Brass Cap at Corner Mkd:

S26	S25	T22S R6W
S35	S36	County Surveyor's

 Office, 1959
Note - North South Fence 50.0 ft. more or less West.
New BT's: 8" R. Fir bears N.55°W. 82.7 ft. scribed S26 T22S R6W CS BT.
13" R. Fir bears N.26°E. 67.3 ft. scribed S25 T22S R6W CS BT.
9" W. Fir bears N.63 1/2°E. 124.6 ft. " S25 T22S R6W CS BT.
No suitable Trees to South.

*FD OK 8/92
J. BRANCH M115-52*

*FD OK
BY K. HOFFMAN
M120-79 8-94*

*Fd. 8/90
M110-47
FO. B. C. 12/58
M115-24*

James W. Byron, Deputy
Milo Godfrey
S. A. Blouw
April 13, 1959
C. S. File No. 49/143

57

Section Corner to Secs. 24 & 25, T22S R6W, & Secs. 19 & 30, T22S R5W.
Found - Orig. 14", now 30" W. Oak S.60°W. 66 ft., shows good
scars. I do not open.
Orig. 10", now 20" B. Oak Snag N.4 1/2°W. 47.5 ft., I open
& find good scribing "BT".
Orig. 20", now 44" W. Oak N.89°E. 47.5 ft., shows good
scars. I do not open.
Orig. 20", now 26", W. Oak, previously opened, shows
good scribing "S30" S.74°E. 32.3 ft.
Also find Scribed Stake at Corner. *SEE ALSO - T.M.'s Book 1 Pg 38*
Set Brass Cap at Corner Mkd: County Surveyor's Office,

S24	S19
1959	T22S R6W
S25	S30 R5W

New BT's: 8" W. Oak bears N.37°W. 8.7 ft. scribed S24 T22S R6W CS BT.
12" R. Fir bears S.57°E. 55.7 ft. scribed S30 T22S R5W CS BT.

*Fd OK
2/86
E. BLOOM
M100-25
12/2/92
S. DEANER
M116-29, CS 63/49*

58

Section Corner to Secs. 13 & 24, T22S R6W, & Secs. 18 & 19, T22S R5W.
Found - Orig. 18", now 22" partly rotted Oak Stump N.15°E. 150.5 ft.
I open near base & find good scribing "BT".
Orig. 24", now 30" partly rotted Oak Snag N.48°W. 115.5 ft.,
I open near base & find good scribing "BT".
30" down Oak checks bear. & dist. for Orig. SE B.T.
No trace of Orig. SW B.T.
Set Brass Cap at Corner Mkd: County Surveyor's Office

S13	S18
1959	T22S R6W
S24	S19 R5W

New BT's:
9" Dbl. W. Oak bears N.28°E. 12.0 ft. scribed S18 T22S R5W CS BT.
9" W. Oak bears S.57°E. 7.9 ft. scribed S19 T22S R5W CS BT.
22" R. Fir bears N.25 1/2°W. 19.4 ft. scribed S13 CS BT. Note- This
BT. scribed on one face & scribed high, above fence.
10" W. Oak bears S.25°W. 32.0 ft. scribed S24 T22S R6W CS BT.
Note - I find 3/4" Iron Rod thus:

*FD OK 12-91
C. GUILLE 1992-0079 M115*

*FD OK 8/81
B. SHANER
M90-2*