

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Twp. Corner to Sec. 6, T22S R6W, Sec. 1, T22S R7W, Sec. 31,
T21S R6W, and Sec. 36, T21S R7W.

Set 1" x 1" x 36" T. Iron from old BT's.
Feb. 17, 1960

By Wilford
N.
Haines
C. S. File 51/67

1/4 Section Corner to Sections 14 and 23.

Set Lot Marker, 1" x 1" x 36" T. Iron with Brass Cap,
inscribed survey point-W.N.Haines #239.

Set Mid-Way

1/4 Section Corner to Sections 14 and 15.

Found Rock & Stake. - *REN. #9*
Set Lot Marker, 1" x 1" x 36" T. Iron with Brass Cap,
inscribed survey point - W. N. Haines #239.

S. W. Corner of D.L.C. No. 42.

Found - Oak B.T., snag, to South for S.W. corner.
D.L.C. #42 corner bears S.84°37'E. 1199.54 ft. from
S.W. corner Section 35, T21S R6W.

Scribed - 12" W.Oak, S.87°15'W. 23.2 feet.

22" W.Oak N.89°30'E. 40.5 ft.

Set 1" x 1" x 36" Iron I Rod with Brass Cap.

S. E. Corner of D.L. C. No. 42.

Found - Oak B.T., snag, to N.W. for S. E. Corner D.L.C. # 43.
Corner bears S.88°21'E. 3803.31 ft. from S.W. corner
Sec.35, T21S R6W.

Scribed - 12" Fir N.17°E. 57.0 ft.

Set 1" x 1" x 36" Iron I Rod with Brass Cap.

S. W. Corner D. L. C. No. 43.

Found - Oak BT. N.73°W. 200 lks.

Set - 1" x 1" x 36" T. Iron.

Note - Found Pipe for N.W. Corner D.L.C. No. 44,
N.89°43'W. 589.7 ft.

Section Corner to Sections 7 - 8 - 17 - 18.

Found - Haines "T" Iron & Cap in mound of Rocks.

Stump of 60" Fir S.32 1/2°W. 37.6 ft. No trace of scribing. #129

Maple 24" S.22°W. 28.0 ft. showing scar.

18" Fir N.40°W. 15.8 ft. scribing shows in scar, not
completely grown over.

No trees near East of Line.

No Renewals found in records except renewal by Frear in 1919. *Ren. #6*

Section Corner to Sections 13 - 14 - 23 - 24.

Found - 1/2" Pipe, probably Pipe set by Irving in 1928. *REN. #24*

Orig. B. Oak, now 38", S.68°W. 21.1 ft., shows old scar,
has been opened previously.

Fir Stump, now 27", S.30°W. 37.3 ft., showing good scar.

Fir Stump, now 18" & 10' high, S.25°E. (instead of S.35°E.)
13.5 ft. Chopped upper blaze open & fd. good scribing.

No trace can be found of Irving's N.E. or N.W. BT's.

Set Brass Cap Mkd: County Surveyor's
Office, 1961

S14	S13
S23	S24

T22S R6W

New BT's: 9" D.Fir S.10°W. 76.6 ft. Mkd: T22S R6W S23 CS BT.

11" D.Fir S.7°E. 60.5 ft. Mkd: T22S R6W S24 CS BT.

22" D.Fir N.58°E. 47.4 ft. Mkd: T22S R6W S13 CS BT.

12" B.Oak N.46 1/2°W. 104.2 ft. Mkd: T22S R6W S14 CS BT.

Corner is at Fence Cor. Fence runs N. & W. from cor. which is on
top of ridge runing N.55°E. & S.55°W.

64

65

66

67

68

69

70

71

Wilford N. Haines
Dec. 1958
Map File
M 14 - 23

Wilford N. Haines
For Harold Woolley
December 1957
Filed Jan. 21, 1958
Map File M 8 - 30

Wilford N.
Haines
July 1961
M 20 - 76

Milo E. Godfrey, Deputy County Surveyor
Vernaon Tracy
Clete Putnam
Aug. 2, 1961
C. S. File No. 49/143

RE-RENEWED, SEE CORNER NO. 119

(Duplicate of Ren. #44)

(Dup. of Ren. #45)

RE-RENEWED, SEE CORNER NO. 129