

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

84

Section Corner to Sections 29 - 28 - 32 - 33.
Found - 1" Bolt with Nut on Top. *-(See F.B. H-106) 9/30/68*
Dead Cedar, now 12", N.60°E. 6.6 ft. Hollow inside, good
reverse scribing "8 2S 6W".
Rotted remnants of S.E. & S.W. Trees found, no scribing.
No trace of N.W. BT.
55" Cedar S.63°E. 25.5 ft. scribed T22 R6W S33 BT 329.
5" Fir N.33½°W. 7.4 ft.; scar healed over.
42" D. Fir S.9°W. 25.3 ft. scribed 32 R6 BT. Rest of
scribing pitched over.
(These 3 trees apparently recently scribed by ~~T. Ellingsen~~, W. Haines
Land Surveyor #329 - Corroborated by Milo Godfrey, Deputy Co. Surv.
#239

85

West ¼ Corner to Section 19 only.
Found - Haines "T" Iron ~~Cap~~ and Cap. *(No Rec.)*
Fir Tree, now 54", S.30°W. 12.5 ft. Has been opened previously
& face burned but portions of unmistakable scribing visible.
This tree has been rescribed in Bark ¼ S 363 BT".
Portions of Fir Stump N.58°E. 48.2 ft. found. No marks found.
Blaze & Scribe one new Tree: 12" D. Fir N.22°E. 46.1 ft. Mkd: ¼ S19 CS BT.

86

¼ Corner to Sections 19 and 20.
Found - Cedar Stump, now 48", approx. 24" when scribed, N.45°E. 65.3 ft.
has been previously opened & scribing "¼S" plainly visible.
Shattered Fir Stump, now 48", S.50°W, instead of N.50°W. 15.8 ft.
No scar or scribing found. No trace of Stump fd. to the N.W.
Set - Iron Pipe with Brass Cap Mkd: County Surveyor's Office, 1961
T22S. R6W ¼ S19/S20.
New BT's: 12" D. Fir S.89°E. 24.1 ft. Mkd: ¼ S20 CS BT.
21" D. Fir N.55½°W. 44.5 ft. Mkd: ¼ S19 CS BT.

87

Section Corner to Sections 19 - 20 - 30 - 29
Found - 4' x 4' x 3' Rock Outcrop with "X" (3" diam.) on N. face,
2 ft. above ground.
Dead Fir Snag, now 52", S.72°W. 41 ft., shows good scar.
48" Fir Tree N. 1°W. 50.8 ft. shows good scar.
60" Fir Tree N.36°E. 25.7 ft., face & bark rotted away.
80" Fir Stump S.20°E. 126 ft. Good Scar.
New BT's: 10" Fir S.47½°E. 19.2 ft. Mkd: T22S R6W S29 CS BT,
14" Fir N.29½°W. 29.3 ft. Mkd: T22S R6W S19 CS BT.
6" Fir N.81°E. 33.5 ft. Mkd: T22S R6W S20 CS BT.
No tree good to S.W.

88

West ¼ Corner to Section 31 only. *Foak 2/94 BY Hoffine*
Found - Haines "T" Iron & Cap at Corner. *C.S. 63/154-5*
Fir Tree, now 30", has been opened previously & good
scribing "T" found.
No trace of N.W. BT.
New BT: 23" D. Fir N.21°E. 27.6 ft. Mkd: ¼ S31 CS BT.
Note - Did Not Set Brass Cap.

89

Section Corner to Secs. 5 & 6, T22S-6W. & Secs. 31 & 32, T21-6W.
Found - 40" Fir S.33°E. 33.0 ft. with faint bark scribing "S5" recognized.
80" Fir Stump N.56°E. 12.5 ft. with traces of old bark scribnd vis.
Stump Hole S. 4°W. 27.7 ft.
Stump Hole N.30°W. 14.5 ft.
Set - Iron Pipe with Brass Cap Mkd: County Surveyor's Office, 1961
T21S
S31 | S32
S 6 | S 5 R6W
New BT's: 32" R. Cedar N.70°W. 17.0 ft. Mkd: T21SR6WS31 CS BT. T22S
6" Hemlock N.19½°E. 20.2 ft. Mkd: T21S R6W S32 CS BT.
16" Hemlock S.48°W. 28.8 ft. Mkd: T22S R6W S6 CS BT.
Rescribe (in wood) 40" Fir S.33°E. 35.0 ft. (to center of tree) Mkd:
T22S R6W S5 CS BT
Sept. 11, 1961

Milo E. Godfrey, Deputy County Surveyor
Vernon Tracy
Clete Putnam
August - 1961
C. S. File No. 49/143

*Foak
12/94
Les Roberts
M121-27*