

Douglas County Surveyor's Record of
Government Corners Renewed

T1 22 S. T. S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section Corner to Secs. 1 & 12, R6W and Secs. 6 & 7, R5W. **111**
Found - Rock Monument at Corner. Also pieces of rotted Oak
Wood N. 4°E. 101 or 102 ft. (Gov't notes call for Oak
Tree N. 4°E. 110.9 ft) Logging Road runs just North of
Oak fragments. No stump hole now visible. W. Haines
states that he has seen scribing there several years
ago. Could not remember whether or not the tree was
standing at the time.

See
C.S. 64/48
Pg 8
For Thiel - Set stone.
11/30/93 D.C.S.O.
J.C.

F.S. 2/81
E. DEAN
1188-65

Set - Brass Cap Mkd: County Surveyor's Office, 1961
R22S R6W S 1 | S 6 R5W
S12 | S 7
New BT's: 16" Fir N.16°W. 46.5 ft. Mkd: T22S R6W S1 CS BT.
4" Fir N.39°E. 21.0 ft. Mkd: S 6 CS BT.
12" Fir S.65°W. 9.4 ft. Mkd: T22S R6W S12 CS BT.
7" Fir S.70°E. 16.5 ft. Mkd: T22S R5W S7 CS BT.
E. & W. Fence is 2.5 ft. N. of Corner.
1 1/4" Pipe bears N.88°E. 14.43 feet.

Milo E. Godfrey, Deputy
Vernon Tracy & Cleate Putnam
October 1961
C. S. File No. 49/143

West 1/4 Corner of Section 30. **FO. OK 2/94 BY HOFFINE C.S. 63/154-5 112**
Found - Fir Tree, now 40", N.58°W., not S.58°W, 7.3 ft. (to face)
This tree has been chopped open & good scribing "BT" visible.
Fir Tree, 60", N.52°E. 13.2 ft., uprooted & down, face down.
Impossible to see scars or scribing.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1961
T22S R7W 1/4 S30 R6W
New BT's: 12" D. Fir S.10°E. 24.8 ft. Mkd: 1/4 S30 CS BT.
9" D. Fir S.73°E. 22.5 ft. Mkd: 1/4 S30 CS BT.
Note - Haines' "T" iron previously set for 1/4 cor. by proportionate
measurement bears N.55°W. 37.3 ft. - REN. # 34

Closing Corner to Sections 31 and 32, T22-6W. **113**
Found - My Corner "T" Iron with G.L.O. Brass Cap alongside
in a pile of rocks. - REN. # 29
Found - 18" Fir B.T. N. 36 1/2°W. 45.4 ft. **CORNER NO. 121**
24" Fir Stump scribed C.C. S32 B.T. N.20°E. 48.1 ft.

Corner to Section 6 and 5 only, T23-6W. **114**
Found - Brass Cap set by G.L.O. pulled out. Set back in same hole.
Orig. Fir B.T., no 6.0 ft. Stump bears S.25°E. 5.3 ft. to face.
New BT's. by GLO: 16" Hemlock S.29°E. 53.3 ft. (not 47 lks.) **122**
10" Hemlock S.31°W. 47 lks. (not 79 lks.) Tree down.

Closing Corner Sections 35 & 36. (N. Line T23S R6W) **115**
Found - GLO Brass Cap set in 1943.
Dead & Rotting Fir Snag, 36" diam., N.80°E. 24.4 ft.,
scribing visible "T22S R6W S36 CC".
32" White Fir N.60°W., (not S.60°W) 57.4 ft., very plain scar.
New BT: 11" White Fir N.33°E. 97.3 ft. Mkd: T22S R6W CC S36 CS BT.

FO. OK
8/92 Bannett
1115-52

FO. OK
8/94
K. Hoffine
1120-79

Sec. Cor. to Secs. 2 & 1 only, T23-6W. (S. Line T22-6W) **116**
Found - G.L.O. Brass Cap set in 1943.
48" Fir S.13 1/2°E. (not S.26 1/2°E.) 71.9 ft., very plain axe scar.
54" Fir S.67°W. 134.0 ft., uprooted & down.
New BT's: 12" White Fir S.62°W. 27.0 ft. Mkd: T23S R6W S2 CS BT.
8" White Fir S.66°E. 14.7 ft., Mkd: T23S R6W S1 CS BT.

Milo E. Godfrey, Deputy
Wm. Storfel & Mike Stone
Feb. 26, 1964
C. S. File No. 49/143

S. E. Corner D. L. C. No. 44. **117**
Found - Rock mkd. with 44.
Orig. Fir BT., now snag, S.80°W. 150 lks.
Set - "T." Iron by Rock.

Wilford N.
Haines
For-Ray Heaton
July 15, 1965
Map. File M 30-16