

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 22 T. S. R 6 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21991

144

C O N T - - -
L.E. Monrean LS #1830
Deputy, Doug. Co.
Surveyors Office
Aug. 29, 1983
C.S. 62/9

This monument is set at position of temporary hub determined from found references per M 88 - 65 and C.S. 58/204.
New BTs - A 6" diam. maple, double blazed and scribed "S2 CS BT", bears N.9°W., 8.0 ft.
An 18" B. oak, double blazed and scribed "T22S R6W S12 CS BT", bears S.11°E., 70.0 ft.
A 28" diam., maple, double blazed and scribed "T22S R6W S12 CS BT" bears S.56°E., 55.9 ft.

145

Donald Branch
L.S. #1137
For: U.S. Bank
Oct. 14, 1983
M 95 - 65

Center 1/4 corner for Section 20.
Set - 5/8" iron rod with cap on 30" rebar. Cap mkd. Branch Eng. LS 1137.
BTs - 10" D. fir tagged, blazed painted & scribed C 1/4 S20 BT, bears N.78°W., 2.2 ft.
7" D. fir tagged & blazed & painted & scribed C 1/4 S20 BT, bears N.13°E., 6.3 ft.
L.S. washer set in blaze in BTs.

10/14/83

146

Eugene A. Bloom
RLS: 492
For: Robert Lee &
Nora May Allen
January, 1986
M 100 - 25

1/4 Section Corner to Sec. 36 (T22-6) and Sec. 31 (T22-5)
SET - A 5/8 by 30" iron rod, with plastic cap mkd. "AA Surveying Incorporated."
BT's - A 10" D. Fir, bears S.66°W., 33.1 ft. dist., scribed "1/4 S36 BT"
A 21" W. Fir BT., bears S. 15° E., 35.2 ft. dist., scribed "1/4 S31 BT."
NOTE - Corner lies 6.7 ft. south of fence.

*FD OK
BY K. Hoffme
M120-75
8-94*

147

Donald Branch
L.S. #1137
For: U.S. National
Bank.
June 16, 1986

Section Corner for Secs. 6,5,7 & 8.
Found - A Douglas County brass cap on 1" pipe marked S6/S5 1961
S7/S8
22" Fir snag with blaze healed & tagged bears N 41°E, 21.4'.
28" Fir bears S21°E, 11.2'. Ren #107
New BT'S - 11" Fir bears N63°W, 18.5', with 3 hacks on front & back & brass L.S. washer at base of tree. No scribing.

RE-ENTRANCED SEE CORNER NO. #178

148

Section corner for section 7 & 8 and secs. 12 & 13, T22-7.
CORNER REPORT ONLY
Found - A 4" x 4" "X" on 4' x 6' bedrock.
18" Fir with B.L.M. tag, Haines disc, healed blaze bears S53°W 25.17'. Record per B.L.M. tag agrees with measured.
12" Fir with healed blaze & B.L.M. tag bears N60°W, 2.10'.
18" Fir with scribing visible, B.L.M. tag, Haines (Ren. #42) disc bears N62°E, 18.03'.

FD OK, Dec. '94, M121-43

149

Charles Guile
For: Weyerhaeuser
Company
April 15, 1987
C.S. 63/54

1/4 Corner for Section 7; and Sec. 12 of T.22-7
Found - Angle iron with 1" brass disc. mkd. "Wilford N. Haines 239 Survey Point". Ren. No. 41
20" Fir with blaze, N.73½°W., 58.5 ft.
24" Fir with blaze, N.45°E., 41.9 ft.
New BTs - 6" W. fir N.46°E., 7.95 ft. to "W" nail with "X" at breast height.
10" Fir, S.32°E., 3.85 ft. to "W" nail.

4/15/87

150

James A. Branch
For: U.S. Nat'l Bank
March 23, 1990
M 109-74 A-B
C.S. 63/104

Section Corner for Secs. 2, 3, 10 and 11.
Found - T Iron set by Wilford Haines in C.S. #42/75. (Ren. #38). Brass cap on top of T iron is missing.
30" (16", 1955) Ash bearing tree bearing S.5°08'E., 26.8 ft. lying on the ground.
New BTs - 8" Ash scribed "SE S 3" BT bears N.8°44'W., 175.6 ft.
13" white Oak scribed "SW S 2" BT bears N.58°09'E., 132.5 ft.
27" W Oak scribed "NW S 11" BT bears S.66°09'E., 100.4 ft.
26" Ash scribed "NE S 10" BT bears S.29°53'W., 79.9 ft.

3/23/90