

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 S T. S. R. 6 W R.W.W.M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97401

182

DOUGLAS COUNTY
RANDALL SMITH
STEPHEN FLAUSE
11/2/90
CS 64/58

marks visible, bears S.13°W 138.6' (agrees w/ rec.)
OBT.

20" now 40" dia., W.Oak with a fully healed blaze, bears S.7½°E.
97.9' (rec. S.7½°E, 95.7') OBT.

Monument Set - A DCSO 2 3/8" dia., brass cap on a 1½" O.D. by 31" long
I.P. is set flush with ground, with corner stone reset
upright along east edge of BC/IP 3" below ground.

DOUGLAS COUNTY SURVEYORS

R T 22 S R
6 S36 S31 S
W S01 S06 W
T 22 S

OFFICE 1990

corner lies in middle of old gravel road at north - south fence crossing
Note: This renewal was lost from 11/2/90 to 1/95.

RE-RENEWED, FREE CORNER NO. #161

183

SOUTH ¼ OF SEC. 18

FOUND - Haines T-iron w/ washer .5' above ground

BT's Fd. - 18" D.Fir, bears N.74°W. 17.7', well haled face we tagged
14" decaying maple, bears S.57°W. 110' (rec. 109.2') no mks.
13" D.Fir, bears S.22°E. 7.9', we scribed ¼ S.19 B.T. & tagged
14" D.Fir, bears N.74°E. 70.8', well healed face & B.T. tag.

corner lies on top of a narrow ridge wich runs N.70°E.

184

SOUTHWEST SEC. COR. OF 18

FOUND - Haines T-iron .3' above ground

BT's FD. - 36" D.Fir stump, bears S.72°W. 13.5', no marks visible
27" D.Fir "high" stump, bears N.77°E. 25.2' chopped out face.
scribing barely visible.
70" D.Fir "high" stump, bears S.70°E. 55.7', bark scribing
visible.
20" D.Fir, bears S.46°W. 32.5', we scribed 22S 7W S24 B.T. &
tagged.

corner lies on a 40% slope to the Northwest

185

WEST ¼ OF SEC. 18

FOUND - Haines T-iron

BTs FD - 24" D.Fir, bears N.8°E. 24.5', no face 3 B.T. tags
52" D.Fir, bears S.10°W. 25', no face LRT location tag
Orig. 12" D.Fir, is a 55" rotten stump, bears N.85°W. 17.8'. old
face visible no scribing.
Orig. 10" Maple, is a 21" wind fall, bears S.55°E. 6.6', no visible
scribing.

corner lies on a 50% southwest slope. BLM clearcut to the Northwest.

186

KEN HOFFINE
LONE ROCK TIMBER
DEC. 1994
M 121 - 43