

Douglas County Surveyor's Record of
Government Corners Renewed

32 T. S. 7 R. W. W. M.

✓ MEANDER CORNER OF ELK CREEK ON LINE BET 17-20
Renew corner from W. Fir called for in field notes, mark
m A.W. Fir S.43¹°E. 39 lks. dist.
A.P. Fir N.25¹°W. 50 lks. dist.

9

Vol. 2, p. 189
Lloyd Cole
Deputy
J. Traylor
G. Baylor
Witnesses
June 18, 1913

✓ CORNER BET. 17-18
Renew from original trees. Fir still standing Oak stump in evidence. **93**

10

✓ COR. TO SECS. 2 4 9 10 Belongs in T225, R.8W.
Renew Cor. set Oak post from original trees which bear as follows.
A Fir 15" in dia. bears N.62°E. dist. 47 lks.
A Fir 8" in dia., bears S.38°E. dist. 75 lks.
A Fir 36" in dia., bears S.70°W. dist. 85 lks.
A Fir 16" in dia. bears N.60°W. dist. 96 lks.

11

T225R8W

✓ CORNER CHANGED BY J.W. COLE Feb. 14, 1921
Reestablished the interior "L" cor. of Cl. 45 from which
A R. Fir 24" in dia. bears N.80°W. 6 ft. dist.
An Oak 12" in dia. bears S.66°E. 3 ft. dist.

12

SEE R.V. #16
Vol. 2 Pg. 253
Vol. 3 Pg. 87

✓ N.E. CORNER CLAIM 45
Renew corner from which
A Fir 12" in dia. bears S.72°30'E. 16 ft. dist.
A Fir 12" in dia. bears N.56°E. 10 ft. dist.

13

Deputy Lloyd Cole
S. Prown
W. Frost
Witnesses
July 5, 1913
Vol. 2 Pg. 253-254

✓ RENEW S.E. COR. BET. SECS. 20 & 21
Set a Rock 8" x 12" x 30". **#110**

14

✓ RENEW THE S.E. COR. OF THE WM. HANCOCK CL. NO. 45
Could not make the trees agree on this corner, so found by using slope measure and changing direction to the Alder given as N.76°W. to N.66°W. they all check the cor. closely. All three trees are alive and standing. Ed. Hancock testifies that the marks on tree N.76°W. were visible 30 years ago. The other two trees bear bark marks of 22°3. 7W. which was most unusual marks for original marks. I set a 4" x 4" x 40" oak post also an iron pitman bar. from which, An original P.T. bears N.52°E. 173.6 ft. slope measurement an original B.T. bears N.64°E. 180.2 ft. slope measure. An original B.T. bears N.66°W. 206.5 ft. slope measure. Marked 2 new trees.
30" dia., bears S.67°E. 42.8 ft.
30" dia., bears N.4°45'E. 28.4 ft. dist.

15

Vol. 3
Pg. 87

✓ WM. HANCOCK D.L.C. NO. 45 INTERIOR "L" COR.
Located this corner from testimony given by Ed. Hancock, as to the position of the witness trees. As this put me on a line run due North of the S.E. Corner of the Claim with but 16.5 ft. over measure from distance called for in field notes also due West of N. 111 Inter "L" corner. I consider this as all of the evidence as possible to get and set a 4" x 4" x 36" post also 2" Iron Pipe for cor. from which
An Oak 20" dia. bears N.45°W. 31.3 ft. dist.
An Oak 15" dia. bears N.75°15'E. 68.0 ft. dist.
F. J. Coles Cor. bears N.75°40'E. 65.0 ft. (REN. #12)

16

Searched for twice - Not found
Dec 19 1959

February 1913
Leslie Hancock
Edward Hancock
Witnesses
F. J. Cole
Deputy

✓ S.E. COR. OF HART D.L.C. NO. 42 from the original B.T. as follows a stump apparently of original B.T. W.56°W. 57.2 ft. A an original P.T. bearing marks N.9°E. 184 ft. a snag of an original B.T. S.87°E. 72.6 ft. Set a rock 18" x 18" x 24" for cor. marked with X and Cl. 42. from which a point of ledge rock marked with X and Cl. No. 42. bears S.80°W. 50.3 ft. Point of ledge rock marked with X and Cl. 42 S.25°30'W. 42 ft.

17

RENEWED
#174

Feb. 50 Pg. 17