

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 7 R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. - B1008

Closing corner to Sec. 36, T 22 S, R 7 W., and Sec. 31, T 22 S, R 6 W.
Found scribe on stub of B. T., N.53 $\frac{1}{2}$ °W., 116.8 feet and stake set by Robert
Kliener.
Set an angle iron with brass cap inscribed-Survey point - Wilford N. Haines
No. 239.

NOTE - SUPERSEDED BY G.L.O. SURVEY, 1956

29

Wilford N.
Haines
1954 - 1955.
C. S. File
42/13.

Northwest corner of Thomas Levins Donation Land Claim No. 38.
Found stump of original Northeast BT, now 36 inches, partly rotted- found
scribe marks.
Corner falls in stream 10 feet wide.
Set iron pipe with brass cap for witness point for corner, N.42°E., 42 feet
from corner and with the brass cap marked DLC 39 wit. pt. County Surveyor's
Office 1956.
Blazed and scribed 12 inch W. C., S.43°E., 38.7 feet, mkd. W. P. C. S. BT.

30

James W. Byron,
Deputy County
Surveyor
January, 1956.
C. S. File 47/47.

$\frac{1}{4}$ corner to Section 1, T22S, R7W., and Section 6, T22S, R6W.
Found: Original Fir, S.88°W., 22 lks.
Cedar stump, N.84°E., 21 lks.
Set an angle iron with brass cap inscribed - survey point - Wilford N.
Haines # 239.
Scribed two trees:
20 inch D. Fir, N.59°30'W., 73.2 feet.
18 inch W. Fir, S.47°E., 165.0 feet.

FD OK
Les Roberts
12/94 M121-27

31

Section corner to secs. 1 & 12, T22S, R7W., and secs. 6 & 7, T22S, R6W.
Corner located by proportional measurement.
Set an angle iron with brass cap at corner point inscribed - survey point -
Wilford N. Haines # 239.
From which:
12 inch Fir, N.22°30'W., 21.5 feet.
24 inch Fir, S.07°E., 70.8 feet.
24 inch Fir, S.22°30'E., 73.8 feet.
6 inch Fir, N.57°E., 45.9 feet.

Wilford N. Haines, Reg. Surveyor No. 239.
Survey for Chester Swearingen and Harold Woolley.
1956.
Map File No. M 3 - 22.

32

$\frac{1}{4}$ corner to sec. 12, T22S, R7W., and sec. 7, T22S, R6W.
Corner location determined by proportional measurement.
Set an angle iron with brass cap for corner, inscribed - Survey point Wilford N.
Haines No. 239.
From which, scribed:
12 inch Fir, N.72°W., 58.8 feet.
16 inch W. Fir, N.45°E., 42.6 feet.

33

Section corner to secs. 12 & 13, T22S, R7W., and secs. 7 & 18, T22S, R6W.
Location of corner determined by proportional measurement.
Set an angle iron with brass cap inscribed - Survey point - Wilford N. Haines,
No. 239.
From which, scribed:
26 inch Fir, S.05°E., 45.5 feet.
26 inch Fir, S.45°E., 51.5 feet.
16 inch Fir, N.13°W., 47.3 feet.
10 inch Fir, N.35°E., 57.7 feet.

34

$\frac{1}{4}$ corner to section 13, T22S, R7W., and section 18, T22S, R6W.
Found original Fir bearing tree. Maple is dead and down.
Set an angle iron with brass cap inscribed-Survey point - Wilford N. Haines
No. 239.

35

(SEE H-102 FOR POSSIBLE BT BY HAINES)

$\frac{1}{4}$ corner between secs. 1 and 12.
Corner located by proportional measurement.
Set an angle iron with brass cap at corner point inscribed-Survey point-
Wilford N. Haines - No. 239.
From which:
52 inch Fir, S.88°W., 23.6 feet.

36

By Ken Hoffine
12-19-23

206