

Douglas County Surveyor's Record of  
Government Corners Renewed

22 T. S. 7 R. W. W. M.

ROSE-CHAPMAN CO., EUGENE, ORE. 21881

Section corner to secs. 1, 2, 11 and 12.

Found original B.T.s:

Cedar, N.60°E., 37 lks.

W. Fir, S.25°W., 15 lks.

Found scribed stake.

Set an angle iron with brass cap at point for corner scribed - survey point - Wilford N. Haines # 239.

SEE CORNER NO. 124 37

1/4 corner to sections 11 and 12.

Corner located by proportional measurement.

Set an angle iron with brass cap at corner point inscribed - survey point - Wilford N. Haines # 239.

From which, scribed:

30 inch Fir, N.52°E., 42.7 feet.

X on rock 4 feet x 4 feet x 5 feet, S.87°W., 15.5 feet.

X on rock 6 feet x 6 feet x 6 feet, N.52°E., 5.1 feet.

SEE CORNER NO. 203 38

Section corner to secs. 11, 12, 13 and 14.

This corner was set from local physical objects called for in the original field notes. The old Scottsburg trail is 5.0 chs (330 feet) East,

1.50 chs. (990 feet) South. Elk Creek is 1.75 chs. (115.5 feet) North.

Set an angle iron with brass cap at corner point inscribed - Survey point - Wilford N. Haines # 239.

From which:

24 inch Alder, S.70°W., 11.0 feet.

12 inch Fir, S.31°W., 30.9 feet.

8 inch Fir, S.25°E., 23.8 feet.

12 inch W. Fir, N.74°E., 22.2 feet.

SEE COR # 156 (SAME) 39

1/4 corner to secs. 12 and 13.

Corner located by proportional measurement.

Set an angle iron with brass cap at corner point inscribed - Survey point - Wilford N. Haines # 239.

From which, scribed:

12 inch Fir, S.62°W., 6.5 feet.

8 inch Fir, N.26°E., 7.0 feet.

FD OK BY Ken Holling 3/94 4/19-23 40

Center 1/4 corner to section 12.

Location of corner established by intersection of N - S and E - W centerlines.

Set an angle iron with brass cap for corner inscribed - Survey point - Wilford N. Haines # 239.

From which:

24 inch Maple, S.80°W., 82.0 feet.

6 inch Fir, S.31°W., 39.4 feet.

41

Closing corner to secs. 3 and 4 on Twp. line.

Found original corner.

Set a 1 inch x 36 inch 1 rod at corner with brass cap inscribed, "Wilford N. Haines, Survey point, #239".

SEE CORNER NO. 127 42

Section corner to secs. 2 & 3, T22S, R7W., and secs. 34 & 35, T21S, R7W.

Point for corner located by proportional measurement.

Set a 1 inch x 36 inch 1 rod at corner with brass cap inscribed, "Wilford N. Haines, Survey point, #239".

From which:

30 inch Fir, N.04°30'W., 29.0 feet.

16 inch Fir, S.75°15'W., 40.9 feet.

24 inch Fir, S.22°00'E., 46.4 feet.

43

1/4 corner to sec. 2, T22S, R7W., and sec. 35, T21S, R7W.

Point for corner located by proportional measurement.

Set a 1 inch x 36 inch 1 rod at corner inscribed, "Wilford N. Haines, Survey point, #239"-(With brass cap).

From which: 30 inch Fir, N.10°30'W., 34.9 feet.

44 inch Fir stump, S.01°30'W., 8.2 feet.

44

Wilford N. Haines, Registered Surveyor No. 239.  
Survey for Chester Sweringen and Harold Woolley.  
1956.

Map File No. M 3 - 22.

Wilford N. Haines  
Survey for Harold Woolley  
March, 1957

C. S. Map File No. M 4 - 52.