

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section corner to secs. 1 & 2, T22S, R7W., and secs. 35 & 36, T21S, R7W.
Found original corner. **67**
Set a 1 inch x 36 inch rod at corner point with brass cap, inscribed
"Wilford N. Haines, Survey point, #239". **45**

Wilford N.
Haines
March, 1957
C. S. Map
File
M 4 - 52.

46-A
Corner on South Boundary Section 31.
Set W. Oak post 4x4x3 from which: W. Oak 12" bears N 67°54'W 181 lks.
(Old Marks in evidence) W. Oak 13" bears N 48°36'W 118 98 lks.
Corner of Sections 31 & 32 on Stan. Parallel. **46**
Set S. Stone 4x10x24. Corner set on true line by prop. measurements.
W. Oak 12 inch bears N 39°06'W 240 lks. (All old landmarks show new
W. Oak 15 inch bears N 14°00'E 378 lks. corner is correctly placed) **47**

Volume 2
Page 265

Section Corner to Sections 35 & 36.
Set from Original B.T's.
Set 1"x 1"x 36" Iron Rod with brass cap inscribed. "Wilford
N. Haines #239 Survey Point".

48
Section Corner for Section 35. (South)
Set 1"x 1"x 36" Iron Rod with brass cap inscribed.
"Wilford N. Haines #239 Survey Point".
18" Fir N.17°W. 16.2 ft.
30" Fir N.11°E. 23.0 ft.

49
Corner to Sections 34 & 35.
Set 1"x 1"x 36" Iron Rod with brass cap inscribed,
"Wilford N. Haines #239 Survey Point".
12" Fir N.17°W. 37.5 ft.
14" Fir N.64°E. 28.1 ft.

Wilford N. Haines
For E. G. Whipple
October, 1957
C. S. File No. 42/309
Map File M 1 - 59

50
C. Corner to Sections 26 & 35.
True Point for Closing Corner is S.89°20'W. 1.98 ft. from
monument which is not terminus of Line.
28" Fir N.30°W. 29.7 ft.
Carved X in Bed Rock .
Found S. E. B. T.
Set 1"x 1"x 36" Iron Rod with brass cap inscribed, see above.

51
Corner to Sections 27 & 34.
8" Fir N.58°W. 26.5 ft.
18" Fir S.77°W. 29.5 ft.
Set 1"x 1"x 36" Iron Rod with brass cap inscribed, see above.

52
Section Corner to Sections 35 & 34.
Set 1"x 1"x 36" Iron Rod with brass cap inscribed as above.
36" W. Fir S.83°E. 7.9 ft.
8" Yew S.15°W. 16.4 ft.

53
Section Corner to Sections 26 & 27.
Set 1"x 1"x 36" Iron Rod with brass Cap inscribed as above.
6" Fir S.71°E. 21.7 ft.
36" Fir N.69°W.103.0 ft.

54
Section Corner to Sections 22, 23, 26, & 27.
Set from Original B. T. Stump
Set 1"x 1"x 36" Iron Rod with brass cap inscribed as above.
10" Fir N.30°E. 34.5 ft. **63**
5" W. Fir S.69°E. 28.0 ft.