

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

Wilford N. Haines
For E. G. Whipple
October, 1957

Map File M 1 - 59
C. S. File No. 42/309

James W. Byron, Deputy
Milo Godfrey
Clete Putnam
Feb. 3, 1960
C. S. File No. 52/14

1/4 Section Corner to Sections 23 & 26.
Set 1"x 1"x 36" Iron Rod with Brass Cap inscribed,
"Wilford N. Haines #239 Survey Point,"
8" Fir N.44°W. 19.3 ft.
60" Incense Cedar S.17°W. 32.7 ft.

55

Corner to Sections 23 & 24.
Set from Original BT's.
1"x 1"x 36" Iron Rod with Brass Cap inscribed as above.

56

Closing Corner Sections 26 & 25.
Set from Original B.T's.
Set 1"x 1"x 36" Iron Rod with Brass Cap inscribed as above.
True Point for C. C. is S.02°58'E. 21.18 ft.

57

1/4 Section Corner to Sections 26 & 25.
Set from Original B. T. to N. E.
22" Fir N.56°30'W. 17.9 ft.
Set 1"x 1"x 36" Iron Rod with Brass Cap inscribed as above.

58

Section Corner to Sections 25, 26, 35, & 36.
Set from Original BT's.
Set 1"x 1"x 36" Iron Rod with Brass Cap inscribed as above.

59

1/4 Section Corner to Sections 35 & 36.
Set from Original B.T.'s.
Set 1"x 1"x 36" Iron Rod with Brass Cap inscribed as above.

60

Center of Section 26.
Set 1"x 1"x 36" Iron Rod with Brass Cap inscribed as above.
12" Fir N.85°E. 22.7 ft.
12" Fir S.85°W. 15.75 ft.

61

Center of Section 35.
Set 1"x 1"x 36" Iron Rod with Brass Cap inscribed as above.
12" Fir S.44°E. 26.0 ft.
44" Fir N.84°W. 10.0 ft.

62

Section Corner to Sections 22, 23, 26, & 27.
Found - Haines angle iron & Brass Cap & 1 1/2" Steel Shaft at corner.
Both BT's. as recorded by Haines, now dead. REN # 54
New BT's: 52" R.Fir Stump bears S.34°W. 40.6 ft. scribed S27 T22S R7W CS BT.
5" R.Fir bears N.19°E. 100.5 ft. scribed S23 CS BT.
18" R.Fir bears N.9°W. 110.7 ft. scribed S22 T22S R7W CS BT.
(NOTE - 18" FIR NOW DOWN, SHATTERED STUMP ONLY LEFT - MARCH 1962)

63

Closing Corner to Sections 25 and 36.
Found - Orig. 20", now 31" Fir N.71°W. 93.1 ft. shows good scribing
on old face.
Orig. S.W. BT. not found.
Set Brass Cap at Corner Map: County Surveyor's S25 | R6W T22S
Office, 1960 R7W S36
Rescribe 30" R.Fir N.71°W. 93.1 ft. CC S25 R7W T22S
No trees near to S.W.

64

1/4 Section Corner to Sections 13 and 24.
Found - Haines angle iron & cap at corner and BT's. scribed by H119-23
Haines 3 or 4 years ago. I also find Orig. 30", now 40" B/94
Cedar, down, shows good scribing. Checks corner location.
Haines BT's. thus: 22" R.Fir N.23°E. 68.3 ft.
17" R.Fir S.37°W. 59.6 ft.

65

RE-RENEWED, SEE CORNER NO. #184
FD OK. BY Ken Hoffman
(SEE H-117)
H-102