

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

88

C. C. Sections 33 and 34.
Set - 1" x 1" x 36" T. Iron
Scribed - 45" Inc. Cedar N.12°W. 47.0 feet.
There is a fence nailed to North side of BT.

Haines
April, 1961
C.S. File
No. 51/191

89

~~RE-NEWED CORNER NO. #108~~
1/4 Section Corner to Sections 16 & 17.
Found - 2 Fir BT's. scribed by C. S. in 1931. Ren. #21
S. E. BT. now a stump.
Set - 1" x 1" x 36" T. Iron.

90

~~RE-NEWED CORNER NO. 112~~
Section Corner to Sections 8 - 9 - 16 - 17.
Found - 2 Orig. BT's. S. E. BT. down. N.W. BT. a stump.
Set - 1" x 1" x 36" T. Iron.
Scribed - 5" Fir S.70°W. 21.0 feet.

91

1/4 Section Corner to Sections 8 and 17.
Found - 2 BT's., scribed 1931. Both BT's., now stumps. Ren. #26
Set - 1" x 1" x 36" T. Iron.
Scribed - 8" Fir N.51°W. 30.6 ft. - 10" Chqpa. S.42°W. 47.7 ft.

92

~~RE-NEWED CORNER NO. 144~~
Section Corner to Sections 7 - 8 - 17 - 18.
Found - Orig. N. W. & S. E. BT's. (These BT's scribed in 1855,
Set - 1" x 1" x 36" T. Iron reported burned in 1871
by Byers.)

93

1/4 Section Corner to Sections 17 and 18.
Found - Stump of Orig. Fir BT. (1855)
Stumps of 2 Fir BT's. scribed about 1915. Ren. #10
Set - 12" x 1" x 36" T. Iron & Scribed:
6" Fir N.87°E. 48.4 feet.
8" Forked Fir N.65°W. 110.5 feet.

94

Center of Section 17.
Found - S. W. BT., scribed by C. S. in 1931 Ren. #23
Set - 1" x 1" x 36" T. Iron.
Corner is N. 0°15'W. of true C 1/4 S.17, 2.7 feet.

95

1/4 Section Corner to Sections 17 and 20.
Found - 2 Oak BT's. Ren. #22
Set - 1" x 1" x 36" T. Iron

96

1/4 Sec. Corner to Sec. 30, T22-7W. & Sec. 25, T22-8W.
Found - Orig. 6", now 30" W.O. N.31 1/2°W. 33.7 ft., center rotted,
no scribing found. Orig. 15", now 30" W.Oak N.58°W.
66.0 ft., center rotted, no scribing found. Both BT's.
were opened years ago, possibly by Cole & each checks
record bearing and distance.

Fence To North & To West from Corner.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1961

1/4 S25/S30 T22S

New BT's:

R8W R7W

11" W.Oak bears S.80°W. 16.0 ft. scribed 1/4 S25 CS BT.

16" W.Oak bears S.24 1/2°E. 36.3 ft. scribed 1/4 S30 CS BT.

I, Henry Beckley, State that the above Orig. BT's. have been used
for Bearing Trees for approximately 40 years. See signed
Statement in File. (ALSO SEE REN. #1)

James W. Byron, Deputy
Milo Godfrey
Glete Putnam
June 6, 1961
C. S. File No. 52/14

97

West 1/4 Corner to Sec. 30, T22-6W. East Bdry. T22-7W.
Found - Fir Tree, now 40", North 58°W. 7.3 ft. (to face.)
Fir Tree, now 60", N.52°E. 13.2 ft., uprooted & down.
Set - Brass Cap with Mkd: County Surveyor's Office, 1961 T22S
New BT's: 12" D. Fir S.10°E. 24.8 ft. Mkd: 1/4 S30 CS BT. 9" D. Fir S.73°E. 22.5 ft.
Note - Haines' "T" iron previously set for 1/4 cor. by prop. meas. bears N.55°W. 37.3 ft.

Milo E.
Godfrey & Crew.
Dec. 1961
C.S. File
No. 49/143

Willford N. Haines
For - Yoncalla Lumber Co.
March 1961
Map File M 22 - 1