

Douglas County Surveyor's Record of  
Government Corners Renewed

22 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Milo E. Godfrey, Deputy  
Vernon Tracey & Clete Putnam  
August 1961  
C. S. File No. 49/143

Closing Corner Sections 24 and 25. *FD OK 2/94 BY HOFFINE C.S. 63/154-5* **98**  
Found - Haines "T" Iron & Cap - Maple tree, now 10", S.68°W. 31.0 ft., *fd. 7/96*  
previously opened, old scribing visible in opened face. *CS 63/104*  
New BT's: 28" R. Cedar N. 8°E. 26.3 ft. Mkd: "CC S24 S25 CS BT".  
12" Maple S.39°E. 13.5 ft. Mkd: "CC S24 S25 CS BT."

Corner to Sections 19 and 30 only, T22S R6W, West Boundary-E. Boundary of 22-7. **99**  
Found - Fir Tree, now 42", N.80°E. 13.9 ft. (21 lks. instead of 91 lks.)  
Old scribing "S6W S19 B" found. *#197*  
Maple Stool, showing evidence of a shoot North of present shoots,  
broken off & rotted away, bears S.20°E. 91 lks. instead of 21 lks.  
No scribing found.

Note - I believe distances to these BT's. were reversed in Nicklin's notes.  
The Closing Corner of Secs. 24 & 25, T22SR7W bears South from this corner  
281.8 ft. (Record was South 266.6 ft.) Also calls on creek crossings &  
top of spur North & South of this point fit Original calls.

Set - Iron Pipe with Brass Cap Mkd: County Surveyor's T22S R6W | S19  
Office, 1961 | S30  
New BT's: 7" Fir S.57°E. 9.6 ft. Mkd: S30 CS BT.  
5" Fir N.36°E. 11.6 ft. Mkd: S19 CS BT.  
From this corner Haines' Monument (for same corner) bears S.75°W. 48.0 ft.

Section Corner to Sections 19 - 20 - 29 - 30. **100**  
Found = 3/4" Iron Pipe 1 foot above ground.  
Bl. Oak, now 36", N.21°E. 143.3 ft. (to face) good scars. *REN #25*  
Fir, now 32", N.25°W. 89.6 ft. (to center of tree) shows good  
scars, did not open. *#189*  
New BT's: 18" W. Oak S.60°W. 59.1 ft. Mkd: T22S R7W S30 CS BT.  
16" Maple (in clump of Maples) S.89°E. 52.5 ft. Mkd:  
T22S R7W S29 CS BT.

1/4 Section Corner to Sections 14 and 13. **101**  
Found - Haines' "T" Iron & Cap at Corner, Also Cedar Stake set  
by Cole, rotted off. - *Ren. #2*  
Old Fir Stump N.5 1/4°E. 93.7 ft., badly burned, no scribing found.  
Stump Hole with remains of Fir Stump in place S.58 1/2°E. 101.6 ft.  
(The 2 above were Cole's BT's.)  
Remnants of old Cedar Stump N.1°E. 17.2 ft. (Orig. BT.) no scribing.  
22" Fir N.11°E. 41.3 ft., open scar, pitch covered, shows  
scribing, probably mkd. by Haines.  
Set - Alongside "T" iron, Brass Cap Mkd: County Surveyor's Office, 1961  
T22S R7W 1/4 S14/S13  
New BT's: 15" R. Cedar S.78 1/2°W. 29.8 ft. Mkd: 1/4 S14 CS BT.

Milo E. Godfrey, Deputy County Surveyor  
Vernon Tracy & Clete Putnam  
December and January 1961  
C. S. File No. 52/14

*FD OK  
4-93  
BY K. HOFFINE  
M117-4*

*SEE  
E*

*REVERSE  
SIDE*