

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 22 S T. S. R 7 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

107

Witness Corner to Sections 16 - 17 - 20 - 21.
Found - Old Fir Stump, scars on SE, SW, NW & NE, found scribe mk. "S" on S.E. Face.
Badly rotted Fir Stump S.26°E. 15.2 ft. Cut open & found scribing "T22S R7W S". (These trees called for in old) Fir Roots N.59°E. 10.6 ft. (fenewal, by Roberts ?, 1904-08?) Stump Hole S.54°W. 22.4 ft. (See F.B. #17, Page 5) Stump Hole N.40³/₄°W. 22.4 ft.
No trace of Original Bearing Trees.
Set - Wit. Cor. 4 ft. North of Corner Stump - Set Brass Cap Mkd: County Surveyor's W.C.

S17	S16
S20	S21

 4 Ft. S. to corner. Office, 1962
New BT's: 18" D.Fir S. 5°E. 146.3 ft. Mkd: T22S R7W S21 CS BT.
17" D.Fir S.47°W. 116.6 ft. Mkd: T22S R7W S20 CS BT.
6" W.Oak N.48¹/₂°W. 114.4 ft. Mkd: T22S R7W S17 CS BT.
18" D.Fir N.14°E. 204.2 ft. Mkd: T22S R7W S16 CS BT.
Fence Corner bears East 3 ft. from Stump Corner - Fences E. & S..

*FDOK
4/94 BY D. BENTZ
1994-0053
FOR R. RUELE*

*Fd. ok
5/16/89
L. ROBERTS
C.S. 62/91*

108

¹/₄ Section Corner to Sections 16 and 17.
Found - Haines' "T" Iron at Corner & Rotted remnants of Fir Stumps in stump holes. This is all that remains of Orig. BT's.
Fir Stump, 18", S.49¹/₂°E. 21.2 ft. Portion of scribe mark visible on old face near top of stump.
Fir Tree, 18", S.44¹/₂°W. 17.8 ft., shows good scar. This tree still alive & in good condition. (This tree & stump mkd/ by Eppstein in 1931)
Did Not Set Brass Cap.
New BT: 3" D.Fir S.86°E. 41.0 ft. Mkd: ¹/₄ S16 CS BT.
A fence corner bears East approx. 50 ft. Fences N. S. & W. This is Gordon & Gardiner ¹/₄ Corner established in 1855.

*Fd. ok
5/14/89
C.S. 62/91 L. ROBERTS*

109

Section Corner to Sections 20 - 21 - 28 - 29.
Found - 2" Iron Pipe & Fir Tree, 60", S.52°W. 67.3 ft. Had been opened previously & old face visible. Good reverse scribing "B" found on chip lying in notch.
Badly rotted Fir Stump N.40°W. 126.7 ft. No scribing found.
Old Fir Stump, 48", S.67°E. 133.3 ft. Did not chop open.
Did Not Set Brass Cap.
New BT's: 15" D.Fir S.27°E. 40.3 ft. Mkd: T22S R7W S28 CS BT.
29" D.Fir S. 4°W. 30.6 ft. Mkd: T22S R7W S29 CS BT.
23" D.Fir N.12¹/₂°W. 116.8 ft. Mkd: T22S R7W S20 CS BT.
20" D.Fir N.54°E. 110.9 ft. Mkd: T22S R7W S21 CS BT.

*Fd. 5/89
D. BAKER
101-55*

110

¹/₄ Corner to Sections 20 and 21 .
Found - Rock 8" x 12" x 30" Set by Cole in 1913, No markings found. Corner lies on open grass slope with no other rocks in the vicinity. It checks out directly south from cor. secs. 16-17-20-21 & also fits Orig. call from top of ridge. Rock set 24" in ground.
Set - Brass Cap alongside Rock Mkd: County Surveyor's Office, 1962

T22S R7W	¹ / ₄ S20/S21
----------	-------------------------------------

New BT's: 36" W.Oak N.27°E. 203.6 ft. Mkd: ¹/₄ S21 CS BT.
24" W.Oak S.17°W. 278.6 ft. Mkd: ¹/₄ S20 CS BT.
Corner on open, grassy, south slope 365 ft. South or Ridge Top.

*Fd. 5/89
D. BAKER
1101-55*

111

Section Corner to Sections 4 - 5--8 - 9.
Found - Fir Tree, now 54", N. 3°E. (instead of N.10°E) 19.8 ft. Faint bark scribing visible in charred bark "S4 T22S"
Fir Tree, 38", S.15°W. (instead of S.20°W) 5.9 ft. Faint bark scribing visible "S8 T2".
Fir Tree, now 56", N.70°W. (instead of N.60°W.) 31.7 ft., slope dist. No scribing fd, cruisers marks nearly cover side facing corner.
40" Fir S.50°E. 7.3 ft. is uprooted & down & almost completely buried in dirt & debris.
Set - Brass Cap at Cor. Mkd: County Surveyor's

T22S R7W	S5 S4
Office, 1962	S8 S9

Rescribed
New BT's: 54" Fir N.3°E. 19.8 ft. bark scribe T22S R7W S4 CS - BT in wood.
38" Fir S.15°W. 5.9 ft. scribed in wood T22S R7W S8 CS BT.
56" Fir N.70°W. 31.7 ft. (slope dist) bark scb. T22SR7W S5 "BT" in wood.

Milo E. Godfrey, Deputy County Surveyor
Vernon Tracy & Clete Putnam
March 1962
C. S. File No. 52/14

New BT: 10" B. Cedar S.17°E. 39.7 ft. Mkd: T22S R7W S9CS BT.

WOOD