

Douglas County Surveyor's Record of
Government Corners Renewed

T. 22 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section Corner to Sections 8 - 9 - 17 - 16. **112**
 Found - Fir, 36", S.55°E. 7.3 ft., uprooted & down, good bark
 scribing visible on under side "S16 T2 R7W".
 48" Fir Stump, N.68°W. 15.8 ft. Bark mostly gone from
 side facing corner. No scars or scribing found.
 Badly rotted remnants of old Maple Stump N.54°E. 25 ft.
 No trace fd. of S. W. BT.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T22S R7W S8 | S9
 Office, 1962 S17 | S16
 5" Fir scribed by Haines in 1961 bears S.61°W. 17.7 ft. scribed:
 "S17 T22S R7W BT".
 New BT's: 4" D.Fir N.60°W. 9.1 ft. Mkd: S8 CS BT.
 4" D.Fir S.25°E. 25.8 ft. Mkd: S16 CS BT.
 No suitable tree near in N.E. Quadrant.
 Haines "T" Iron Set in 1961 bears S.70°E. 4.7 ft. Ren. #90
 Fence Corner, Fences West & North, bears N.82°W. 8 ft.

*FD OK 5/5/89
L. ROBERTS
C.S. 63/18*

$\frac{1}{4}$ Corner to Sections 4 and 9. **113**
 Found - Rotted W. Fir Snag S.67 $\frac{1}{2}$ °W. 38.3 ft. Opened & found
 good scribing "B. T."
 54" D.Fir Stump N.75°E. 8.6 ft. Did not cut open.
 Set - Brass Cap at Corn Mkd: County Surveyor's T22S R7W $\frac{1}{4}$ S 4
 Office, 1962 S 9
 New BT's: 16" D.Fir N.56°W. 84.2 ft. Mkd: $\frac{1}{4}$ S 4 CS BT. **160**
 60" D.Fir S. 3°W. 30.0 ft. Mkd: $\frac{1}{4}$ S 9 CS BT.
 4" x 4" Sq. Stake, 2 ft. above ground, painted white & Mkd:
 "S $\frac{1}{4}$ S4" on North face bears S.48°W. 4.2 ft.

Milo E. Godfrey, Deputy County Surveyor
 Vernon Tracy and Cleve Putnam
 March 1962
 C. S. File No. 52/14

Sec. Cor. to Secs. 6 - 7, T22-7W. & Secs. 1 - 12, T22-8W. **114**
 Found - Rock Set by B.B. Irving, 1929. Rock had fallen over but
 apparently had not slid away from corner. Reset Rock
 & piled mound of rock around it. (Sec #27 of T. 22-8)
 32" Fir N.15°W. 15.8 ft., good bark scribing visible,
 Blaze & scribe "BT" in wood.
 48" Fir S.42°E. 27.7 ft. good bark scribing visible,
 Blaze & scribe "BT" in wood, top of tree now dead.
 60" Dead Fir S.42°W. 23.1 ft. good bark scribing visible.
 Blaze & scribe "BT" in wood. No live trees avail in S.W.
 No trace found of N.E. BT.
 Blaze & Scribe 16" Hemlock N.39°E. 48.7 ft. Mkd: T22S R7W S6 CS BT.
 Corner lies on very steep N.E. Slope approx. 300 ft. North of
 top of ridge.

*FD OK 7/5/85
L. ROBERTS
M 90-74 CS 63/18*

$\frac{1}{4}$ Corner to Sec. 7, T22-7W. & Sec. 12, T22-8W. **115**
 Found - Plowshare Set by B.B. Irving in 1929, nearly buried in ground.
 Alongside plowshare Set Brass Cap Mkd: County Surveyor's Office, 1962
 T22S $\frac{1}{4}$ R8W S12/S7 R7W.
 Corner lies on open grassy slope. No trees within 500 ft.
 Note - Mr. Haines' house bears S.10°W. approx. 550 ft. from corner. Sec #28 of T. 22-8

*FD OK L. ROBERTS
6/27/85
M 90-74
CS. 63/18*

Sec. Cor. to Sec.s 7 - 18, T22-7W. & Secs. 12 - 13, T22-8W. **116**
 Found - Haines' "T" Iron & 19" W.Oak S. 64°W. 205.5 ft. Shows good scar. Ren #29 of T. 22-8
 26" W.Oak S.78°W. 176.1 ft., shows good scar.
 17" W.Oak, N.70°W. (not N.79°W) 189.9 ft. Has been opened
 previously, scribing visible "S" & "2".
 Blaze & Scribe 9" W.Fir N.59°W. 205.5 ft. Mkd: T22S R8W S12 CS BT.
DID NOT SET BRASS CAP.