

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 22 S. T. S. R. 7 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Wilford N. Haines  
Found by Milo E. Godfrey & Crew  
June 4, 1962  
C. S. File No. 52/14

*FD OK 4-93-4 M 11-7-4 K. HOFFMAN*  
*Unrecorded*  
1/4 Corner to Sections 14 and 23. 130  
Found - Haines' "T" Iron & Cap. - 63" Fir N.31°E. 54.8 ft. Orig.  
calls for 8" Fir N.31°E. 54.8 ft. This tree recently bark  
scribed "1/4 S14 363 BT". -Ren # 5  
20" Bl. Oak S.38°E. 99.0 ft. Cut open, tree hollow, has been  
cut open, several years ago & all marks, if any, are rotted away.  
Cole calls for 10" Oak S.44 1/4°E. 99.0 ft.  
Stump Hole with some old Fir Bark still in place S.40°W. 38.3 ft.

1/4 Corner to Sections 27 and 34. 131  
Found - Haines' "T" Iron with wooden stake alongside, old piece of wood  
with good reverse scribing is nailed to wooden stake, could  
not find where it came from. Ren. # 142  
54" Fir Stump bears South 33.0 ft. No scars or scribing visible.  
No evidence of chopping found on it.  
No trace could be found of N.E. bearing tree.  
9" D.Fir, recently scribed "1/4 S34 BT" bears S.28 1/2°W. 35.8 feet.

Wilford N. Haines  
For E.G. Whipple Mill  
March - April 1960  
Map File M 18 - 33

Standard Corner to Sections 3 and 4, T23-7W. 132  
Found - 1" Iron Pipe and 3 Bearing Trees:  
36" D.Fir S.28°W. 18.0 ft.  
24" Laurel S.47°W. 63.0 ft.  
20" Fir S.26°E. 55.0 ft.

Standard 1/4 Corner to Sections 3, T23-7W. 133  
Set - 1" x 1" x 36" T. Iron  
Scribed 24" R. Cedar S.29°W. 26.5 feet.

Standard Corner to Sections 3 and 2 only, T23-7W. 134  
Found - 1" x 1" x 36" T. Iron (See Ren. #170)  
Original S.W. BT. - New BT: 10" Fir S.65°E. 29.5 feet.

Wilford N. Haines  
For Woolley & Whipple  
April 1961  
C.S. File 51/191

North 1/4 Corner to Section 4 only, T23-7W. 135  
Set - "T" Iron & Cap. - M38-69  
12" D.Fir S.57°W. 21.1 ft., blazed & scribed, not legible, completely  
pitched over, Haines' metal disc on tree.  
An old Oak Stump, uprooted, showing an upper & lower scar, both of  
which are completely rotted out inside bears S.87°E. 641.8 ft.  
Gov't. notes call for a 20" W.Oak S.87°E. 607.2 feet.  
No trace of old S.W. B.T. found.  
Note - This corner visited by Milo E. Godfrey & Crew, June 1962.  
See C.S. File No. 52/14

Wilford N. Haines  
March 1957  
M 4 - 52 *NOT SOURCE*

South 1/4 Corner to Section 34 only. 136  
Point for corner located by prop. measurement.  
Set - 1" x 36" T Rod at corner point with brass cap inscribed,  
"Wilford N. Haines, Survey Point, #239". *this fd. cor on N. 84s of 22-7 OK 4/90*  
Note - ~~Haines Corner found by Godfrey's crew, May 1962, See C.S. File 52/14~~

Wilford N. Haines  
Sept. 1960  
Map M 11 - 72

1/4 Corner to Sections 10 and 15. 137  
Set - 1" x 1" x 36" T. Iron with brass cap inscribed.  
Scribed: 12" Cedar N.56°E. 25.4 ft.  
10" W.Fir S.37°W. 22.8 ft.  
Note - Corner found by Milo E. Godfrey, May 1962, See C.S. File 52/14

Milo E. Godfrey & Crew  
June 11, 1962  
C.S. File No. 52/14

1/4 Corner to Sections 9 and 10. 138  
Found - Haines "T" Iron & Cap at Corner. Ren. # 73  
40" Fir S.40°E. 9.2 ft., fragment of old bark scribing visible "1/4".  
40" Fir S.1°W. 9.9 ft., shows good axe scar at bottom (B.T. scar)  
Haines has reblazed & scribed, in wood. Both old B.T.'s.  
New BT's: 15" D.Fir N.75°E. 20.1 ft. Mkd: 1/4 S10 CS BT.  
7" D.Fir N.36°W. 28.3 ft. Mkd: 1/4 S 9 CS BT.