

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 22 S. T. S. R. 7 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

Center of Section 28.

Set - "T" Iron, 1"x1"x36" and  
Scribed: 6" Fir N.25°W. 82.6 ft.  
10" Fir S.46°E. 121.1 ft.

167

1/4 Corner to Sections 33 and 34.

Set - 1" x 1" x 36" "T" Iron  
Scribed - 11" W.Fir N. 49° W. 171.3 feet  
12" W.Oak S. 27° E. 359.1 feet.

168

April, 1961

Sec. Cor. to Sections 1 & 2 only, T23-7W.

Set from Orig. Bearing Trees.

Set - 1"x1"x36" Iron Rod with Brass Cap inscribed:  
"Wilford N. Haines #239 Survey Point".

169

Sec. Cor. to Sections 2 & 3 only, T23-7W.

Set - 1"x1"x36" Iron Rod with Brass Cap inscribed: #134

"Wilford N. Haines #239 Survey Point.

Found - S. W. BT. & 10" Fir S.65°E. 29.5 feet.

170

Oct. 1957

Closing Corner for Secs. 4 and 3, North boundary.

Found - Haines "T" Iron and cap. Ren. #127

A 12" Red Cedar now 18", S.17°E., 41.8 ft. scribe visible.

D. Fir, 64", S.20°E., 37.6 ft. Is now blown down.

Set - 1" x 30" Iron pipe with brass cap marked:

COUNTY SURVEYORS

OFFICE

1975

T 21 S R 7 W

S 33

S 4 | S 3

T 22 S R 7 W

CC

New BT - A 6" Hemlock, S.48°E., 43.2 ft. mkd. CC T22S R7W S3 CS BT.

We set Haines "T" iron along side the cap. Corner lies in bottom of draw center line north-south.

Compass declination: 20° east.

1/29/75

South Corner to Sec. 23 and 24 only

REN # 125

Found-1" X 1" T Iron set by Haines, only remooaning orig. BT

A 6" now 23" D Fir with orig. scribe marks and rescribing by Godfrey

(Ren.# 125) visible on unhealed blaze bears N31 1/2°E., 29.0 ft.

A BT marked by Godfrey, a29" now 32" D. Fir alive and well Healed bears

S23°E., 13.3 ft.

Set- 1" x 30" I.P. with brass cap attached, Marked

T22S R7W

DOUGLAS CO. SURVEYOR

1975

S23 S24

S26

We place Haines T iron alongside the brass cap Compass Declination Setting 20°E.

Closing Corner Sec. 26&25

REN#57

Found- 1"x1" T-iron set by Haines in 1957 near the base of a 30" D.fir.

An Orig. 8" now 30" D. Fir, alive and completely Healed bears S59°E., 33.0 ft.

An Orig. 50" now 60" D. fir scribing visible on previously opened blaze,

bears S85°W., 26.4 ft. We do not set a brass cap.

New BT-An 18"D.Fir bears S40°W., 57.9 ft. scribed "CC T22S R7W S26 CS BT"

in a double blaze. Compass Declination setting 20° East 12/29/75

SE Cor. DLC #42

Found - An 18"x18"x24" sandstone, firmly set 10" in the ground, with a  
chiseled "X" on top and chiseled "Cl 42" on NE face. Ren. #17

From which:

A point of exposed bedrock with chiseled markings "X Cl 42" bears  
S.29°W., 22.3 ft. (rec. per Ren. #17, S.25°30'W., 22.0 ft.)

We cannot detect any signs of disturbance in the vicinity of the found stone even though it's position disagrees with the recorded measurements to the found

174

Gary L. Langlitz

Karen Cheney

Oct. 26, 1976

C.S. 59/24

Doug. Co. Surveyors

Wilford N. Haines  
Whipple and Woolley  
C.S. 51/191 - M 38-69  
Filed 12/8/69

MARCH 71

Wilford N. Haines  
For: E.G. Whipple  
Map M 1 - 59  
C.S. File 42/309

JAN. 1972

Gary C. Commons  
Peter L. Earle  
Surveyors office  
Jan. 29, 1975  
C.S. 57/17

Gary L Langlitz  
A. Vic Cangie  
M. Lenora Ladig  
12/29/75  
CS 57/39

Fd. 3/10  
CS 63/104

FD. 6/91  
M 113-26