

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 22 S. T.S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(Continued)
Doug. County Surv.
Sept. 21, 1981
C.S. 61 / 27

New BT's continued -
16" D. Fir scribed "T22S R6W S30 CS BT" on double blaze, bears
N.71°E., 42.8-ft.
Note - Haines "T" Iron bears S.8 1/2 °E., 6.25-ft.

9/21/81

185

Doanld Branch
For: U.S. Nat. Bank
June 16, 1986
M 102 - 29

Section corner for section 7 & 8 T22-6, and secs. 12 & 13, T22-7.
CORNER REPORT ONLY

Found - A 4" x 4" "X" on 4'x 6' bedrock.
18" fir with B.L.M. tag, Haines disc., healed blaze bears S53°W
25.17'. Record per B.L.M. tag agrees with measured.
12" fir with healed blaze and B.L.M. tag, Haines Ren #34
disc bears N62°E, 18.03'.

186

Charles W. Guile
For: Weyerhaeuser Co.
April 15, 1987
C.S. 63/54

Center 1/4 Corner for Section 12
Found - Angle iron with 1" brass disc mkd. "Wilford N. Haines
239 Survey Point" Ren. \$41
21" fir, S.32°W., 39.6 ft.
Double Maple, 36" +, S.78°W., 80.5 ft.
Weyerhaeuser BTs:
16" Fir, S.86°W., 21.0 ft. with "W" nail.
16" Fir, N.10°W., 23.5 ft. with "W" nail.

4/15/87

187

1/4 Corner for Sec. 12 and Sec. 7 of T.22-6
Found - Angle iron with 1" brass disc mkd. "Wilford N. Haines 239
Survey Point". Ren. No. 33
20" Fir with blaze, N.73½°W., 58.5 ft.
24" Fir with blaze N.45°E., 41.9 ft.
New BT - 6" W. fir, N.46°E., 7.95 ft. to "W" nail with "X" at breast
height.
10" Fir, S.32°E., 3.85 ft. to "W" nail.

4/15/87

188

Douglas County
Surveyors office
Randall Smith
Stephen Flause
June 30, 1987
C.S. 62/45

North 1/4 Corner for Section 6 only of T.23-7
Found - 1962 Douglas County brass cap on a 1½" O.D. iron pipe leaning
1.3 ft. southeast; protrudes 9" above ground. Ren. #121
(No original bearing trees found. All bearings and distances taken to
plumb position of brass cap/iron pipe.)
16" now 29" dia. W. oak with a previously opened blaze (no
scribing found) bears S.7°W., 79.2 ft. (agrees well with rec.)
8" now 33" dia. W. oak with a fully healed single blaze bears
S.21½°E., 131.5 ft. (Rec. S.20°E., 130.0 ft. distance is a
face measurement per Ren. #27A of T.23-7)
20" now 24" dia. W. oak with a fully healed double blaze bears
S.4°W., 62.3 ft. (agrees well with rec. per Ren. #121)
21" now 36" dia. D. fir with a fully healed single blaze bears
S.33°E., 60.5 ft. (Rec. S.33°E., 59.8 ft. distance is a face
measurement per Ren. #121)
Set - Douglas County brass cap and iron pipe returned to plumb
position. Protrudes 9" above ground.
Monument lies at the intersection of a east-west and south running fence
lines.

6/30/87

189

John Hollingsworth
For: Ore. State
Parks & Recreation
Feb. 25 1987
M 104 - 77
C.S. 63/62

Center 1/4 Corner for Section 15
Found - 1965 BLM iron pipe with brass cap firmly set.
24" white fir stump, S.70°E., 11.9 ft. to center, tree has broken
off and rolled down hill, has partially visible scribe marks.
12" rotten maple log, N.63°W., 46.0 ft. no marks visible.
New BTs - 28" fir, S.73°E., 58.6 ft. to 2 finish nails side and center,
blazed and scribed "C 1/4 S15BT", attached Parks corner tag.
5" fir, S.64°W., 7.52 ft. to 2 finish nails side and center,
blazed and scribed "X BT", set orange Carsonite post with decal
marked "Property Boundary-State Park Land Behind this Sign" 2 ft.
southeast.

2/25/87

190