

Douglas County Surveyor's Record of  
Government Corners Renewed

T 22 T. S. R 7 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

191

1/4 Corner for Sections 14 and 15.  
Found - 1965 BLM brass cap on 2 1/2" I.P. Top of I.P. may have slid 0.20 ft. east. (down the hill).  
14" fir N.27 1/2°W., 20.5 ft. to center with healed over blaze scar attached to Parks corner tag.  
Fir stump N.40°W., 33.0 ft. to center, no marks visible. (orig.)  
Did not check Cole's tie to tunnel or BLM tie to U.S.C. and G.S. BM L246, 1934, because of hazard. Ren. #3  
No evidence of BLM SE bearing tree.  
New BT - 5" fir S.73 1/2°E., 10.13 ft. to two finish nails, blazed and scribe "1/4 S14 BT" attached parks corner tag. Set orange Carsonite post with decal marked "Property Boundary - State Park Land Behind This Sign" 2.0 ft. west.

FD OK  
2/90  
O.D.O.T  
BY K. HOFFINE  
M117-4

John E. Hollingsworth  
For: Oregon State  
Parks & Recreation  
Division  
1987  
M 104 - 77  
C.S. 63/62

1/21/87

192

Section Corner for Secs. 14, 15, 22 and 23  
CONDITION REPORT ONLY  
Found - 1965 BLM brass cap firmly set and 0.3 ft. above ground.  
34" W. fir snag N.22 1/2°E., 263.3 ft. with rotted face in open blaze.  
31" fir N.24 1/2°E., 279.2 ft. scribes visible "T22S R7W S14 BT" (NO REC)  
20" fir S.83 3/4°E., 186.8 ft. with healed blaze scar.  
34" fir S.81 1/4°W., 252.8 ft. with healed blaze scar.  
20" Oak N.74°W., 145.9 ft. with healed blaze scar.  
Set orange Carsonite post with decal marked "Property Boundary - State Park Land Behind this Sign" 2.0 ft. northwest.  
Elk Creek Tunnel Forest State Park. Corner falls in a field 116.2 ft. east of a north-south fence and 306.9 ft. south of an east-west fence. Bearings and distances by hand compass and steel tape.

3/10/87

Les Roberts  
For International  
Paper Company  
M 108 - 22  
C.S. 63/91  
May 24, 1989

1/4 Corner for Sections 9 and 16  
(No evidence found or original corner)  
Set - 3/4" x 36" aluminum rod with 3 1/4" alum. cap by single proportionate measure. Buried purple magnetic marker under 36" alum. rod. Set alum. post, with land survey monument sign bolted to, beside alum. cap.  
New BTs- 33" Fir bears S.02°W., 29.1 ft. (Scribed/painted red)  
48" Fir stump bears N.34°W., 84.0 ft. (Scribed/painted red)  
Corner lies on South slope at the edge on a new clear cut unit.

5/24/89

193

Ken Hoffine  
L.S. #2291  
For: Lone Rock  
Timber Co.  
March, 1990  
C.S. 63/104

Section Corner for Secs. 23 and 24 only. (South)  
Found - Corner is a 1" I.P. with DCSO brass cap. Ren. #172  
1" x 1" T iron set by haines along side cap.  
26" D. fir bears N.31 1/2°E., 29.0 ft. healed face with both county and BLM BT tags. Orig. BT.  
34" D. fir bears S.23°E., 13.3 ft. well healed face with both County and BLM BT tags. Ren. No. 125  
Found BT of no record:  
8" maple bears West 52.5 ft. scribing visible, no BT tag so put up a Lone Rock Timber location tag with above information.

194

Ken Hoffine  
For: Lone Rock  
Timber Co.  
Gary Angiolet  
Oct. 1990  
C.S. 63/127

Closing Corner for Section 36; and Sec. 31 of T.22-6  
CORNER REPORT ONLY  
Corner is a 1956 GLO brass cap 1.0 ft. above ground in good condition  
18" D.F. bears N.39 1/2°E., 60.0 ft. Well healed face. WE tag.  
42" D.F. bears N.39°W., 49.5 ft. Well healed face and BT tag.  
38" D.F. stump (covered with tin) bears N.16°W., 23.5 ft. scribing visible and BT tag. NO RECORD.  
Haines T Iron bears S.38 1/2°E., 14.0 ft. Ren. No. 29  
Painted faces and wrote BT on tree trunks of BTs with flourescent orange paint. Corner sits on 40% west slope approx. 100 ft. east of Brush Ck. Rd.

195

10/90

RE-RENEWED, SEE CORNER NO. #199