

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 22 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

201

Harvey Wilcox  
Aug. 4, 1993  
C.S. 63/138  
(Corner Restoration Form)

Center South 1/16 Section 7.

- Found - 28" D.Fir stump w/healed face and tag, bears N.41°E., 6.6 ft.  
34" D.Fir stump w/healed face and tag, bears S.41°W., 20.5 ft.  
5/8" Iron rod 30" long with plastic cap marked Stuntzner Engr. bears N.87°E., 4.70 ft.  
5/8" Iron rod 30" long with plastic cap marked Stuntzner Engr. bears S.13°W., 5.93 ft.
- Set - Replaced the iron pipe and brass cap back to the position it was in before the area was logged. We used the 5/8" iron rods that we set prior to the logging to reference the corner back in place. Placed the same monument that we removed back in a new mound of stones.
- Note - Corner falls on rocky spur ridge in logged off area.

202

Ken Hoffine  
For: Lone Rock Timber  
C.S. 63/154-5  
Feb. 1994

North 1/4 Corner for Section 1 T.23S.R.7W only. See renewal # 122.

- Found - Haines T-Iron 1.5 ft. above ground.
- BTs - 30" D.Fir stump bears S.2°E., 69.5 ft. No marks, (rec. S.1°E., 70.5 ft.)  
10" D.Fir bears S.21°E., 14.3 ft. I scribe BT and tag tree.
- Note - Ground on steep south slope approximately 40 ft. north of shallow bowl like head of draw. Clearcut to west of corner.

203

Ken Hoffine, LS 2291  
For; Lone Rock Timber  
M 119-23  
3/94

1/4 Cor. Secs. 11 & 12

- Found - Haines T-Iron in good condition. (Ren. # 38)  
30" Douglas Fir stump bears N.52°E., 47.7', bark scribed & BLM tag.  
4'x4'x5' rock with chopped "X" on face bears S.87°W., 15.5', I paint.  
6'x6'x6' rock with chopped "X" on face bears N.52°E., 5.1' I paint.
- New BT- 7" Douglas Fir, bears S.24°E., 8.5', I tag tree.
- Note - Corner lies on extremely steep rock West slope.

5/94

Les Roberts, L.S. 1039  
For: Seneca Jones  
Timber Co.  
Dec. 1994  
M 121-27

Cor. Secs. 1 & 12: 6 & 7 T22-6

- Found - Haines "T" iron set in survey M 3-22 (Ren. #32)  
24" Fir, N.17°W., 21.5' (scar vis.) 1956 BT.  
36" Fir, S.43°E., 51.5' (rec. S.22°30'E., 73.8') (scar vis.) 1956 BT.  
40" Fir, S.06°E., 45.7' (rec. 70.8') (scar vis.) 1956 BT.

204

NE Township Cor. T22-7 (NE Cor. sec. 1)  
CONDITION REPORT ONLY

- Found - 1986 BLM iron pipe & brass cap.  
28" Fir snag, N.59°E., 37.0' (scribe vis.), 1855 BT.  
1966 Douglas County brass cap, 0.55' south of 1986 BLM iron pipe & brass cap. (Ren. #162)  
14" Hemlock, N.26°W., 13.2' (scribe vis.), 1966 BT.  
15" Hemlock, N.80°E., 25.0' (scribe vis.), 1966 BT.  
30" Hemlock, S.61°E., 30.0' (scribe vis.), 1966 BT.

1/9/95

206

KEN HOFFINE  
LONE ROCK TIMBER  
DEC. 1994  
M 121 - 43

EAST 1/4 OF SEC. 13

- FOUND - Haines T-iron
- BTs FD - 24" D.Fir, bears N.8°E. 24.5', no face 3 B.T. tags  
52" D.Fir, bears S.10°W. 25', no face LRT location tag  
Orig. 12" D.Fir, is a 55" rotten stump, bears N.85°W. 17.8'.  
old face visible no scribing.  
Orig. 10" Maple, is a 21" wind fall, bears S.55°E. 6.6', no visible scribing.
- corner lies on a 50% southwest slope. BLM clearcut to the Northwest.