Douglas County Surveyor's Record of Government Corners Renewed

22 · T. S. 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 81052

INTERIOR "L" COR. OF CL. 47 — 19
Renew from old B.T.s — See 1963 Gov't. B.C.-Vol. 33, Pg. 13734
Set in 1½" x 30" Iron pipe, from which
A 18" Fir, bears N.54¼°E. 67 lks. dist.
A 18" Fir, bears N.79¼°W. 28½ lks. dist.

SEC. COR. OF 8-9-16-17 — 20
Renew from old B.T.s
Set in 1½" x 40" Iron pipe, from which
A 30" Fir, bears S.56°W. 23 lks. dist. old tree
A 24" Fir, bears S.10°E. 30 lks. dist. old tree
A 72" Fir, bears N.60°E. .05 lks. dist. old tree
A 34" Fir, bears N.31¼°W. 48 lks. dist. old tree
RE-ESTABLISHED CORNER NO. 74

S.W. COR. OF ABEL P. FRYER CL. 47 — 21
Renew from old B.T.s
Set in a 1½" x 40" Iron pipe, from which
A 12" W. Oak, bears N.82°E. 90 lks. dist.
A 12" W. Oak, bears N.71½°E. 81 lks. dist.
RE-ESTABLISHED CORNER NO. 80

N.W. COR. OF SIMON P. ALLINSWORTH CL. No. 46 — 22
Renew from old B.T.s — See 1963 Gov't. B.C.-Vol. 33, Pg. 13734
Set in 1½" x 30" Iron pipe, from which
A 60" Fir, bears N.67°E. 84 lks. dist. old tree
A 18" Fir, bears S.62°E. 47 lks. dist. old tree
A 10" Fir, bears S.02½°E. 31 lks. dist. old tree

S.W. COR. OF CL. 46 — 23
Renew from old Gov. B.T.s — See 1963 Gov't. B.C.-Vol. 33, Pg. 13733
Set in 1½" x 24" Gal. Iron Pipe, from which
A 20" Fir, bears N.9°W. 05 lks. dist.
A 30" Fir, bears S.79¼°W. 10 lks. dist.

N.W. COR. OF JOHN E. GARDNER CL. 51 — 24
Renew from old B.T. — See 1963 Gov't. B.C.-Vol. 33, Pg. 13732
Set in a 1" x 24" Iron Bar, from which
A 30" Fir, bears N.46½°E. 50½ lks. dist.
A 24" Fir, bears S.42½°E. 32 lks. dist.

N.W. COR. D.L.C. 50 — 25
Reset from old Myrtle B.T.
By setting a 10" x 10" x 3" sandstone Rock from which
A 8" ash, bears N.34°E. 12.4 ft. dist. C.S. B.T.
RE-ESTABLISHED CORNER NO. 76 (SEE REN. #34)

N.E. COR. D.L.C. 40, (44 - T22-7) — 26
Location identified from old snag of both original B.T.s
Set a sandstone 6" x 6" x 12" for corner from which
A 22" Fir bears S. W. lks.
Scribed Cl. 44 C.S. B.T.
RE-ESTABLISHED CORNER NO. #148 - T22-7W

SEC. COR. 1,6,12,7 — 27
Identified location from 4 O.B.T.s which I followed and scribed
Set a sandstone 7" x 12" x 28" for corner with a X chiseled on top. 12C.S. on S.W. face 1 on N.W. face 6 on N.E. face and 7 on S.E. face.
RE-ESTABLISHED CORNER NO. 60

¼ SEC. COR. E SIDE SEC 12 — 28
Location identified from snag of Orig. B.T. Set a plow share for corner. On account of last summers fire there were no live trees in sight of the corner to mark for B.T.s except by going an excessive distance.
RE-ESTABLISHED CORNER NO. 61

N. W. Corner Section 12. — 28A
Set Sandstone 7"x12"x28" long securily in the ground & supported by Mound of Rock in the location as determined from all four of Orig. BT's.
Reblaze & scribed all BT's.
SAME AS # 56

66

Sept. 1917 F.B. 43, Page 12 C.S. Vol 3, Page 1

F.B. 43, Page 13

F.B. 43, Page 14

Witnesses
F. C. Frear Deputy County Surveyor
Chas. C. S. Clements
F. R. S. Solomon

Apr. 30, 1920

Sept. 1917

Ben R. Irving Dep. Co. Surv.
N. E. Richardson
Oliver Haines
Dec. 1929

C.S. File 14/38 M6-7

C.S. 14/38