

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 8 R. W. W. M.

✓ SEC. COR. 12,7,13,18 29
Set an oak post properly marked and with a 1" x 60" pipe driven for the corner. Location determined from an old down and partially burned fir. This tree was shown to have by J.W. Jones and old resident who had seen the scribe marks many times. Upon measuring out the proper distance, found the remains of an old Oak stump of proper size and position to have been the other B.T. Set as new B.T.s
A 12" W. Oak S.64°W. 205.5 ft. dist.
A 14" W. Oak, S.78°10'W., 176.1 ft. dist.
A 12" W. Oak, N.78°51'W., 189.9 ft. dist.
All properly blazed and scribed. SEE RENEWAL #62

✓ 1/4 SEC. COR. 1,12 30
Position identified from a ~~map~~ ~~tree~~ ~~to~~ ~~be~~ ~~an~~ ~~O.B.T.~~ ~~This~~ ~~tree~~ ~~has~~ ~~been~~ ~~badly~~ ~~damaged~~ ~~and~~ ~~carries~~ ~~an~~ ~~axe~~ ~~blaze~~ ~~of~~ ~~proper~~ ~~size~~ ~~position~~ ~~and~~ ~~shape~~ ~~to~~ ~~have~~ ~~been~~ ~~the~~ ~~orig.~~ ~~B.T.~~ ~~bearing~~ ~~and~~ ~~distance~~ ~~places~~ ~~corner~~ ~~on~~ ~~an~~ ~~E. & W. blazed~~ ~~line.~~ ~~Set~~ ~~as~~ ~~new~~ ~~4" x 6" x 20" for corner and blaze and scribe~~ ~~A 14" Hemlock, N.32°E. 88 lks. dist. 1/4 S. 1 C.S. B.T.~~ ~~A 12" Fir, S.5°W. 18 lks. dist. 1/4 S. 12, C.S. B.T. in~~ ~~bank 42" FIR - SEE MAP FILE 6-7 M.C. COR. NOT PD. IN 1962~~
SEE CORNER NO. #156

✓ N.E. COR. SAMUEL TURNER (Dec 50) (F.B. 22 Page 5) 31
W. Oak 10" in dia., bears S.50°E., 17 lks. dist.
W. Oak 8" in dia., bears N.1°E., 15 lks. dist.

POINT ON WEST LINE OF 32
D.L.C. No. 51 (F.B. 43 P. 14) Bl. 3, Pg. 1
Set 1" x 20" Pipe
Fir 24" in dia., bears S.27°E., 2 lks. dist. #
Oak 18" in dia., bears S.68°E., 29 1/2 lks. dist. 140

✓ COR. TO SEC. 20-21-28-29 33
Found one old B.T. a White Oak, 30" in dia. bears S.43 1/2°E., 424.4 ft. dist. Marks plain all other trees gone. Set a Cedar stake in Sawyer's Garden from which
36" Red Fir, bears N.43°W. 150 ft. dist.
12" White Fir, bears S.48 1/2°E. 351.5 ft. dist.
See M120-49 A & B

✓ N.W. COR. D.L.C. 50 34
Reset from 8" Ash B.T. (Myrtle B.T. cut out) by setting
6" x 12" x 20" Conc. block from which
A 12" Myrtle stump, about 4" high, bears S.10 1/2°E. 32.3 ft. in dist. 76

Interior angle corner on the south boundary of the Andrew Sawyer D. L. C. No. 49. This corner is at the intersection of the south boundary and the meander line on the right bank of the Umpqua River. 35

Location identified from both of the original bearing trees which have scribe marks visible but in very poor condition. Drove an iron pipe 1" x 48" - 42" in the ground for the corner and set a cedar post alongside. An oak 16 ins. diam. bears N. 49°E. 33.5 ft. and a maple 12 ins. diam. bears S. 72°W. 52.0 ft. both blazed and scribed CL. 49 CS. BT.

MEANDER CORNER BETWEEN 4 and 9 36
Found old stake properly scribed. An old fir stump in very poor shape sets N.29°30'W. 29.8 ft., but the scribing was still plain when I cut into the stump. Ren. #2
New bearing trees were marked as follows:
An 8" Oak bears N. 7°30'E., 26.6 ft. scribed M.C. S.4B.T.
A 10" Oak bears S.51°30'E. 28.6 ft. scribed M.S. S.9, B.T.

THIS RENEWAL IS OF BYARS 1881 M.C.
(NOTED BY M. GODFREY, 12/62) L.O.
SEE C.S. FILE 52/14
FOR 1855 M.C. 24
RIGHT BANK

SEE VOL. 4 PG 4
C.S. File 14/38 M6-7
Dec. 1929
M. B. Germond
F. C. Freer
Sept. 1917
Witnesses
Ren. R. Irvine
W. E. Richardson
Oliver Haines
Dep. Co. Surv.
M. E. Richardson
Tune, 3, 1935
F. C. Freer
P. D. Wolford
J. H. Wolford
J. N. E. Richardson
July 27, 1936
A. Boyer
T. Billick
F. A. Thomas
Witnesses.
May 26, 1941
Ben R. Irvine
W. E. Richardson
Loren Weber
C. F. Bessie
Reg. Prof. Engineer
No. 1286
Oct. 25, 1944
C.S. 40/7