

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

James W. Byron
M. Godfrey
S. Bilow
April 16, 1958
C.S. File No. 49/77

49

$\frac{1}{4}$ Section Corner to Sections 5 & 4.
Found - Orig. 24" now 38" Fir S.1°W. 26.1 ft. Old bark scribing " $\frac{1}{4}$ S".
Orig. N. E. BT. not found.
Set Brass Cap at Corner Marked: $\frac{1}{4}$ S5/S4 T22S R8W County Surveyor's
Office, 1958. 75
New BT's: 26" R. Fir bears S.83°W. 10.0 ft. scribed $\frac{1}{4}$ S5 CS BT.
26" R. Fir bears S. 5°E. 68.1 ft. scribed $\frac{1}{4}$ S4 CS BT.

AR. Evans
for Bernau &
Sawyer
Jan. 1951
S. 44/78
le M 10 - 62

Southwest ~~SW~~

50

Northwest Corner of D.L.C. No. 49.
Determined from Original B.T.:
D. Fir N.33°W. 50 lks., rescribe this tree which is 24" diam.
Set $\frac{3}{4}$ " Iron Rod for Corner. 63
Blaze & Scribe New BT.: 12" Chinquapin S.58°W. 22.0 ft. Mkd. N.W.Cl.49 CS BT.

M. B. Germond
For Sam Brown
1916
Vol. 2, Page 162
F. B. No. 22, Pages 5-7

51

Northeast Corner of Claim 50. (Duplicate of #31)
Set 4" W.Oak Stake. Found old B.T.
W. Oak 10 S.50 $\frac{1}{2}$ °E. 17 lks.
W. Oak 8 N. 1°E. 15 lks. 79

52

Northwest Corner.
Set Cedar Post 4". Found old BT. (Dup. of #34)
An Ash 9" N.74°45'W. 43 $\frac{1}{2}$ lks.
A Myrtle 5" N.23°10'W. 37 lks. 76

53

Northeast I. Corner.
Cedar Stake 4" x 5".
Red Fir 14" S.80 $\frac{1}{2}$ °W. 49 lks.
Red Fir 16" N.67°W. 40 lks. 69

54

$\frac{1}{4}$ Corner between 15 & 14.
Reset with Cedar Stake 5" sq. and note old B.T. Standard. 72

55

Northwest Corner of Section 14.
Rock 6x8x12 and note old B.T. standing. S.88°40'E. from N.W. Corner at
42.05 lks. I fell 12 lks. N. of Corner. Set in: 68
R. Fir 20 N.66°30'E. 19 $\frac{1}{2}$ lks. ← THESE BT'S WERE SET AT
W. Fir 16 S. 9°30'W. 77 lks. ← N $\frac{1}{4}$ COR. SEC. 14 - NOT AT SEC. COR.
A.E.G.

56

Ben E. Irving
For Oliver Haines
Nov. 24, 1929
Recorded in Vol. 4,
Page 4.

Section Corner to Sections 1, 2, 11 and 12.
Survey began at N. W. Corner to Section 12.
Renew this corner by setting a Sandstone 7" x 12" x 28" long, (See also
securely in the ground and supported by a mound of rocks in Ren #28A)
the location as determined from all Original BT's:
Reblaze & Scribe all BT's:
24" Fir N.30°E. 25 lks.
48" Fir S.26°E. 89 lks.
48" Fir S. 5°W. 71 lks.
30" Fir N.55°W. 21 lks.

FD. OK. 4/16 - Woolley Logging - C.S. 57/21

57

James W. Byron, Deputy
Milo Godfrey
Clete Putnam
June 6, 1961
C. S. File No. 52/14

$\frac{1}{4}$ Section Corner to Sec. 25, 22-8W. & Sec. 30, 22-7W.
Found - Orig. 6", now 30" W.O. N.31 $\frac{1}{2}$ °W. 33.7 ft., center rotted, no
scribing fd. Orig. 15", now 30" W.Oak N.58°W. 66.0 ft.,
center rotted, no scribing fd. Both BT's. were opened years
ago possibly by Cole & each checks record bearing & distance.
Fence To North & To West from Corner.
Set Brass Cap at Corner Mkd: County Surveyor's $\frac{1}{4}$ S25/S30 T22S
Office, 1961 R8W R7W
New BT's: 11" W.Oak bears S.80°W. 16.0 ft. scribed $\frac{1}{4}$ S25 CS BT.
16" W.Oak bears S.24 $\frac{1}{2}$ °E. 36.3 ft. scribed $\frac{1}{4}$ S30 CS BT.
See Statement by Henry Beckley in file in regard to Orig. BT's.