

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 8 R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 97196

58

Witness Corner to Sections 28 and 27.
This Wit. Cor. was set on Original Survey in 1885 and lies on top of
a ridge about 683 ft. South of a Corner to Section 27 & 28,
according to Byar's Survey of 1881.
Found - Rotted Stump S. 73° E. 51.9 ft. with very plain scribing "BT".
Fir Tree, now 48", S. 54° W. 17.2 ft., showing bark scribing,
"S28 28" this tree still in good condition.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1961
T22S R8W W. C. S28/S27.
New BT: 8" D. Fir N. 34° E. 12.3 ft. Mkd: W.C. S27 CS BT.

RE-RENEWED, SEE CORNER NO #169

James W. Byron - Deputy
Milo E. Godfrey - Corners set by Godfrey
Cleto Putnam
June 8, 1961
C. S. File No. 52/80

59

Section Corner to Sections 27 and 28.
Found - 18" Fir, now 27", West 20.5 ft., uprooted & down. This
tree had been opened before it fell, face down,
traces of scribing visible.
16" Fir, now 24" dead snag, N. 85° E. 35.0 ft., shows good
scar. Did not chop open.
Set Brass Cap Mkd: County Surveyor's Office, 1961 T22S R8W 1/4 S28/S27.
New BT's: 18" Fir N. 42° W. 32.2 ft. Mkd: 1/4 S28 CS BT.
15" Fir N. 20° E. 44.5 ft. Mkd: 1/4 S27 CS BT.
Note - This Corner lies on a steep West Slope about 100 ft.
West of a ridge top.

60

Sec. Cor. to Secs. 1 - 12, T22-8W. & Sec. 7 - 6, T22-7W.
Found - Rock Set by B.B. Irving, 1929. Rock had fallen over but aptly.
had not slid away from corner. Reset Rock & Piled mound around.
32" Fir N. 15° W. 15.8 ft. Good bark scribing visible. Blaze &
scribed "BT" in wood. *SEE COR # 27*
48" Fir S. 42° E. 27.7 ft. good bark scribing visible. Blaze &
scribe "BT" in wood. Top of tree now dead.
60" Dead Fir S. 42° W. 23.1 ft. good bark scribing visible. Blaze
& Scribe "BT" in wood. No live trees avail. to S.W.
No trace found of N.E. BT.
Blaze & Scribe 16" Hemlock N. 39° E. 48.7 ft. Mkd: T22S R7W S 6 CS BT.
Corner lies on very steep N.E. Slope approx. 300 ft. North of top of ridge.

*FOOK 7/5/85
L. ROBERTS
M 90-74
C.S. 63/18*

Milo E. Godfrey, Deputy County Surveyor
Vernon Tracy & Cleto Putnam
March 1962
C. S. File No. 52/14

61

1/4 Corner Sec. 12, R8W. & Sec. 7, R7W. *Cor # 28*
Found - Plowshare Set by B.B. Irving, 1929, nearly buried in ground.
Alongside Plowshare Set Brass Cap Mkd: County Surveyor's Office,
1962, T22S 1/4 R8W S12/S7 R7W
Corner lies on open grassy slope. No trees within 500 ft.
Note - Mr. Haines' House bears S. 10° W. approx. 550 ft. from corner.

*FOOK 7/5/85
L. ROBERTS
M 90-74
C.S. 63/18*

62

Section Corner to Secs. 12 - 13, R8W. & Sec. 7 - 18, R7W.
Found - Haines' "T" Iron & 19" W. Oak S. 64° W. 205.5 ft., shows good scar.
26" W. Oak S. 78° W. 176.1 ft., shows good scar. *SEE COR # 29*
17" W. Oak N. 70° W. (not N. 79° W.) 189.9 ft. has been opened
previously, scribing visible "S" & "2".
Blaze & Scribe 9" W. Fir N. 59° W. 205.5 ft. Mkd: T22SR7W S12 CS BT.
DID NOT SET BRASS CAP.

63

N. W. Corner to D. L. C. No. 58.
Found - 3/4" I. Pipe at Corner & BT's. as recorded by A. Evans.
Chinquipin now dead. *Ren #50*
New BT's: 12" R. Fir bears S. 33° E. 59.4 ft. scribed N.W. Cl. 58 CS BT.
Rescribe, now 28" R. Fir N. 33° W. 33.0 ft. Mkd: S.W. DLC 49 CS BT.

James W. Byron
& Crew
For Oregon State
Game Comm.
5/4/62
C.S. File 52/119