

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 22 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Milo E. Godfrey, Deputy County Surveyor  
Vernon Tracy and Mike Stone  
December 20, 1962  
C. S. File No. 52/14

Section Corner to Sections 8 - 9 - 16 - 17.

74

Found - 1 1/2" x 40" Iron Pipe set by Frear, 1917, pulled out of ground by uprooted tree. - REN.#20

16" Dogwood N.55°W. 15.8 ft., cut open & find good scribing, top of tree broken off, but remaining part still alive.

28" W. Fir Snag S.56°W. 14.5 ft, cut open & find Frear's scribing.

26" W. Fir Stump S.10°E. 25.7 ft., stump hollow, on piece of wood inside stump, still attached, find portion of old face with original scribing visible "16 22S R8W".

72" D. Fir N.60°E. 3.3 ft., recently uprooted, part of Frear's scribing "S9" visible in bark.

38" D. Fir N.31 1/4°W. 31.7 ft., recently uprooted, face buried in mud.

Set - Brass Cap at Cor. Mkd: County Surveyor's T22S R8W S 8 | S 9  
Reset I.P. alongside. Office, 1962 S17 | S16

New BT's: 9" Hemlock N.30°W. 72.3 ft. Mkd: T22S R8W S8 CS BT.

6" W. Fir N.47 1/2°E. 53.6 ft. Mkd: T22S R8W S9 CS BT.

12" W. Fir S.57°E. 69.4 ft. Mkd: T22S R8W S16 CS BT.

9" W. Fir S.84°W. 80.8 ft. Mkd: T22S R8W S17 CS BT.

1/4 Corner to Sections 5 and 4.

75

Found - Brass Cap set by Co. Surveyor's Office, 1958. REN.#49

Fir, S.83°W. 10.0 ft., alive & in good condition, scribing visible.

Fir Stump S. 5° E. 68.1 ft. "BT" still on stump, rest of scribing gone with log.

New BT: 16" D. Fir N.25°E. 29.9 ft. Mkd: "1/4 S 4 CS BT".

N. W. Corner D. L. C. No. 50.

76

Found - Concrete Block set in prior renewal. REN.#52 Set Rock 8" x 12" x 21" alongside & drove in gun barrel found lying nearby. #139

19" Ash Tree N.34°E. 12.4 ft., previously opened, scribing visible.

9" Ash N.75°W. 28.7 standing in river.

Myrtle Clump N. 23° W. 24.4 ft. and S.10 1/2°E. 32.3 ft.

New BT's: 8" Myrtle N. 17° W. 23.7 ft. Mkd: NW. DLC 50 CS BT.

15" Myrtle S. 6°E. 31.1 ft. Mkd: NW DLC 50 CS BT.

Meander Corner Sections 4 & 9, right bank of river.

77

Found - W. Oak, now 24", N.48°E. 22.4 ft., cut open, fd. axe mks. at least 60 years old where tree was opened previously. Also found small portion of straight scribe mks. on pice of old face. The center of a clump of young Ash trees growing in a circle bears S. 4° W. 16.5 ft.

This location also fits tie from N. W. corner D.L.C. No. 50.

Corner location too close to river. Set Wit. Cor. 20 ft. East of M.C.

Set - Brass Cap Mkd: County Surveyor's T22S R8W WC 1855 WC S 4  
Office, 1962 20 ft. W. to M. C. S 9

New BT's: 18" D. Fir North 11.0 ft. Mkd: W.C. M.C. S 4 CS BT.

10" Ash S.47°W. 26.8 ft. Mkd: W.C. MC S 9 CS BT.

Note - This is a renewal of Gordon & Gardiner's Meander Corner, 1855 survey. Byar's section line (1881 survey) is approximately 200 ft. South.

Witness Corner to Sections 4 and 9, 15 chains E. of M. C.

78

Found - Old W. Oak, now 28", S.26°W. 42.2 ft. (slope dist.) showed scars on bark, opened tree & fd. it hollow. Very old axe marks found.

Also portions of both upper & lower faces, no scribing found.

Rotten remains of big oak stump N.49°W. 42.2 ft. Too far gone to find scars or scribing.

This location is due East & approx. 15 chains Dist. from Meander Cor., above.

Set - Brass Cap at Cor. Mkd: County Surveyor's T22S R8W W.C. S 4  
Office, 1962 S 9

New BT's: 10" D. Fir S.13°W. 12.8 ft. Mkd: WC S9 CS BT.

11" D. Fir N.13°E. 14.3 ft. Mkd: W.C. S4 CS BT.

Note - This Witness Corner was set by Gordon & Gardiner, 1855 survey.