

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 22 S. T. S. R. 8 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

79

Most Northerly N. E. Corner D. L. C. No. 50.  
 Found - 14" W.Oak N.1°E. 9.9 ft., showed good axe scar, chopped  
 open & found portion of scribe mark on partly rotted face. *Ren. #51*  
 16" W.Oak S.50½°E. 11.2 ft., shows faint scar. Didn't open.  
 Old W.Oak S.3°E. 175 lks. Small piece of dead & rotting wood  
 against old face with reverse scribing visible, portion  
 of "BT" (Orig. BT.)  
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962  
 T22S R8W N NE D.L.C. 50.  
 Blaze & Rescribe: 16" W.Oak S.51°E. 11.2 ft. Mkd: N NE DLC 50 BT.CS.  
 15" D.Fir N.85½°E. 10.5 ft. Mkd: N NE DLC 50 CS BT.  
 Corner lies on very Steep S. W. slope.

80

S. W. Corner D. L. C. No. 47. - Wit. Corner 15 ft. East.  
 Found - 16" W.Oak N.82°E. 59.4 ft., cut open & fd. portion of scribe.  
 16" W.Oak N.71½°E. 53.5 ft., Cut open & fd. good scribing "S".  
 (These 2 trees mkd. by Frear, 1917) *Ren. #21*  
 Did not find Pipe set by Frear, nor Original BT.  
 Corner position falls in Creek.  
 Set - Wit. Cor. 15 ft. East of DLC Cor. Set Brass Cap Mkd:  
 County Surveyor's Office, 1962 T22S R8W W.C. SW. DLC 47 L  
 New BT's: 14" D.Fir S.82°W. 6.7 ft. Mkd: WC SW DLC 47 CS BT.  
 11" D.Fir S.71°E. 61.5 ft. Mkd: WC SW DLC 47 CS BT.

81

Wit. Corner to S.W. Cor. D.L.C. No. 44.  
 Found - Co. Surveyor's Brass Cap set in 1955. *Ren. #48*  
 The 14" D.Fir N.28°W. 27.0 ft. still alive & in good cond.  
 The SW. BT. Mkd. in 1955 is now dead, down & rotting.  
 New BT: 16" Fir S.49°W. 25.9 ft. Mkd: WC SW DLC 44 CS BT.

82

Section Corner to Secs. 31 and 32, only.  
 Found - 1½" I. Pipe, 15" above ground, with cap stamped S 31/S 32  
 S 6  
 60" Fir N.70°W. 13.9 ft. (to face) with fairly plain bark  
 scribing "S31 T22S R8W".  
 Rotten Remains of Fir Stump N. 8° E. 23 ft., too far gone to  
 find markings.  
 New BT: 5" D.Fir N.38°E. 31.5 ft. Mkd: "S32 CS BT.

83

Closing Cor. for Secs. 25 and 36, on W. Line of T22-8W.  
 Found - 52" Fir S.68°E. 44.9 ft., chopped open & fd. gd.rev.scrbng.  
 28" Fir S.25°W. 40.9 ft, shows good axe scar.  
 (Rescribe "T22S R9W S36 CS BT")  
 48" Fir N.67°W. 43.6 ft., shows good axe scar, injury on N.W.  
 face shows tree rotting in center.  
 ( all distances on B.T.'s (old) are slope-dist. from center of trunk)  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T22S R9W CC S25 R8W  
 Office, 1963 S36  
 New BT's: 11" D.Fir N.66°E. 22.3 ft. Mkd: CC S25 S36 CS BT.  
 8" D.Fir N.38°W. 16.7 ft. Mkd: T22S R9W S25 CS BT.  
 Corner lies nearly at foot of steep south slope, in upper edge  
 of cut bank on old logging road.

84

Closing Corner for Sections 6 and 5, T23-8W., S. Line of T22-8W.  
 Found - 58" Fir N.36°W. (not N.44°W.) 39.6 ft. Cut open scar &  
 found good scribing, tree alive & in good condition.  
 34" Fir S.20°W. 27.1 ft, shows very good axe scar.  
 Badly rotted W.Fir Stump N.40°E. 34.3 ft. Portion of flat  
 face & axe marks, but no scribing.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's CC T22S  
 Office, 1963 T23S S 6/S 5 R8W  
 New BT: 10" D.Fir S.74°E. 27.0 ft. Mkd: T23S R8W CC S5 CS BT.  
 Found - 1½" I.P. 15" above ground with cap stamped, probably set by  
 Long Bell Lumber, N. 86° E. 3.2 ft. from Cor. as Set above.

Milo E. Godfrey, Deputy County Surveyor  
 Vernon Tracy and Mike Stone  
 December & January 1963  
 C. S. File No. 52/14

S25 R8W 49/103