# Douglas County Surveyor's Record of Government Corners Renewed

T. 22 S. T. S. R. 8 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Milo E. Godfrey
V. Tracy &
Mike Stone
Feb. 25, 1963
C.S. File
No. 52/14

85

Section Corner to Sections 17 - 18 - 19 -20.
Found - G.L.O. Brass Cap set in 1931 alongside rotten Fir Stump.
34" W. Fir S.16¼°W. 37.0 ft, shows good scar.
Old Fir Snag N.70°W. 39.0 ft., shows very plain axe scar.
Badly rotted W. Fir Stump N.11½°E. 37.6 ft., no marks visible.
D. Fir Stump S.52½°E. 50.2 ft., shows good axe scar.
New BT's: 8" W.Fir N.48°W. 21.2 ft. Mkd: T22S R8W S18 CS BT.
15" D.Fir N.50°E. 46.0 ft. Mkd: T22S R8W S17 CSBT.
7" D.Fir S.70°E. 45.9 ft. Mkd: T22S R8W S20 CS BT.

86

R9W - - - R8W - - - - -
Corner to Sections S 36/ S 31 T22S
S 6 T23S
Found - 1½" Iron Pipe (Galv.) & wooden stake.
54" Fir N.65°W. 77.9 ft., old uproot, dead. Found bark scribing.
72" Fir N.70°E. 90.4 ft., old, dead, uproot, bark charred & covered with mud, no scribing found.
DID NOT SET BRASS CAP. - Iron Pipe in good condition.
New BT's: 9" D.Fir N.68°E. 45.8 ft. Mkd: T22S R8W S31 CS BT.
20" D.Fir N.66°W. 25.0 ft. Mkd: T22S R9W S36 CS BT.
D.Fir S.89°W. 30.4 ft. Mkd: T23S R8W S6 CS BT.
Corner lies on Steep North East Slpe.

- - - - - - - - - - Fd. O.K. FEB. 1967 V.R.T.

87

¼ Corner to Sections 19 and 20.
Found - G. L. O. Brass Cap set in 1960.
White Fir Snag N.45°E. 13.2 ft., scribing visible "S". Orig. BT.
13" W.Fir S.16°E. 63.4 ft., scribing visible in not completely healed blaze. Tree alive & in good condition.
Fir Snag, recently broken off, N.46½°W. 15.8 ft., scribe visible in not completely healed blaze.
New BT: 18" W.Fir S.59°W. 24.9 ft. Mkd: ¼ S19 CS BT.
Corner lies approximately 200 ft. South of ridge top.

- - - - - - - - - - - - - - - -

88

Meander Corner, left Bank, S.7 and Sec. 18.
Found - Brass Cap set in 1931, buried 28" below surface of ground.
30" Cottonwood Tree N.17¼°E. 52.8 ft. No scars visible. Tree alive and in good condition.
25" Maple S.63½°W. 99.7 ft. Scars dimly visible. Tree alive and in good condition.
Set - ¾" Rod on top of Brass Cap, extends approx. 4" above ground.
Reblaze & Scribe 25" Maple S.63½°W. 99.7 ft. Mkd: "MC S18 CS BT".
New BT: Blaze & Scribe 9" Maple N.60°W. 8.8 ft. Mkd:"M.C. S7 CS BT."

- - - - - - - - - - - - - - - -

89

¼ Section Corner to Sections 7 and 18.
Found - Brass Cap at Corner, Top buried 24" below ground.
24" W. Oak S.52¼°E. 909.6 ft., shows very plain axe scar. Tree alive and in good condition. FD. OK 3/80 L. Roberts MB3-74
12" W.Oak, not maple, N.4°W. 238.9 ft. Tree dead, face rotted. Found fragment of reverse scribing on edge of overgrowth.
Set - ¾" Rod on top of Brass Cap, Rod extends approx. 6" above ground surface
A Power Pole(Copco A2563 6-387 3) bears N.12°E. 9.3 ft. from ¼ Corner.
New BT: 21" W.Oak N.35°W. 216.7 ft. Mkd: ¼ S 7 CS BT. Tree stands at edge of high bank along river.
Now stump

- - - - - - - - - - - - - - - -

90

SW 1/16 Section 18.
Found - Gov't. Brass Cap set in 1931.
28" W. Fir S.42°W. 44.2 ft., shows good axe scar.
Rotted remnants of White Fir Stump N.76°W. 10.6 ft., too far gone to find any markings.
Reblaze & Scribe 28" W.Fir S.42°W. 44.2 ft. Mkd: "SW 1/16 S18 CS BT".
New BT: 31" D.Fir N.11°E. 25.5 ft. Mkd: "SW 1/16 S18 CS BT".

- - - - - - - - - - - - - - - - - - -

Milo E. Godfrey, Deputy County Surveyor
Vernon Tracy and Mike Stone
March 1963
C. S. File No. 52/14