

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 22 T. S. R 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

139

CONT.

R. B. Kimberling
F. C. Silagy
Doug. Co. Surveyors
Office
Jan. 16, 1978
C.S. 59/46

Set - Gun barrel at corner, 2.5 ft. below ground, with a 3" x 22" x 10" concrete alongside.
Set - A witness corner 50.0 ft due east, a 1" x 36" I.P. with a brass cap set 6" above ground marked: "Douglas County Surveyor"
T 22 S R 8 W
50 ft due west
to
NW Cor
DLC 50
Witness Cor.
1978

Witness corner Accessories:
New bearing and distances to DLC corner;
A 19" Ash bears N.76°W., 43.2 ft.
A 15" Myrtle bears S.57°W., 52.9 ft.
New BT - A 10" Maple bears S.8°E., 11.4 ft. double blazed and marked "WC NW DLC 50 CS BT"
Corner is on bank of Umpqua River across from Mather mailbox 357, Hwy. 38.
1/16/78

Romanso E. Ware
LS #1005
For: George Fenn
Dec. 1977
M 68 - 73

Witness point on West line DLC #51. **140**
Found - 18" now 32" Oak bears S.69°W., 29.5 lks. opened & fd. scribing "BT 51". Ren. #32
Set - Brass cap stamped "T22S R8W W.P. West Line D.L.C. 51 RPLS 1005 1977"
BT's - 12" Ash bears S.83°E., 10.3 ft.
24" Maple bears N.22°W., 20.5 ft.
Both trees scribed "W.P. D.L.C. 51 BT" and have aluminum washer attached & stamped L.S. 1005.
Dec. 1977

¹⁻⁷⁹
Wilford N. Haines
L.S. #239
For: John W. Duncan
Sept. 1979 M 80-20

Interior Corner, DLC #37 **141**
Found - Rock with X.
Set - 5/8" rebar alongside.
9/27/79

Les Roberts
For:
International
Paper Company
June 1980
M 84 - 39

Northeast corner of DLC #38 (in Sec. 13) **142**
Found - Downed 30" Oak, N.12°W., 70.0 ft. face visible.
Downed 24" Oak, N.4°E., 153.1 ft. badly burned.
Set - 1 1/2" Iron pipe with International Paper Co. brass cap.
BT's - 18" Fir, N.73°E., 16.6 ft.
16" Fir, N.56°W., 10.9 ft.

Northwest corner DLC #39 (in Sec. 13) **143**
Found - N-S-E Fence
38" Oak, S.25°E., 99.0 ft. face visible, hollow tree.
26" Downed Oak, S.65°E., 133.3 ft. face visible.
Set - 1 1/2" Iron pipe with International Co. brass cap.
BT - 12" Fir, N.79°E., 82.4 ft.

1/4 Corner between Secs. 13; and Sec. 18 of T.22-7 **144**
Set - 1 1/2" iron pipe with International paper Co. brass cap.
BT's - 13" Fir, N.8°E., 8.4 ft.
7" Fir, N.88°W., 16.2 ft.

SW corner Lot 1, Sec. 18 and SE cor. Lot 1, Sec. 13. **145**
Set - 1 1/2" Iron pipe with I.P. brass cap.
BT's - 12" Alder, N.25°E., 29.2 ft.
17" Alder, N.60°W., 16.0 ft.
6/80

Stephen Flause
Deputy - Doug. Co.
Surveyors Office
Karen Mosely
Bill Stewart
Sept. 9, 1980
C.S. 61/11

Center 1/4 Corner for Section 29. **146**
Found - 1965 BLM brass cap properly marked, on a 2 1/2"x28" I.P..
Monument is pulled out of soil and lying on surface because of recent land clearing. No evidence of the monuments original position remains. (Record of date stamped on cap is 1964)
An original 6" Fir, now 17" by 8" tall fir stump which is opened to find part of the remaining scribing which reads "S2".