

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 8 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

146

cont. from previous page -

Stephen Flause
Deputy - Doug. Co.
Surveyors Office
Karen Mosely
Bill Stewart
Sept. 9, 1980
C.S. 61/11

From the preceeding stump, we measure N.6 1/2°W., 199.3 ft. (302 lks.) to approx the orig. location of the monument. From this position we find an orig. 19" now a 29" DBH White Fir bearing S.86°W., 218.2 ft. This tree is partially opened to find the scribing "C 1/4".

The most acceptable corner position is found to be at intersection of the orig. distance.

From this position: the 17" diam. by 8" tall fir stump now bears S.05 1/2°E. 199.3 ft. and the 29" White fir bears N.86 1/2°W., 221.8 ft.

Set - Upon measuring to the point of orig. intersection distances and finding reasonable bearings to the orig. BTs, this position is referenced out and the monument is replaced in the ground at this determined orig. location. The monument now protrudes 2" from the ground and is firmly set. WE ADD RESET C.S. 1980" to stamping on brass cap.

New BT's- A 25" DBH White Fir, bears N.84°E., 118.7 ft. Tree is scribed "C 1/4 S29 CS BT" on a double blaze and is located in a random East-West fenceline.

An 8" D. Fir bears N.64°W., 215.3 ft. Tree scribed "C 1/4 S29 CS BT" on a double blaze.

All trees are retagged or tagged with DCSO BT tags.
Monument is 53 feet south of a random east-west fenceline.

9/9/80

147

Les Roberts, Triangle
Engineering
For: Norman Rydell
Dec. 1980
M 86 - 29

S. W. Corner DLC #39

Found - 6" x 8" x 12" stone of unknown origin with "X" on top. Stone found 20 ft. west of 4 ft. creek. Bearing and distance to N.W. corner of DLC 39 fits original notes.

Set - 14" White Fir, N.23°E., 76.4 ft.
24" Ash, bears East 18.0 ft.

12/80

148

W. Carey Weatherly
For:
W. Carey Weatherly
May 8, 1982
C.S. 58/247 (three pgs)

Meander Cor. on the North (right) bank of Umpqua River, common to Sec. 18 of T. 22-8, and Sec. 13 of T. 22-9.

Found - 1963 Douglas Co. Surveyor's B.C., buried 2-ft., Ren. #109. from which:

BT's - 18" rotten alder snag bears South, 17.8-ft.
12" rotten alder snag bears S.2-1/2°E., 14.4-ft. per Ren#109.
24" oak, face evident, but rotted, bears S.31°W., 61.0-ft. (Rec. S.37°W., 85.5-ft.).

BO - SW cor. of concrete wall bears N.13°W., 150.5-ft. Ren.#109.

Set - 7/8" x 48" galv. I.P., with plastic cap mkd. LS 1667, over the B.C., from which:

New BTs- 8" alder bark scribed: T22S R8W MC BT bears N.79°E., 33.8-ft.
10" alder bark scribed: T22S R9W MC BT bears S.3°W., 15.6-ft.

5/8/82

149

Rockne R. Luckman
LS #1254
For: International
Paper Co.
June 10, 1982
M 92 - 54

1/4 Corner for Secs. 29, & 32.

Found - Brass Cap. Gov't. Resurvey.

BT's - 27" D. Fir (record 16") bears S.60°W., 148.75-ft. (Cat-face & tag).
12" chinquapin (record 5") bears N.64°W., 58-ft. (no blaze or tag, but ribbon is sticking out of bark).

New BT:- 9" D. Fir bears N.56°W., 15.0-ft. (not of record). 6/10/82

150

Center 1/4 Corner of Sec. 32.

Found - Brass Cap. Gov't. Resurvey.

BT's - 19" hemlock (now a stump w/tags) bears S.38°E., 66.0-ft.
17" fir (now snag w/blaze) bears N.24-1/2°W., 66.0-ft.

New Bt - 3-ft. fir bears N.22°W., 9.8-ft. (not of record).

6/10/82

151

Les Roberts L.S.
#1039
For: International
Paper Co.
M 90 - 29
Oct. - Dec. 1982

North 1/4 Corner for Section 2 only, of T.23-8

No evidence found of original corner.

Set - 5/8" x 30" iron rod at proportionate distance. Rod has yellow plastic cap marked "Roberts" L.S. 1039. Rod buried 1.0 ft.

New BTs - 15" oak, S.57°E., 282.2 ft. (scribed)
18" oak, S.77°E., 270.8 ft. (scribed).

Note - Incorrect corner bears S.89°46'12"E., 0.89 ft. I removed incorrect set pin on 12/30/82.