

**Douglas County Surveyor's Record of  
Government Corners Renewed**

22      T. S.      8      R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Donald L. Branch    LS #1137  
For: International Paper Company  
January/February 1986

M 100 - 31

*FND BLM BC 9/92  
R. DeLAN M115-68*

Les Roberts    P.L.S. #1039  
For: International Paper Co.  
June, 1986

M 102 - 18

Center 1/4 Section Corner for Section 26  
SET - 1 1/2" x 30" iron pipe with cap mkd. LS 1137.  
BT's - 12" D. Fir., bears N.48°W., 15.06 ft. dist.,  
scribed C1/4 S26 BT.  
10" D. Fir, bears S.49°32'W., 23.13 ft. dist.,  
scribed C 1/4 S26 BT.

159

1/4 Section Corner for Secs. 25 and 26  
Found - A 1964 BLM Brass cap on a 2" iron pipe.  
BT's - 24" Fir stump, bears N.79°54'E., 27.83 ft. dist.  
18" Chinquapin, bears N.78°33'W., 46.35 ft. dist.  
NEW BT - 13" Chinquapin, bears S.33°44'E., 58.16 ft. dist.,  
scribed 1/4 S25 BT.

160

1/4 Section Corner for Sections 26 and 35  
SET - A 2 1/2" x 30" Aluminum pipe with cap mkd. LS 1137.  
BT's - 8" Oak, bears S.21°45'E., 73.61 ft. dist., scribed 1/4 S35 BT.  
8" Oak, bears N.14°20'E., 129.63 ft. dist., scribed 1/4 S26 BT.

161

Section Corner for Sections 26, 27, 34, and 35  
Found - A 1962 BLM Brass Cap on a 2" iron pipe.  
BT's - No standing bt's found.  
NEW BT's - 6" D. fir, bears N.40°53'W., 14.45 ft. dist., scribed  
T22S R8W S27 BT.  
4" D. Fir, bears N.67°30'E., 22.83 ft. dist., scribed  
X BT.  
5" D. fir, bears S.71°20'E., 34.35 ft. dist., scribed X BT.  
4" D. fir, bears S.64°24'W., 26.69 ft. dist., scribed X BT.

162

East 1/4 Corner Section 3  
SET: - 1 1/4" Iron Pipe and Brass Cap. Stamped " T22S R8W 1/4 3|2  
1986 P.L.S. 1039". Purple Magnetic marker buried under 36"  
pipe.  
BT's - 10" Fir, bears S 13° W, 19.7 ft. Scribed/Painted Red.  
30" Fir, bears N 6° W, 22.2 ft. Scribed/Painted Red.  
Note: Set metal fence post, with land survey monument sign wired to,  
beside brass cap. Corner lies on steep East slope about 150'  
West of Paradise Creek Road.

163

West 1/4 Corner Section 3.  
SET - 1 1/4" x 36" Iron Pipe and Brass Cap Stamped " T22S R8W 1/4  
S4|S3 1986 P.L.S. 1039" Buried Purple Magnetic marker under  
Iron Pipe. Old 1" Iron Pipe bears S 6°20'15"W, 77.81'.  
Found - 48" Fir Stump bears N68°E, 109.5' (Scribe Vis.), 1881 BT.  
68" Fir bears N62°W, 141.2' (Record N62°W, 120.1') scar  
Visible, 1881 BT.  
New BT's - 9" Fir bears S76°W, 10.9' ( Scribed/Painted Red)  
12" Fir bears S47°E, 23.2' (Scribed/Painted Red)  
Note - Set metal fence post, with survey monument sign wired to,  
beside brass cap. Corner lies on West slope about 50' West  
of 10 year old logged unit. Corner set by using record data  
from original N.E. BT. fits for bearing but not for distance  
as noted.

164

South 1/4 Corner Section 34 only. T21-8  
Found - A 1952 G.L.O. Brass Cap set firmly in ground, marked W.C.  
30" Corner Tree bears West. 1.98'.  
24" Fir stump bears N54°E, 25.2' (Scribe Vis.) 1952 B.T.  
Record N54½°E, 25.7'.  
New B.T. 8" Fir bears N17°W, 12.6' (Scribed/Painted Red)  
Note - Set metal fence post, with survey attention sign wired to,  
beside brass cap. Corner lies on South slope about 50' South  
of old dirt logging road.

165

Ren#104