

Douglas County Surveyor's Record of
Government Corners Renewed

22

T. S.

8

R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. - 21881

166

North East Corner Section 3 (Closing Corner).
Found - 1952 G.L.O. Brass cap set firmly in ground.
15" Fir up-root S78W, 54.0, 1952 BT. Scribe visible.
28" Cedar Stump, S07E, 25.0' (rec. S08-1/4E, 25.1')
no marks, 1952 BT.
New BT's- 7" Fir, S35W, 8.3'. Scribed/Painted red.
18" Cedar, N54W, 33.5'. Scribed/Painted red.
Drove R.R. spike in side of 28" Cedar stump, 1952 BT.
Note - Set metal fence post, with survey attention sign wired to,
beside brass cap. Painted all BT's red. Corner lies on
North slope approx. 75' South of small creek.

167

North West Corner Section 3 (Closing Corner)
Found - 1945 G.L.O. Brass Cap set firmly in the ground.
24" Fir stub, S07E, 18.1' (rec. S11-1/4E, 17.2)
1881 BT. Scribe visible. Ren.#105
40" Fir, S64W, 24.5 (rec. S62W, 25.1') 1881 BT. Scar Visible.
No Rec. 6" Fir, N08W, 29.5'. Scar Visible.
Note - Set metal fence post, with survey attention sign wired to,
beside cap. Painted all BT's red. Corner lies on north-
west slope approx. 150' from dirt road.

168

Northwest Corner for DLC #54
Found - 23" now 39" dia. D. fir with a fully healed single blaze, opened
and scribing found "22S R8W" bears N.9¼°W., 142.0 ft. (Rec.
N.9¼°W., 143.9 ft. is a slope dist.) 1964 resurvey BT
6" now 12" dia. 3 ft. high D. fir stump with a fully healed single
blaze, opened and scribe found "8" bears S.10½°W., 130.0 ft.
(Brass cap on iron pipe gone, recent logging in area.)
Set - A DCSO brass cap on a 1 3/8" O.D. X 32" I.P., protrudes 5" above
ground and marked "Douglas County Surveyors T22S S28 | C 54
R8W 1986".
Monument set from 1964 BLM BTs at record bearing and distance to
SW BT and rec. bearing and a slope dist. to NW BT. Position
falls in old wire woven fence and wood post uncovered. Wire
orientated North-South.
New Accessories:
Boat spike set in top center of 12" dia. 3 ft. high D. fir stump.
(SW BT) stamped "DCSO 1986" bears S.10½°W., 130.0 ft.
21" dia. D. fir double blazed and scribed "NW DLC 54 CS BT" bears
N.29½°E., 155.0 ft.

169

Witness corner for Sections 27 and 28.
Found - A 1961 DCSO 2½" brass cap on a 1½" I.P. protruding 18" above
ground. (remarked 1962 by BLM). Ren. #58
Orig. 36" now 54" dia. D. fir with bark scribing visible "28 S"
and a H chopped in bark facing BC/I.P., bears S.58½°W. 18.7 ft.
to center. (Rec. orig. S.54°W., BLM S.58½°W., 17.2 ft. dist.
is a face measurement.)
Southeast BT is gone, a slight depression found at record bearing
and distance.
8" fir now a 12" dia. 1 ft. high D. fir stump bottom of blaze
evident No scribing found, bears N.34½°E., 12.2 ft. (agrees
with record)
New BTs - 6" dia. D. fir double blazed and scribed "WC S27 CS BT" bears
S.17°E., 3.9 ft.
8" dia. D. fir double blazed and scribed "WC S27 CS BT" bears
N.10°E., 11.5 ft.
9" dia. D. fir double blazed and scribed "WC S28 CS BT" bears
N.31°W., 12.1 ft.
Corner lies on top, near east end of a east-west ridge.

L)?<?>•

Les Roberts P.L.S. 1039
For:International Paper Co.
June 1986
M 102 - 18

Douglas County Surveyors Office
Randall W. Smith
Stephen J. Flause
October 7, 1986
C.S. 62/37