Douglas County Surveyor's Record of Government Corners Renewed

22 T. S. 9 R. W. W. M.

KORE-CHAPMAN CO. EUGENE, ORE. 81084

Nov. 20, 1936 Nov. 9, 1936
A. Royer A. Royer
Will Gerrison Will Gerrison
Bert Lane Bert Lane D.C.S.
Fred Schindler Fred Schindler
Witnesses Witnesses
Vol. 4 Pg. 32 CS 23/24

1 S.W. COR. D.L.C. 39
Set from orig. Hemlock B.T. to the N.E. Set 3" x 3" x 36" Fir post for Cor., from which
A 15" Maple, bears S.71½°W., 18.2 ft. dist. marked D.L.C. 39 B.T.

2 SEC. COR. TO 5 & 8 #107
Set from Alder Orig. B.T. which is now dead and about to fall. 1½" x 36" pipe for cor., from which
A 20" Fir, bears S.52½°E., 48.5 ft. in dist. marked C.S. S.8. B.T. found and cut out original B.T.
Fir S.5°W. 19.8 ft. in dist.

RE-RENEWED, SEE CORNER NO.

Nov. 21, 1936 Vol. 4 Pg. 32

3 COR. AT INTERSEC. N. LINE D.L.C. 38 & LINE BET. SEC. 7 & 8.
Cross on rock from which
18" Fir, bears N.58°W., 17.1 ft. dist. marked D.C.L. S. 7 B.T.
"FD. COR. SEE STATE HWY (CS. A-4)"

4 N.E. COR. LOT 12 SEC. 8
Cor. at intersec. sec. line bet. 5 & 8 and W. line D.L.C. 39. 3" x 3" x 30" post. from which #110
40" Burly Maple, bears N.43°E. 23.5 ft. Marked L 12 B.T.
20" Alder, bears S.40°E. 32.5 ft. dist. Marked L 12 B.T.

RE-RENEWED, SEE CORNER NO.

A. Royer Will Garrison Bert Lane Fred Schindler R. J. Andrews

5 At the Corner of SECS. 35 & 36. T.21S. R.9W. W.M. & SECS. 1 & 2 T.22S. R.9W.
I found all witness trees in place, but the Hemlocks, which are the trees for Secs. 35 & 36 have been killed by fire. I therefore set a Hemlock post 4" long, 4" diam. 18" in ground, from which
A Hemlock 9" dia. bears N.47½°W. 34 ft. dist. Marked T.21S. R.9W. Sec 35 B.T. Eng. 722
A Fir, 36" dia., bears N.60°E. 65 ft. dist. Marked T.21S. R.9W. Sec. 36 B.T. Eng. 722

H. T. Lewis Engr. #722 Oct. 18, 1939

6 CORNER SECS. 15-16-21-22
At the corner of Sections 15-16-21-22, T.22S., R.9W. W.M. I found the S.W. witness tree in good shape & evidences of the N.W. & N.E. trees, but no evidence of the corner post. I therefore set a Fir post 4' long, 4" dia., 18" in ground, from which:
A Fir 10" in dia., bears S.84°E. 11 ft. dist. marked T.22S., R.9W., Sec. 22 B.T. 722
A Fir 16" in dia., bears N.45°E. 9 ft. dist. Marked T.22S. R.9W. Sec. 15 B.T. 722
A Fir 13" in dia., bears N.40°W. 54 ft. dist. Marked T.22S. R.9W. Sec. 16 B.T. 722

RE-RENEWED, SEE CORNER NO. 62

H. T. Lewis Engr. #722 Sept. 28, 1939

Rec. By H. L. Eppstein

7 COR. SECS. 16-17-20-21
At the cor. of Secs. 16-17-20-21. T.22S. R.9W. W.M., I found the S.W. witness tree in place, also faint marks on the rotten bark of the 60" Fir described in the Government notes, but no evidence of Cor. post. I therefore set a Fir post 4' long, 4" in diam., 14" in ground from which
A Maple, 14" in dia. bears N.31°E. 33 ft. dist. Marked T.22S. R.9W. Sec. 16, B.T. 722
A Fir, 30" in dia. bears N.14" W. 30 ft. dist. Marked T.22S. R.9W. Sec. 17 B.T. 722
A Hemlock, 8" in dia., bears S.50°E. 7 ft. dist. Marked T.22S. R.9W. Sec. 21 B.T. 722

RE-RENEWED, SEE CORNER NO. 22

H. T. Lewis Engr. #722 Sept. 29, 1939

Wilford N. Haines
June 6, 1956.
C. S. File No.
42/153.

8 Northeast corner of the Job Hatfield D. L. C. No. 41.
Found stake and 2 original B.T.s:
44 inch D. Fir (dead), N.50°W., bark scribed.
40 inch D. Fir (now a stump) S.08°E., with good scribing.
Drove a 36 inch angle iron with brass cap at corner point inscribed - "Survey point - Wilford N. Haines # 239".
Nailed a brass cap to each orig. B.T. inscribed "Survey point - Wilford N. Haines # 239".