

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 22 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97881

Found ok 8/91  
H. Wilcox #113-60

30

Sec. Cor. to Secs. 12 & 13, T22-9W. & Secs. 7 & 18, T22-8W.  
Found - Brass Cap set in 1931 in good condition.  
32" Maple N.12°E. 38.9 ft., good axe scars visible.  
30" Fir S.85°W. 35.0 ft., scars plainly visible.  
Tree partially dead.  
30" Maple N.40°W. 48.2 ft. Tree in poor condition, but  
no other trees available to N. W.  
The S. E. Bearing Tree is gone, no trace found.  
New BT's: 14" D. Fir S.45°E. 102.7 ft. Mkd: T22S R8W S18 CS BT.  
15" D. Fir S.64°W. 55.5 ft. Mkd: T22S R9W S13 CS BT.

Sept. 11, 1963

Township Corner -

	T21S		
R9W	S 36	S 31	R8W
	S 1	S 6	
	T22S		

31

Found - Brass Cap set by Cadastral Survey of 1945, bulldozed  
out & buried in ground, lying across corner position.  
38" Fir Stump N.12½°W. 12.5 feet.  
48" Fir Stump S18½°W. 163.0 ft., axe marks in bark "S1 BT".  
Burned Remnants of big Fir Stump S.21½°E. 18.5 ft.  
38" Fir Stump N.36°E. 107.6 ft.  
36" Fir Stump N.37°E. 34.3 ft.  
No scribe marks found.  
No trace of other old BT's.  
Reset - Gov't. Brass Cap in proper position.  
Rescribe - 38" Fir Stump N.12½°W. 12.5 ft., "T21S R9W S36" (broke scribe)  
No live trees available.

Found ok 8/91  
H. Wilcox #113-60

32

¼ Section Corner to Sec. 12, T22-9W. & Sec. 7, T22-8W.  
Found - Dead Fir Snag, 22" diam. & approx. 35 ft. high.  
Dead Fir Snag, 18" diam., & approx. 20 ft. high, ¼ N.50°W.  
13.2 ft., opened & found good scribing, "BT".  
Rotten Piece of Fir Stump S.30°E. 7.2 ft. Too far gone  
to find any markings.  
Set - Wit. Corner 6 ft. North of ¼ Corner.  
Brass Cap for Cor. Mkd: County Surveyor's Office, 1963  
T22S R9W W.C. ¼ S12/S 7 R8W 6 ft. S. to Corner.  
New BT's: 27" Fir Stump N.40°W. 19.0 ft. Mkd: W.C. ¼ S12 CS BT.  
27" Fir Snag S.84°E. 31.6 ft. Mkd: W.C. ¼ S 7 CS BT.  
No live trees available.

33

Section Corner to Secs. 1 & 12, T22-9W. & Secs. 6 & 7, T22-8W.  
Found - 1" Iron Pipe extending 18" above ground surface.  
45" Dead Fir N.45°W. 4.0 ft., bark scribing(not orig.) fd.,  
"T22S R9W S1", no orig. scribng. fd., bark badly burned.  
60" Dead Fir N.32°E. 15.8 ft., bark scribing(not orig.) fd.,  
"T22S R8W S6BT". No orig. scribing found, bark badly  
burned, yellow tag dated 4/27/54.  
24" Fir Stump S.42°W. 27.7 ft., stump cut low, no mks. found.  
No trace of S.E. BT.  
16" Fir Snag, about 10' high, scribed in wood, T22SR8W S7"  
S.77½°E. 35.3 ft., yellow tag dated 4/27/54.  
20" Fir Stump & 5 ft. high, bark scribing found "T22SR9WS12BT".  
S.65°W. 27.0 ft. (not orig. BT) yellow tag dated 4/27/54.  
Set - Brass Cap alongside I.P. & Mkd: County Surveyor's Office, 1963  
R9W S 1 S 6 R8W  
T22S S12 S 7  
Rescribe in bark, 45" Dead Fir N.40°W. 4.0 ft. Mkd: T22S R9W S1 CS BT.  
No live trees available.

Milo E. Godfrey, Deputy County Surveyor  
Wm. Stoffel & Mike Stone  
September 1963  
C. S. File No. 52/14