

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 22 S. T.S. R. 9 W. R.W.W.M.

ROCK-CHAPMAN CO., EUGENE, ORE. 21881

#85 34

Milo E.  
Godfrey  
& Crew  
Oct. 3, 1963  
C.S. File  
No. 52/14

Meander Corner Right Bank Sec. 13, T22-9W. & Sec. 18, T22-8W.  
Found - Alder, now 18", mkd. in 1931 for Wit. Cor. to Meander Corner, shows good scars.  
27" White Oak S.40°W. 45.5 ft., cut open & fd. good scribe mkd. "T".  
No trace of N. E. Tree.  
Set - At true proportionate point for M. C., according to 1931 survey, 17.8 ft. N. of Wit. Corner  
Brass Cap Mkd: County Surveyor's Office, 1963  
T22S M. C. R9W S13/S18 R8W  
New BT's: 12" Alder S.24°E. 14.4 ft. Mkd: M.C. S18 CS BT.  
16" White Oak S.37°W. 35.5 ft. Mkd: M. C. S13 CS BT.  
Angle at S.W. Corner of concrete Block Wall bears N.13°W. 150.5 ft. Wall along edge of yard around house.

85.5' per FIELD NOTES 5/18/82 J.R.

RE-RENEWED SEE CORNER NO.

Milo E.  
Godfrey & Crew  
Mar. 20, 1964  
C.S. File  
No. 52/14

1/4 Corner to Sections 7 and 18.  
Found - 12" Fir Stump N.17 1/2°E. 13.2 ft., previously opened, good scribing visible on old face "1/2S". Other BT. not found. (See M 27-33)  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964 T22S R9W 1/4 S 7 S 18  
New BT's: 5" Hemlock N.23 1/2°W. 26.1 ft. Mkd: 1/4 S7 CS BT.  
26" D.Fir N.32°E. 73.0 ft. Mkd: 1/4 S7 CS BT.  
No trees near in Section 18.

35

Wilford N. Haines  
For L. & H. Lumber  
July, 1967  
Map File M 34 - 29

~~S.E. 1/16 Section 4.  
Found - Iron, N. 87° 28' E. 90.2 ft.  
2 Trees which looked like BT's, did not open.  
Set - 5/8 Steel Rod, from which:  
BT: 6" Fir N. 60° W. 12.6 ft.~~

36

~~C.E. 1/16 Section 4.  
Found - 1. Iron 97.6 ft. from corner.  
Set - 5/8" Steel Rod, from which:  
Scribed: 12" Inc. Cedar S. 51° W. ?~~

37

Section Corner to Sections 14 - 15 - 22 - 23.  
Found - Orig. BT's: N.19°W. (down, good scribing)  
N.65°E., now 36, rescribed on bark.  
S.84°E., gone.  
S.19°W., now 48"  
Set - 5/8" Steel Rod, from which:  
Scribed 4" Fir N. 51° W. 23.0 ft.

38

RE-RENEWED SEE CORNER NO. 52

Wilford N. Haines  
For: A. Sagaberd Est.  
July, 1967  
Map File M 34 - 31

S 1/16 to Sections 14 and 15.  
Set - 5/8" Steel Rod, from which:  
Scribed: 26" Fir S. 43° W. 16.1 ft.  
28" Fir S. 75° E. 101.9 ft.

39

1/4 Corner to Sections 14 and 23.  
Found - Rock & Remains of old BT's.  
Set - 5/8" Steel Rod, from which:  
Scribed: 13" Fir S. 34° E. 31.3 ft.  
18" Fir N. 55° W. 135.8 ft.

40

E. 1/16 to Sections 14 and 23.  
Set - 5/8" Steel Rod, from which:  
Scribed: 28" Fir N. 4° W. 86.5 ft.  
20" Fir S. 19° W. 8.6 ft.

41