

Douglas County Surveyor's Record of
Government Corners Renewed

T. 22 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

63

1/4 Corner to Sections 26 and 35.

Found - Orig. 30", now 36" Fir, down, N. 8° E. 13.2 ft., prev. opened and shows "S" scribe and axe notch.

Orig. 24", now 34" Fir Stump, S. 2° W. 47.5 ft., shows good scar, we do not open.

Set - Brass Cap at Cor. Mkd: County Surveyors T 22 S R 9 W
Office 1/4 S 26
1968 S 35

New BT's: 14" Chinquapin S. 71° W. 46.7 ft. mkd. 1/4 S35 CS BT.
6" D. Fir N. 58° E. 37.8 ft. mkd. 1/4 S26 CS BT.

Note - This corner lies on bench sloping S.W. in dense rhododendron.
2/28/68

Tracy &
Crew
C. S. File
No.
54/60

Fd. by:
R. Luckman
1-13-68
M93-41

64

Township Corner common to Sections 31 & 36, T22-9& 10 W.

Original - Stone 6x14x16" in 4'x2' mound of stone, found in place, from which a:
FOOK PER BAKER
APRIL 87 C.S. 63/50
M104-19

Ridge top, NW and SE, bears North 300 lks.; now in place.

Ridge top, NW and SE, bears East 300 lks.; now in place.

Restored - Set 1 1/2" x 36" galv. iron pipe with 3" br. cap mkd:

"Ore.St.Bd. of Forestry T22S R10W R9W S36 S31 S1
T23S R10W 1967 RS359," 30" in ground, alongside
corner stone in mound of rock & from which a:

17" Fir bears N. 73 1/2° E. 20.9 ft. to face; scribed T22S R9W
S31 BT RS 359.

27" Fir bears N. 21° W. 24.5 ft. to face; scribed T22S R10W
S36 BT.

Set - 4"x4"x72" white painted cedar post 1.6 ft. W. of corner pipe.
Ore.St. Forestry Dept. metal location poster on 27" Fir BT.

Ore.St.Bd. of Forestry
Arnold G. Gibson
Oct. 26, 1967
C. S. File No. 55/68

65

1/4 Corner common to Sections 31 & 6, T22 & 23S, R. 9W.

Original - Post, now missing, from which a:

20" Fir bears North 18 lks.; now 26", face opened, knife
scribes 4S visible at correct age.

24" Fir bears South 23 lks.; now 28" snag, knife scribes
1/ - S BT visible at correct age.

Creek, course North, bears East 325 lks.; now in place.

Restored-Set- 1 1/2" x 36" galv. iron pipe with 3" br. cap mkd: "Ore.St.
Bd. of Forestry 1/4 S31 S6 1967 RS359", 30" in ground,
and from which a:

20" Hemlock bears S. 69 1/2° W. 42.2 ft. to face; scribed
1/4 S6 BT RS359.

Set - 4"x4"x72" white painted cedar post 1.2 ft. S. of corner pipe.

FO OK
1/68
J. BYRON
CS 54/60

66

Closing Corner for Sections 9 and 16.

Found - 1 1/2" I.P. & Brazed Cap at Corner point & 1894 Orig. BT's:

8", now 30" W. Fir sawed stump, N. 65° E. 53.5 ft., open top
of stump and find reverse scribe marks.

30", now 48" Fir shattered stump, S. 40° W. 121.4 ft., showd old scar.

8", now 28" W. Fir, snag, N. 21° W. 116.4 ft. (Rec. 97.7),
previously opened & shows "S9" scribe.

At Corner point in place of unrecorded Pipe;

Set - Brass Cap at Cor. Mkd: County Surveyor's T 22 S R 9 W
(Reset old pipe alongside) Office CC S 9
1968 S 16

New BT's: 7" Alder S. 45° W. 57.0 ft. mkd. T22S R9W S16 CC CS BT.

13" D. Fir N. 84° W. 68.2 ft. mkd. T22S R9W S 9 CC CS BT.

This corner lies on gentle E. slope in old logged-off area.

V. R.
Tracy &
Crew
6/24/68
C. S. File
No. 54/60

67

Closing Corner, Township Corner for Sec. 1, T23-10 & Sec. 6, T23-9W.

Set - Ore.St.Bd. of Forestry 1 1/2" x 36" Galv. I.P. with Bronze Cap.

26" Fir N. 72 1/4° E. 27.5 ft.

42" Fir S. 38 1/4° W. 12.8 ft. (RS359) Yellow Metal Location Poster.

46" Fir S. 60° E. 34.8 ft.

White Painted Cedar Post bears N.W. 1.0 ft.

Ore.St.Bd. of
Forestry
M 36 - 32

March 15, 1968

SEPT '68