

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 22 T. S. R 9 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

89

Section corner for Secs. 25, 26, 35 and 36
 Found - Recently set 1 1/2" Iron pipe with brass cap set by Luckman Surveying.
 Orig. 48" fir, now 40" rotting stump. I open and find scribed "T22S R9W S36".
 Orig. 36" fir, now 39" rotting stump. I open and find scribed "T22S R9W S35".
 Set - Since found brass cap did not agree with found original BTs, I Set 1" x 30" Iron pipe with brass cap using record bearings and distances from both BTs. Cap marked "Douglas Co. Surveyor T22S S26 S25 S35 S36 R9W 1982".
 Orig. 48" now 40" fir stump bears S.68°E., 89.1 ft.
 Orig. 36" now 39" fir stump bears S.25°W., 87.8 ft.
 The found brass cap bears N.79 1/2°W., 34.9 ft. from cor. I set.
 New BTs - 12" hemlock scribed "T22S R9W S25 CS BT" in double blaze bears N.72°E., 48.5 ft.
 10" fir scribed "T22S R9W S36 CS BT" in double blaze bears S.61°E., 33.8 ft.
 10" hemlock scribed "T22S R9W S35 CS BT" in double blaze bears S.16°W., 42.3 Ft.
 15" fir scribed "T22S R9W S26 CS BT" in double blaze bears N.81°W. 18.3 ft.
 Douglas County BT tags on all trees. 12/14/82

Gregory Quibell, Deputy
 Douglas County Surveyors Office
 John Powell - Randy Smith
 December 10 and 14, 1982
 C.S. 62/1

90

1/4 Corner for Sections 25 and 36.
 Found - Recently set 1 1/2" Iron pipe with brass cap firmly set. Brass cap proportioned by Luckman surveying in November 1982.
 Orig. 10" now 38" fir with old G.L.O. tag and good scar. I open and find scribed "1/4 S" 14" deep in the tree. Tree was found alive and well.
 Orig. 36" now 38" fir, down and rotting. Tree appeared to have fallen on its face so I dug hole under tree and opened to find scribed "1/4S".
 Douglas Co. Forest appraisal tag on 21" hemlock. Tag was dated 4-13-54 and was marked = "Approx 40 ft. N 15° W to N 1/4 Cor."
 Set - Since the found brass cap did not fit the orig. BTs, I Set a 1" x 30" Iron pipe with brass cap attached at record bearing & distance from the standing orig. 10" now 38" fir (S.62°W., 37.6 ft.) Bearing & distance to root hole of down 38" fir BT is: S.72°W., 62.0 ft. (Rec. S.77°W., 52.8 ft.) Bearing and distance to found Forest Appraisal tag is: S.14°E., 48.0 ft. (Rec. approx. 40 ft. S.15°E.)
 Found brass cap bears N.13°E., 36.1 ft. from brass cap I set.
 New BTs - 21" hemlock scribed "1/4 S36 CS BT" in double blaze bears S.14°E., 48.0 ft.
 11" fir scribed "1/4 S36 CS BT" in double blaze bears S.88°W., 36.6 ft.
 8" fir scribed "1/4 S25 CS BT" in double blaze bears N.41°W., 12.9ft
 Douglas Co Surveyor Office BT tags placed on all trees. 12/10/82

91

1/4 Corner common to Secs. 35, & 36.
 Set - 1 1/2" Galv. Pipe w/B.C. mkd. T 22 S R 9 W 1982 W 1/4 35|36 PLS 1254, at proportionate distance, after thorough search
 found - A "U.S. Dept. of Int." tag on a 20" maple bears south, 52.6-ft. - tag states: Approx. 1/4 cor. S 35 T 22 S R 9 W Date 1-3-45.
 New BTs- 13" D. Fir bears N.28°W., 10.9-ft. blazed & scribed on the south-west side of tree: W 1/4 Sec.36 T 22 R 9.
 14" D. Fir bears S.63°W., 31.75-ft. E 1/4 S 35 T 22 R 9. 1/83

92

East 1/4 Corner of Sec. 36 only.
 Set - 1 1/2" Galv. Pipe w/B.C. mkd. R 9 W E 1/4 36| R 8 W 1982 PLS 1254.
 New BTs- 11" D. Fir bears N.30°E., 15.1-ft.
 14" D. Fir bears N.58°W., 0.6-ft. 1/83

Rockne R. Luckman
 PLS #1254
 For: International Paper Co.
 Jan. 13, 1983
 M 93 - 41