

Douglas County Surveyor's Record of
Government Corners Renewed

T. 22 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91891

Lawrence B. Olsen
PLS#655
For International
Paper Co., Mar. 17, 86
M 100 - 65

N.E. CORNER LOT 12 SEC. 8.
Set - 5/8" I.R. With plastic cap marked "P.L.S. 655".
From which a 2" I.P. bears S 47° 47' 06" W, 62.56 ft.

REN#4

110

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
June 10, 1992
C.S. 64/26

Sec. Cor. for 7, 8, 17 and 18
Found - 3 1/4" BLM brass cap on a 2 1/2" O.D. Iron pipe, leaning 1 ft. west.
BC/IP 1 ft. under ground. (1970)
15" now 18" dia. 2 ft. tall D.Fir stump with a fully healed
single blaze, bears N.83 1/2°E., 77.9 ft. (agrees w/rec) BLM
23" now 24" dia. 3 ft. tall D.Fir stump with a fully healed s:
blaze, bears S.56°E., 67.3 ft. (agrees w/rec) 1970 BLM
12" now 24" dia. 1 ft. tall D.Fir stump, we opened blaze and
found scribing "W" bears S.48 1/2°W., 48.2 ft. (agrees w/rec) BLM
15" now 24" dia. 3 ft. tall D.Fir stump with a fully healed single
blaze bears N.54 1/2°W., 44.2 ft. (agrees w/rec) BLM
5/8" I.Rod from M 69-36, we agree with record distance of 327.6 ft
Bearings not checked.

111

Set - BLM brass cap, iron pipe returned to plumb position, 1 ft.
below ground.

New Accessories:

- 9" "+" chisled in sandstone cut bank, 3 ft. above road, along
east side of gravel road, bears S.87 1/2°E., 41.9 ft.
- 6" "+" chisled in sandstone cut bank, 2 ft. above road, along
east side of gravel road, bears S.27°E., 38.6 ft.

Metal witness post & sign 4 ft. east of corner. Area around corner is
clearcut. No reasonable trees to scribe.

6/10/92

1/4 Corner for Section 6 only

112

Found - No trace of monument.
22" D.Fir stump 3 1/2 ft. tall, S.27°E., 34.3 ft. (Rec. S.31 1/2°E)
bark removed, sheet metal cap on top.
30" D.Fir stump 2 1/2 ft. tall, N.60°E., 22.8 ft. (Rec. N.58°E)
bark removed, sheet metal cap on top.
Set - 30" x 2 1/4" Iron post with 2 1/2" brass cap, top 5" above mound of
stone at intersection of record distances from found
accessories. Cap mkd:

T 22 S
R 10 W R 9 W
1/4 S 6
1992 RPLS 811

No new accessories marked.

Corner is located in a newly logged BLM clear-cut (Mill Creek ridge
timber sale Unit #4). It is on very steep (80%) southwest slope about
400 ft. northeast of Little Mill Creek.

6/26/92

113

Steven P. Ness
L.S. #811
June 26, 1992
C.S. File 63/138