

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 22 S. T. S. R. 10 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W.  
Byron.  
For Doug. Co.  
Park Dept.  
Dec. 1962  
C.S. 52/86  
RM 1 - 34  
M 22 - 16

Points on line, Section Line between Sections 13 and 24. 27  
Set Brass Cap on high bank Mkd: County Surveyor's Office, 1962, S13 T22SR10W  
from which: 10" Myrtle bears N.28°W. 49.0 ft. scribed S13 CSS24.  
(Set 7' Steel Fence Post at B.C.)

Point on line - Set 4' Section of Steel Fence Post 1.0 ft. above ground,  
top of low bank from which:  
12" Myrtle bears S.42°W. 31.6 ft. scribed S24 CS BT.  
26" Myrtle bears N.25°E. 4.5 ft. scribed S13 CS BT.

Bruce R.  
Rogers, Dep.  
and Crew  
April, 1965  
C. S. File  
No. 54/1

Witness Corner to Section Corner of 28  
Sections 32 & 33 only, T21-L0W.  
Found - GLO Brass Cap at Corner mkd. 1919.  
16" Fir, now 30" Snag, N.65°W. 37.6 ft., chopped out,  
found good scribing "R".  
No trace of N. E. BT. 37  
Set - Brass Cap 34 ft. S. of Corner Mkd: County Surveyor's Office, 1965  
T21S R10W S 32/S 33  
T22S (35' N. to Cor.)  
New BT's: 26" Fir N.17°E. 6.8 ft. Mkd: W.C. T22S R10W S5 CS BT.  
24" Fir S.75°E. 15.4 ft. Mkd: W.C. T22S R10W S5 CS BT.

Closing Corner for Sections 22 and 23. 29  
Original: Stone 20"x16"x12" (found, 4 notches on N. 2 notches on E.  
& CC on NE faces) from which a: - SEE REN. #30, below  
36" Maple bears N.32°W. 72 lks.; now rotted uproot, sprouts growing  
out of trunk.  
12" Maple bears N.54°E. 107 lks.; remains of rotted stump alongside of  
five foot diam. clump, Orig. tree lost downstream.  
4" Vine Maple bears S.15°W. 22 lks.; missing, sprouts in area.  
Trail bears N. 50 lks.; in place. - Mill Ck bears N. 1.50 chs.; in place.  
Mill ck. bears East 4.30 chns; in place.  
Beginning of ascent bears West 70 lks.; in place.  
Restored: SET 4"x4"x72" white painted Cedar Post 2.0 ft. S. of corner  
stone in mound of rock, and from which a:  
36" Hemlock bears N.20½°W. 61.9 ft.; scribed T22S R10W CC S22 BT RS359.  
9' x8' x 4' high boulder bears N. 80° W. 25.7 ft.; scribed XBO.  
24" Maple bears N. 73½° E. 51.9 ft.; scribed T22S R10W S23 CC BT by  
SET 4"x4"x72" white painted (See Ren. No. 12) Allen G. Terry, April 1956.  
Cedar Post FOR TRUE COR BEARS S 02°00'01"E 58.5ft (135-48)

Ore. St. Bd. of Forestry  
Arnold G. Gibson  
March 30, 1966  
C. S. File No. 51/349

James W.  
Byron, Co.  
Surv.  
7/20/66  
C. S. File  
No. 54/1

Cl. Corner to Sections 22 and 23.  
Found - Corner Stone at Corner, as recorded & Orig. N. W. BT, now  
face down, no scribing found.  
4" x 4" Post, as set in Ren. #29, above.  
No trace of Orig. N.E. BT. May have been washed out by Mill Creek.  
All BT's. as recorded by Gibson, 1966. All Ok, Rock B.O. O.K.  
Set - Brass Cap alongside Corner Stone mkd: County Surveyor's T 22 S R 10 W  
Office, 1966 CC S 22 / S 23  
S 27

Note - Call North to Mill Creek Checks O. K.

July 20, 1966

MICROFILM TO HERE 10/67

Arnold G. Gibson  
Ore. St. Bd. of Forestry  
Dec. 30, 1967  
C.S. File No. 55/64  
M 35 - 48

Section Corner common to Sections 27 and 28.  
Orig. - 20"x16"x8" Stone (fd. in place, X on top, 2 notches visible on SW  
side & 3 notches on SE side) from which a:  
4" Fir bears N.78°W. 80 lks., now 72", scribes S28 vis., BT face  
covered (dist. 76.0 ft.)  
16" Cedar bears S.66°E. 30 lks.; now 20" x 6' stub, portions of  
scribes R10 W, S27, remaining (dist. 24.2 ft.)  
36" Fir bears S.53°W. 200 lks.; missing (steep sidehill, possible slide.)  
Restored - Set 1½"x36" gal. iron pipe with 3" br. cap mkd. "Ore. St. Bd. of  
Forestry T22SR10WS22S28S27 1967 RS359", 34" in ground on  
south side of original stone, & from which a:

(continued over)

27

28

29

30

31