

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 S. T. S. R. 10 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

72" Fir(Orig.) bears N.78°W. 76.0 ft.; scribed RS 359.
19" Fir bears S.62°E. 12.2 ft.; scribed T22S R10W S27 BT.
29" Fir bears N.47°W. 25.3 ft.; scribed T22S R10W S22 BT.

Set- 4"x4"x72" white painted cedar post 0.5 ft. N.50°W. of corner stone.

Oregon State Forestry Dept. metal location poster on 19" Fir BT.
Note - A. G. Terry Cor. bears N.87°54'23"E. 301.15 ft., Ren. #14.

Witness Corner common to Sections 26 and 27.

32

Orig: Sandstone (now missing) from which a:

30" Maple bears S.62°E. 80 lks.; now 69" with rotted butt.
4" Vinemaple bears S.20°W. 12 lks.; now missing.
4" Vinemaple bears N.80°E. 10 lks.; vinemaple clump in place.
6" Vinemaple bears N.85°W. 10 lks.; now missing.

Found line blazes 300 ft. E. of section corner point which is 33 ft. N.

Note - 4" Sq. Post by A. G. Terry bears S.72°14'12"West 97.5 ft. - Ren. #11.

Set - 1½"x36" gal. iron pipe with 3" br. cap mkd. "Ore.St.Bd.of Forestry S23 S27 S26 T22S R10W WC 1967 RS 359", 30" in ground, on south bank of Mill Creek, in mound of rock, & from which a:
36" Maple bears S.34°W. 21.9 ft., to face; scribed WC T22S R10W S27 BT.

33" Fir bears N,83°E. 135.5 ft., to face; scribed WC T22S R10W S23 BT.

69" Maple(Orig.) bears S.62°E. 52.8 ft. scribed RS359.

8'x 4' x 5' Rock bears N.83°E. 65.2 ft.

Set - 4"x4"x72" white painted cedar post 1.3 ft NW of corner pipe.

Ore.St.Forestry Dept. metal location poster on 36" Maple BT.

(True Cor. N.02°51'41"E. 33.0 ft.)

33

¼ Corner common to Sections 22 and 23.

Orig.-5'x5'x4' Stone(in place, 4" x, ¼ S on W. side) from which a:

36" Maple bears N.9°W. 64 lks.; now missing.
10" Maple bears N.20°E. 56 lks.; now 30" maple, rotted in center, orig. axework in bark (dist. 66 lks.).

Rewitnessed: 30" Maple(Orig) bears N.20°E. 43.6 ft.

48" Fir bears S.60°E. 64.2 ft.; scribed ¼ S23 BT.

31" Maple(one of clump of three) bears S.49°W. 57.7 ft., scribed S22 BT RS359.

Ore.St.Forestry Dept. metal location poster on 31" Maple BT S.49°W.

(Set 4"x4"x72" Cedar Post for True Cor. bears S.02°00'07"E. 58.5 ft.)

WHITE PAINTED

34

South ¼ Corner to Section 22.

Set - Ore.St.Bd.Forestry 1½"x36" Gal.Iron Pipe with 3" bronze cap.

24" Cedar N.87½°E. 31.0 ft.

18" Alder N.24½°W. 16.7 ft.(RS 359) YMLP.

4"x4"x72" White Painted Cedar Post SE 1.0 ft.

Note - A.G. Terry ¼ corner point bears N.85°51'30"W. 154.15 ft.(Ren.#13)

North ¼ Corner to Section 27.

34A

¼ Corner reestablished - Set OSBF 1½"x36" Gal.IronPipe - Mound of Rock.

Set - 20" Fir S.56½°E. 38.8 ft. (RS 359)

50" Fir N.76½°W. 31.2 ft.

Y.M.L.P. on 4" Hemlock N.51 ¾° W. 2.1 ft.

W.P.C.P. S.65°E. 2.2 ft., spur ridge C S E West, brs. 51 ft. south.

35

Township Corner common to Sections 31 and 36, T22-9 & 10W.

Original - Stone 6x14x16" in 4'x2' mound of stone, found in place, from which a:

Ridgetop, NW. and SE., bears North 300 lks.; now in place.

Ridgetop, NW. and SE., bears East 300 lks.; now in place.

Restored - Set 1½"x36" galv. iron pipe with 3" br. cap mkd. "Ore.St.Bd. of Forestry T22S R10W R9W S36 S31 S1 T23S R10W 1967 RS359, 30" in ground, alongside corner stone, in mound of rock, and from which a:

17" Fir bears N.73½°E. 20.9 ft. to face; scribed T22S R9W S31.

27" Fir bears N.21°W. 24.5 ft. to face; scribed T22S R10W S36BT.

Set 4"x4"x72" white painted cedar post 1.6 ft. West of corner pipe.

Ore.St.Forestry Dept. metal poster on the 27" Fir BT.

Oregon St. Board of Forestry
Arnold G. Gibson
December 12, 1967 - Filed March, 1968
C. S. File No. 55/64 Map M 35 - 48

Ore.St.Bd. of Forestry
Arnold G. Gibson
Oct. 26, 1967
C. S. File No. 55/68

BOOK PER BAKER
APRIL 17 1964
CS. 63/50