

Douglas County Surveyor's Record of
Government Corners Renewed

T. 22 S. T. S. R. 10 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

SECTION 18 EAST SIDE

1/4 Corner common to Sections 17 and 18. SEE CORRELATION REPORT - C.S. 55/101 51 11/18/64 U.S.
Orig. - 12'x 30' bluff (1/4 + S visible at corner point) from which a:
4" Fir bears S.18°E. 60 lks.; now 25" stump, face closed
4" Fir bears S.48°W. 20 lks.; missing, slide rock.
Rewitnessed - Set - 4" x 4" x 72" white painted Cedar post 2.0 ft.
S.30°E. of corner point, from which a:
18" Fir bears S.58°W. 28.5 ft.; scribed 1/4 S18 BT RS 359.
9" Fir on spur top, course S.12°W., bears N.82°E. 93.1 ft.;
scribed 1/4 S17 BT.
Ore.St.Forestry Dept. metal location poster on 18" Fir S58W 28.50 ft.

Section Corner common to Sections 17 - 18 - 19 - 20. 52
Orig. - Sandstone 20x18x8" (now missing, falls in clear cut area),
from which a:
4" Fir bears N.88°E. 50 lks.;, now 30", face closed on E-W ridge top.
6" Cedar bears S.69°E. 40 lks.; missing, in 1964, prior to logging.
Jerry Phillip's found windfall stub with scribes S/S (See
(affidavit in C.S.File 51/349)
4" Cherry bears S.87°W. 30 lks.; missing.
4" Fir bears N.1°W. 50 lks.; missing.
Spur ridge, course E., bears North 20 lks.; in place.
Set - 1 1/2"x36" galv. iron pipe with 3" br. cap mkd: Ore.St.Bd.ofForestry
T22S R10W S17S18S19S20 1968 RS 359", 34" in ground,
2' South of rock bluff 12' high, course E-W, & from which a:
30" Fir(Orig.) bears N.88°E. 33.0 ft.; scribed RS 359.
7" Fir(on ridge top, course E., & 1'E. of above bluff, now
running N-S) bears N.41°E. 12.7 ft.; scribed T22S R10W S17 BT.
14" Fir stump bears S.61°W. 28.6 ft., scribed T22S R10W S19 BT.
30" Fir stump bears S. 9° E. 47.6 ft.; scribed T22S R10W S20 BT.
7" XBO in above bluff bears N.23°W. 2.0 ft.
Set 4 x 4 x 72" white painted Cedar post 5 ft. S.42°W. of corner pipe.
Ore.St.Forestry Dept. metal location poster on 30" stump S9E 47.6 ft.
Also ELM poster on 30" fir (orig.) N.88°E. 33.0 ft.

Section Corner common to Sections 34 and 35, T22 & 23 S., R.10W. 53
Original - Stone 5'x4'x8"; found with 4" X, 8 in. from the north end
and 4 notches on the west, from which a:
28" Fir bears N.80°E. 12 lks.; now 28" burned windfall,
scribes T S R O B visible.
36" Fir bears S.6°W. 15 lks.; now a 52" windfall.
30" Fir bears N.82°W. 10 lks.; now a 36" windfall.
Stone 3' high bears N.20°W. 30 lks.; now a 30' high bluff in place.
Spur, course N.15°E., bears west 60 lks.; now in place.
Rewitnessed:
Marked 2 notches on the E. of orig. stone 5x4x3 ft., from which:
50" Fir bears N. 6° E. 116.0 ft.; scribed T22S R10W S35 BT RS359.
30' Bluff bears N. 31° W. 15.0 ft.; marked XBO.
Set - 4 x 4 x 72 in. white painted cedar post 2 ft. NW of Cornerstone.
Ore.St.Forestry Department metal location poster on:
50" Fir N. 6° E. 116.0 ft.

1/4 Corner to Sections 14 and 23. FND. OK 8/9/ BY WILCOX 54
M 113-76 A & B
Set - Ore.St.Bd. of Forestry 1 1/2"x36" I.Pipe with 3" Bronze Cap.
36" Maple N.43 1/2°W. 40.6 ft., Yellow metal location poster.
20" Alder S.1 1/4°E. 23.8 ft.(RS359)
White Painted Cedar Post, 4x4x72", North 1.0 feet.

1/4 Corner to Sections 23 and 24.
Reestablished - Set - Ore. St. Bd. of Forestry 1 1/2"x36" I. Pipe with 3" B.C.
24" Hemlock S.12 3/4° E. 36.0 ft. (RS359)
45" Fir N.82 1/2°W. 35.6 ft., Yellow Metal Poster.
White Painted Cedar Post, 4x4x72", N. E. 1.3 feet.

RE-RENEWED CORNER NO. #91 55
10/27/69

SEE M94-51 - SURVEY FOR I.P. Co. 1983 ESTABLISHING THIS
CORNER IS NOW FOR 23 ONLY - REN. #87

Ore.St.Bd. of Forestry
Arnold G. Gibson
E.D. Kucera, Transitman
C.S. File No. 55/101

Dec. 1968

Ore.St.Bd. Forestry
Arnold G. Gibson
12/68 C.S. File 55/101

Ore.St. Board of Forestry
Arnold G. Gibson
10/27/69 Map M 38 - 59