

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 10 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Oregon State Department of Forestry - Arnold Gibson
Charles W. Cook, Engineer
Redding, Graham, Bodewig
May 30, 1972
C. S. File 55/233

Oregon State Board of Forestry
Arnold Gibson
Charles Cook
May 30, 1972
C. S. File 55/265

1/4 Corner for Section 16 (West side) 64
Original Stone (missing) from which a:
5" maple, bears N.60°W., 651 lks.; now missing, clump of small maples
in place.
6" Fir, bears N.35°E., 55 lks.; now 36" windfall, scribe T visible.
Set - 1 1/2" x 36" galv. iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY 1/4 S16 1971 RS 359", 34" in ground, and from which a:
26" Fir, bears N.25°W., 17.6 ft. to face; scribed 1/4 S17 BT.
22" Fir, bears N.69 1/2°E., 14.3 ft. to face; scribed 1/4 S16 BT. RS 359.
Set - 4" x 4" x 72" white painted Cedar post 2.0 ft. North of corner pipe.
Oregon State Forestry Department metal location poster on 26" Fir BT
N.25°W., 17.6 ft. #105
5/30/72

Closing Corner common to Sections 30 & 31. 65
Original Stone 36" x 20" x 10" (in place, CC on west, 5 notches on north,
and 2 notches on east) from which a:
8" Fir, bears N.58°E., 60 lks.; now 23" in place, face grown over
(bearing N.63°E.).
6" Fir, bears S.65°E., 20 lks.; now 29" in place, face grown over.
4" Fir, bears N.46°W., 35 lks.; now missing.
29" Fir, (not recorded) Bears S.75°W., 10 ft.; scribe G exposed,
approx. 18 years old by ring count, #116
Set - 4" x 4" x 72" white painted Cedar post N.80°E., 2.6 ft. from above
stone, from which a:
20" Fir, bears S.33 1/2°E., 44.9 ft. to face; scribed T22S R10W S31 CC BT
23" Fir, (orig) bears N.63°E., 40 ft. to face; scribed RS 359.
Set - 4" x 4" x 72" white painted Cedar post 2.6 ft. N.80°E. of corner stone.
Oregon State Forestry Department metal location poster on 29" Fir BT
(orig) S.65°E., 12.3 ft.
5/30/72

Section corner common to Sections 25 & 36 (East End) T22S R11W. 66
Original 18" x 12" x 18" stone (missing) from which a:
60" Burnt Fir, bears S.59°W., 167 lks.; now 60" snag, in place, scribes
T23S R11W 36 visible.
10" Alder, bears N.41°W., 36 lks.; missing, in slide out.
Set - 1 1/2" x 36" galv. iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY T22S S25 S36 R11W T22S S31 R10W 1971 RS 359", 34"
in ground, in mound of rock, and from which a:
19" Fir, bears N.41°W., 69.0 ft. to face; scribed T22S R11W S25 BT RS 359
35" Fir, bears West 100.8 ft. to face; scribed T22S R11W S36 BT.
Set - 4" x 4" x 72" white painted Cedar post 3.0 ft. N.50°W., of corner
pipe. Oregon State Forestry Department metal location poster on 19"
Fir BT N.41°W., 69.0 ft.
5/30/72

Southeast Township Corner, Section 36 only, T.22-11. 67
Set - 1 1/2" x 36" Iron pipe with 3" bronze cap, 34" in ground, from which
36" Fir, N.22 1/2°W., 59.6 ft. with yellow metal location poster. (RS 359)
21" Fir, N.63°W., 79.7 ft.
Set - 4" x 4" x 72" white painted Cedar post S.25°E., 2.0 ft. 1/21/72

Section Corner for Section 31 only, (SW) T22-10. 68
Original 20" x 12" x 8" stone (in place, no marks visible) from which a:
36" Fir, bears N.73°E., 44 lks.; now 50" rotten snag 30' tall, in
place, no marks visible.
30" Fir, bears S.24°W., 12 lks.; now 28" rotten stub in place, scribes
S31 B Visible.
40" Fir, bears N.55°W., 29 lks.; now missing.
Set - 1 1/2" x 36" gal. iron pipe with 3" bronze cap marked "OREGON STATE BOARD
OF FORESTRY T22S R10W S31 T23S R11W S1 1971 RS 359", 35" in ground
with original stone along side, and from which a:
22" Fir, bears N.42°E., 10.6 ft. to face; scribed T22S R10W S31 BT 359.
33" Fir, bears N.09°W., 10.6 ft. to face; scribed T22S R10W S31 BT.
Set - 4" x 4" x 72" white painted Cedar post 2.7 ft. S:01°W., of corner pipe.
Oregon State Forestry Department metal location poster on 33" Fir BT.

(Duplicate of Ren # 59) 11/22/71